触发器

触发器 [triggers.tekton.dev/v1b TriggerTemplate [triggers.tekto EventLister

触发绑定 [triggers.tekton.dev/v1 拦截器 [triggers.tekton.dev/v1al 集群触发器

集群拦截器 [triggers.tekton.dev/v1alpha1]

触发器 [triggers.tekton.dev/v1beta1]

`triggers.tekton.dev` group

Trigger defines a mapping of an input event to parameters. This is used to extract information from events to be passed to TriggerTemplates within a Trigger.

`v1alpha1` version

▼ spec `object`

Spec holds the desired state of the Trigger

▼ bindings `[]object` required

▼ apiversion `string`

APIVersion of the binding ref

▼ kind `string`

Kind can only be provided if Ref is also provided. Defaults to TriggerBinding

▼ name `string`

Name is the name of the binding param Mutually exclusive with Ref

▼ ref `string`

Ref is a reference to a TriggerBinding kind. Mutually exclusive with Name

▼ **value** `string`

Value is the value of the binding param. Can contain JSONPath Has to be pointer since "" is a valid value Required if Name is also specified.

▼ **interceptors** `[]object`

TriggerInterceptor provides a hook to intercept and pre-process events

▼ **bitbucket** `object`

BitbucketInterceptor provides a webhook to intercept and pre-process events

▼ **eventTypes** `[]string`

▼ **secretRef** `object`

SecretRef contains the information required to reference a single secret string This is needed because the other secretRef types are not cross-namespace and do not actually contain the "SecretName" field, which allows us to access a single secret value.

▼ **secretKey** `string`

▼ **secretName** `string`

▼ cel `object`

CELInterceptor provides a webhook to intercept and pre-process events

▼ filter `string`

▼ overlays `[]object`

CELOverlay provides a way to modify the request body using DeprecatedCEL expressions

▼ expression `string`

▼ key `string`

▼ github `object`

Deprecated old fields below

▼ eventTypes `[]string`

▼ secretRef `object`

SecretRef contains the information required to reference a single secret string This is needed because the other secretRef types are not cross-namespace and do not actually contain the "SecretName" field, which allows us to access a single secret value.

▼ **secretKey** `string`

▼ **secretName** `string`

▼ **gitlab** `object`

GitLabInterceptor provides a webhook to intercept and pre-process events

▼ **eventTypes** `[]string`

▼ **secretRef** `object`

SecretRef contains the information required to reference a single secret string This is needed because the other secretRef types are not cross-namespace and do not actually contain the "SecretName" field, which allows us to access a single secret value.

▼ **secretKey** `string`

▼ **secretName** `string`

▼ **name** `string`

Optional name to identify the current interceptor configuration

▼ params `[]object`

InterceptorParams defines a key-value pair that can be passed on an interceptor

▼ name `string` required

▼ value required

▼ ref `object` required

Ref refers to the Interceptor to use

▼ apiVersion `string`

API version of the referent

▼ kind `string`

InterceptorKind indicates the kind of the Interceptor, namespaced or cluster scoped.

▼ name `string`

Name of the referent; More info: http://kubernetes.io/docs/user-guide/identifiers#names ↗

▼ webhook `object`

WebhookInterceptor refers to an old style webhook interceptor service

▼ header `[]object`

Param declares an ParamValues to use for the parameter called name.

▼ name `string` required

▼ value `object` required

ParamValue is a type that can hold a single string or string array. Used in JSON unmarshalling so that a single JSON field can accept either an individual string or an array of strings.

▼ objectRef `object`

ObjectRef is a reference to an object that will resolve to a cluster DNS name to use as the EventInterceptor. Either objectRef or url can be specified

▼ apiVersion `string`

API version of the referent.

▼ fieldPath `string`

If referring to a piece of an object instead of an entire object, this string should contain a valid JSON/Go field access statement, such as desiredState.manifest.containers[2]. For example, if the object reference is to a container within a pod, this would take on a value like: "spec.containers{name}" (where "name" refers to the name of the container that triggered the event) or if no container name is specified "spec.containers[2]" (container with index 2 in this pod).

This syntax is chosen only to have some well-defined way of referencing a part of an object.

▼ kind `string`

Kind of the referent. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds ↗

▼ name `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ namespace `string`

Namespace of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/namespaces/ ↗

▼ resourceVersion `string`

Specific resourceVersion to which this reference is made, if any. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#concurrency-control-and-consistency ↗

▼ uid `string`

UID of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#uids ↗

▼ **url** `string`

▼ **name** `string`

▼ **serviceAccountName** `string`

ServiceAccountName optionally associates credentials with each trigger; Unlike EventListeners, this should be scoped to the same namespace as the Trigger itself

▼ **template** `object` required

▼ **apiversion** `string`

▼ **ref** `string`

▼ **spec** `object`

TriggerTemplateSpec holds the desired state of TriggerTemplate

▼ **params** `[]object`

ParamSpec defines an arbitrary named input whose value can be supplied by a `Param`.

▼ **default** `string`

Default is the value a parameter takes if no input value via a Param is supplied.

▼ **description** `string`

Description is a user-facing description of the parameter that may be used to populate a UI.

▼ **name** `string` required

Name declares the name by which a parameter is referenced.

▼ **resourcetemplates** `[]object`

TriggerResourceTemplate describes a resource to create

Trigger defines a mapping of an input event to parameters. This is used to extract information from events to be passed to TriggerTemplates within a Trigger.

`v1beta1` version

▼ **spec** `object`

Spec holds the desired state of the Trigger

▼ **bindings** `[]object` required

▼ **apiversion** `string`

APIVersion of the binding ref

▼ kind `string`

Kind can only be provided if Ref is also provided. Defaults to TriggerBinding

▼ name `string`

Name is the name of the binding param Mutually exclusive with Ref

▼ ref `string`

Ref is a reference to a TriggerBinding kind. Mutually exclusive with Name

▼ value `string`

Value is the value of the binding param. Can contain JSONPath Has to be pointer since "" is a valid value Required if Name is also specified.

▼ interceptors `[]object`

TriggerInterceptor provides a hook to intercept and pre-process events

▼ name `string`

Optional name to identify the current interceptor configuration

▼ params `[]object`

InterceptorParams defines a key-value pair that can be passed on an interceptor

▼ name `string` required

▼ **value** required

▼ **ref** `object` required

Ref refers to the Interceptor to use

▼ **apiVersion** `string`

API version of the referent

▼ **kind** `string`

InterceptorKind indicates the kind of the Interceptor, namespaced or cluster scoped.

▼ **name** `string`

Name of the referent; More info: http://kubernetes.io/docs/user-guide/identifiers#names ↗

▼ **webhook** `object`

WebhookInterceptor refers to an old style webhook interceptor service

▼ **header** `[]object`

Param declares an ParamValues to use for the parameter called name.

▼ **name** `string` required

▼ value `object` required

ParamValue is a type that can hold a single string or string array. Used in JSON unmarshalling so that a single JSON field can accept either an individual string or an array of strings.

▼ objectRef `object`

ObjectRef is a reference to an object that will resolve to a cluster DNS name to use as the EventInterceptor. Either objectRef or url can be specified

▼ apiVersion `string`

API version of the referent.

▼ fieldPath `string`

If referring to a piece of an object instead of an entire object, this string should contain a valid JSON/Go field access statement, such as desiredState.manifest.containers[2]. For example, if the object reference is to a container within a pod, this would take on a value like: "spec.containers{name}" (where "name" refers to the name of the container that triggered the event) or if no container name is specified "spec.containers[2]" (container with index 2 in this pod). This syntax is chosen only to have some well-defined way of referencing a part of an object.

▼ kind `string`

Kind of the referent. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds ↗

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **namespace** `string`

Namespace of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/namespaces/ ↗

▼ **resourceVersion** `string`

Specific resourceVersion to which this reference is made, if any. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#concurrency-control-and-consistency ↗

▼ **uid** `string`

UID of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#uids ↗

▼ **url** `string`

▼ **name** `string`

▼ serviceAccountName `string`

ServiceAccountName optionally associates credentials with each trigger; Unlike EventListeners, this should be scoped to the same namespace as the Trigger itself

▼ template `object` required

▼ apiversion `string`

▼ ref `string`

▼ spec `object`

TriggerTemplateSpec holds the desired state of TriggerTemplate

▼ params `[]object`

ParamSpec defines an arbitrary named input whose value can be supplied by a `Param`.

▼ default `string`

Default is the value a parameter takes if no input value via a Param is supplied.

▼ description `string`

Description is a user-facing description of the parameter that may be used to populate a UI.

▼ name `string` required

Name declares the name by which a parameter is referenced.

▼ **resourcetemplates** `[]object`

TriggerResourceTemplate describes a resource to create

TriggerTemplate [triggers.tekton.dev/v1beta1]

`triggers.tekton.dev` group

TriggerTemplate takes parameters and uses them to create CRDs

`v1alpha1` version

▼ spec `object`

Spec holds the desired state of the TriggerTemplate from the client

▼ params `[]object`

ParamSpec defines an arbitrary named input whose value can be supplied by a `Param`.

▼ default `string`

Default is the value a parameter takes if no input value via a Param is supplied.

▼ description `string`

Description is a user-facing description of the parameter that may be used to populate a UI.

▼ name `string` required

Name declares the name by which a parameter is referenced.

▼ **resourcetemplates** `[]object`

TriggerResourceTemplate describes a resource to create

▼ **status** `object`

TriggerTemplateStatus describes the desired state of TriggerTemplate

TriggerTemplate takes parameters and uses them to create CRDs

`v1beta1` version

▼ **spec** `object`

Spec holds the desired state of the TriggerTemplate from the client

▼ **params** `[]object`

ParamSpec defines an arbitrary named input whose value can be supplied by a `Param`.

▼ **default** `string`

Default is the value a parameter takes if no input value via a Param is supplied.

▼ **description** `string`

Description is a user-facing description of the parameter that may be used to populate a UI.

▼ **name** `string` required

Name declares the name by which a parameter is referenced.

▼ resourcetemplates `[]object`

TriggerResourceTemplate describes a resource to create

▼ status `object`

TriggerTemplateStatus describes the desired state of TriggerTemplate

EventListener [triggers.tekton.dev/v1beta1]

`triggers.tekton.dev` group

EventListener exposes a service to accept HTTP event payloads.

`v1alpha1` version

▼ spec `object`

Spec holds the desired state of the EventListener from the client

▼ labelSelector `object`

A label selector is a label query over a set of resources. The result of matchLabels and matchExpressions are ANDed. An empty label selector matches all objects. A null label selector matches no objects.

▼ matchExpressions `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ key `string` required

key is the label key that the selector applies to.

▼ operator `string` required

operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.

▼ **matchLabels** `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **namespaceSelector** `object`

NamespaceSelector is a selector for selecting either all namespaces or a list of namespaces.

▼ **matchNames** `[]string`

List of namespace names.

▼ **resources** `object`

▼ **customResource** `object`

▼ **kubernetesResource** `object`

▼ **replicas** `integer`

▼ **serviceType** `string`

Service Type string describes ingress methods for a service

▼ **spec** `object`

WithPodSpec is the shell around the PodSpecable within WithPod.

▼ **template** `object`

PodSpecable is implemented by types containing a PodTemplateSpec in the manner of ReplicaSet, Deployment, DaemonSet, StatefulSet.

▼ **metadata** `object`

Standard object's metadata. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#metadata ↗

▼ **spec** `object`

Specification of the desired behavior of the pod. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#spec-and-status ↗

▼ **activeDeadlineSeconds** `integer`

Optional duration in seconds the pod may be active on the node relative to StartTime before the system will actively try to mark it failed and kill

associated containers. Value must be a positive integer.

▼ **affinity** `object`

If specified, the pod's scheduling constraints

▼ **nodeAffinity** `object`

Describes node affinity scheduling rules for the pod.

▼ **preferredDuringSchedulingIgnoredDuringExecution** `[]object`

An empty preferred scheduling term matches all objects with implicit weight 0 (i.e. it's a no-op). A null preferred scheduling term matches no objects (i.e. is also a no-op).

▼ **preference** `object` required

A node selector term, associated with the corresponding weight.

▼ **matchExpressions** `[]object`

A node selector requirement is a selector that

contains values, a key, and an operator that relates the key and values.

▼ **key**

`string`

required

The label key that the selector applies to.

▼ **operator**

`string`

required

Represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists, DoesNotExist. Gt, and Lt.

▼ **values** `[]string`

An array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. If the operator is Gt or Lt, the values array must have a single element, which will be interpreted as an integer. This array

is replaced during a strategic merge patch.

▼ **matchFields**
`[]object`

A node selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**
`string`
required

The label key that the selector applies to.

▼ **operator**
`string`
required

Represents a key's

relationship to a set of values. Valid operators are In, NotIn, Exists, DoesNotExist. Gt, and Lt.

▼ **values** `[]string`

An array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. If the

operator is Gt or Lt, the values array must have a single element, which will be interpreted as an integer. This array is replaced during a strategic merge patch.

▼ **weight** `integer`

required

Weight associated with matching the corresponding nodeSelectorTerm, in the range 1-100.

▼ **requiredDuringSchedulingIgnoredDuringExecution** `object`

If the affinity requirements specified by this field are not met at scheduling time, the pod will not be scheduled onto the node. If the affinity requirements specified by this field cease to be met at some point during pod execution (e.g. due to an update), the system may or may not try to eventually evict the pod from its node.

▼ **nodeSelectorTerms**

`[]object` required

A null or empty node selector term matches no objects. The requirements of them are ANDed. The TopologySelectorTerm type implements a subset of the NodeSelectorTerm.

▼ **matchExpressions**

`[]object`

A node selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**

`string`

required

The label key that the selector applies to.

▼ **operator** `string` required

Represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists, DoesNotExist. Gt, and Lt.

▼ **values** `[]string`

An array of string values. If the operator is

In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. If the operator is Gt or Lt, the values array must have a single element, which will be interpreted as an integer. This array is replaced during a strategic merge patch.

▼ **matchFields**

`[]object`

A node selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**

`string`

required

The label key that the selector applies to.

▼ **operator**

`string`

required

Represents a key's relationship to a set of values. Valid operators are In, NotIn,

Exists, DoesNotExist. Gt, and Lt.

▼ **values** `[]string`

An array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. If the operator is Gt or Lt, the values array must have a single element,

which will be interpreted as an integer. This array is replaced during a strategic merge patch.

▼ podAffinity `object`

Describes pod affinity scheduling rules (e.g. co-locate this pod in the same node, zone, etc. as some other pod(s)).

▼ preferredDuringSchedulingIgnoredDuringExecution `[]object`

The weights of all of the matched WeightedPodAffinityTerm fields are added per-node to find the most preferred node(s)

▼ podAffinityTerm `object` required

Required. A pod affinity term, associated with the corresponding weight.

▼ **labelSelector**
`object`

A label query over a set of resources, in this case pods. If it's null, this PodAffinityTerm matches with no Pods.

▼ **matchExpressions**
`[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**
`str`

in
g
required

key is the label key that the selector applies to.

▼ **operator** **s** **tr** **in** **g** required

oper

at
or
re
pr
es
en
ts
a
ke
y's
rel
ati
on
sh
ip
to
a
se
t
of
va
lu
es
.
Va
lid
op
er
at
or
s
ar
e
In,
N
otI
n,

Exists and Does Not Exist.

▼ **values** `[]string`

values is an array of string values

. If the operator is In or NotIn, the values array must be non-empty. If the operator

or
is
Ex
ist
s
or
D
oe
s
N
ot
Ex
ist
,
th
e
va
lu
es
ar
ra
y
m
us
t
be
e
m
pt
y.
Th
is
ar
ra
y
is
re

pl
ac
ed
du
rin
g
a
str
at
eg
ic
m
er
ge
pa
tc
h.

▼ **matchLabels** `object`

matchLab
els is a
map of
{key,value
} pairs. A
single
{key,value
} in the
matchLab
els map is
equivalent
to an
element of
matchExpr

essions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **matchLabelKeys** `[]string`

MatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key in (value)` to select the group of

existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MatchLabelKeys and LabelSelector. Also, MatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysIn PodAffinity feature gate.

▼ **mismatchLabelKeys** `[]string`

MismatchLabelKeys is a set of pod label keys to

select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key notin (value)` to select the group of existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MismatchLabelKeys and LabelSelector. Also, MismatchLabelKeys cannot be set when LabelSelector isn't set. This is an

alpha field and requires enabling MatchLabelKeysIn PodAffinity feature gate.

▼ **namespaceSelector** `object`

A label query over the set of namespaces that the term applies to. The term is applied to the union of the namespaces selected by this field and the ones listed in the namespaces field. null selector and null or empty namespaces list means "this pod's namespace". An empty selector ({}) matches all namespaces.

▼ **matchExpressions** `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string` required

key is the label key that th

e se le ct or ap pli es to.

▼ **operator** `string` required

op er at or re pr es en ts a ke y's rel ati on sh ip to a

set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values**

`[]string`

values is an array of string values. If the operator is In or NotIn, the valu

es
ar
ra
y
m
us
t
be
no
n-
e
m
pt
y.
If
th
e
op
er
at
or
is
Ex
ist
s
or
D
oe
s
N
ot
Ex
ist
,
th
e
va

lu es ar ra y m us t be e m pt y. Th is ar ra y is re pl ac ed du rin g a str at eg ic m er ge pa tc h.

▼

matchLabels

`object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **namespaces**
`[]string`

namespaces specifies a static list of namespace names that the term applies to. The term is applied to the union of the namespaces listed in this field and the ones selected by namespaceSelector. null or empty namespaces list and null namespaceSelector means "this pod's namespace".

▼ **topologyKey**
`string`
required

This pod should be co-located (affinity) or not co-located (anti-affinity) with the pods matching the labelSelector in the specified namespaces,

where co-located is defined as running on a node whose value of the label with key topologyKey matches that of any node on which any of the selected pods is running. Empty topologyKey is not allowed.

▼ **weight** `integer`

required

weight associated with matching the corresponding podAffinityTerm, in the range 1-100.

▼ **requiredDuringSchedulingIgnoredDuringExecution** `[]object`

Defines a set of pods (namely those matching the labelSelector relative to the given namespace(s)) that this pod should be co-located (affinity) or not co-located (anti-affinity) with, where co-located is defined as running on a node whose value of

the label with key matches that of any node on which a pod of the set of pods is running

▼ **labelSelector**
`object`

A label query over a set of resources, in this case pods. If it's null, this PodAffinityTerm matches with no Pods.

▼ **matchExpressions**
`[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**
`string`
required

key is the label key that the selector applies to.

▼ **operator** `string` required

operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the

operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.

▼ matchLabels `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **matchLabelKeys**
`[]string`

MatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key in (value)` to select the group of existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MatchLabelKeys and LabelSelector. Also, MatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysInPodAffinity feature gate.

▼ **mismatchLabelKeys**
`[]string`

MismatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key notin (value)` to select the group of existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MismatchLabelKeys and LabelSelector. Also, MismatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysInPodAffinity feature gate.

▼ **namespaceSelector** `object`

A label query over the set of namespaces that the term applies to. The term is applied to the union of the namespaces selected by this field and the ones listed in the namespaces field. null selector and null or empty namespaces list means "this pod's namespace". An empty selector ({}) matches all namespaces.

▼ **matchExpressions**
`[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**
`string`
required

key is the label key that the selector applies to.

▼ **operator** `string` required

operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the

operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.

▼ **matchLabels** `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ namespaces

`[]string`

namespaces specifies a static list of namespace names that the term applies to. The term is applied to the union of the namespaces listed in this field and the ones selected by namespaceSelector. null or empty namespaces list and null namespaceSelector means "this pod's namespace".

▼ topologyKey

`string` required

This pod should be co-located (affinity) or not co-located (anti-affinity) with the pods matching the labelSelector in the specified namespaces, where co-located is defined as running on a node whose value of the label with key topologyKey matches that of any node on which any of the selected pods is running. Empty topologyKey is not allowed.

▼ **podAntiAffinity** `object`

Describes pod anti-affinity scheduling rules (e.g. avoid putting this pod in the same node, zone, etc. as some other pod(s)).

▼ **preferredDuringSchedulingIgnoredDuringExecution** `[]object`

The weights of all of the matched WeightedPodAffinityTerm fields are added per-node to find the most preferred node(s)

▼ **podAffinityTerm** `object` required

Required. A pod affinity term, associated with the corresponding weight.

▼ **labelSelector** `object`

A label query over a set of resources, in this case pods. If it's null, this PodAffinityTerm matches with no Pods.

▼ **matchExpressions** `[]objec t`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string` required

key is the label key that th

e se le ct or ap pli es to.

▼ **operator** `string` required

op er at or re pr es en ts a ke y's rel ati on sh ip to a

set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values**

`[]string`

values is an array of string values. If the operator is In or NotIn, the valu

es
ar
ra
y
m
us
t
be
no
n-
e
m
pt
y.
If
th
e
op
er
at
or
is
Ex
ist
s
or
D
oe
s
N
ot
Ex
ist
,
th
e
va

lu es ar ra y m us t be e m pt y. Th is ar ra y is re pl ac ed du rin g a str at eg ic m er ge pa tc h.

▼ **matchLabels** `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼

matchLabelKeys `[]string`

MatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key in (value)` to select the group of existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MatchLabelKeys and LabelSelector.

Also, MatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysIn PodAffinity feature gate.

▼ **mismatchLabelKeys** `[]string`

MismatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key notin (value)` to select the group of existing pods which pods will be taken into consideration for

the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MismatchLabelKeys and LabelSelector. Also, MismatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysInPodAffinity feature gate.

▼ **namespaceSelector** `object`

A label query over the set of namespaces that the term applies to. The term is applied to the

union of the namespaces selected by this field and the ones listed in the namespaces field. null selector and null or empty namespaces list means "this pod's namespace". An empty selector ({}) matches all namespaces.

▼ **matchExpressions** `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string` required

key is the label key that the selector applies to.

▼ **operator** `string`

g

required

operator represents a key's relationship to a set of values. Valid operators are

In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of strin

g
va
lu
es
. If
th
e
op
er
at
or
is
In
or
N
otI
n,
th
e
va
lu
es
ar
ra
y
m
us
t
be
no
n-
e
m
pt
y.
If
th

e
op
er
at
or
is
Ex
ist
s
or
D
oe
s
N
ot
Ex
ist
,
th
e
va
lu
es
ar
ra
y
m
us
t
be
e
m
pt
y.
Th
is
ar

ra
y
is
re
pl
ac
ed
du
rin
g
a
str
at
eg
ic
m
er
ge
pa
tc
h.

▼ **matchLabels** `object`

matchLab
els is a
map of
{key,value
} pairs. A
single
{key,value
} in the
matchLab
els map is

equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **namespaces** `[]string`

namespaces specifies a static list of namespace names that the term applies to. The term is applied to the union of the namespaces listed in this field and the ones selected by namespaceSelector. null or empty

namespaces list and null namespaceSelect or means "this pod's namespace".

▼ **topologyKey**

`string`

required

This pod should be co-located (affinity) or not co-located (anti-affinity) with the pods matching the labelSelector in the specified namespaces, where co-located is defined as running on a node whose value of the label with key topologyKey matches that of any node on which any of the selected pods is running. Empty topologyKey is not allowed.

▼ **weight** `integer`

required

weight associated with matching the corresponding podAffinityTerm, in the range 1-100.

▼ **requiredDuringSchedulingIgnoredDuringExecution** `[]object`

Defines a set of pods (namely those matching the labelSelector relative to the given namespace(s)) that this pod should be co-located (affinity) or not co-located (anti-affinity) with, where co-located is defined as running on a node whose value of the label with key matches that of any node on which a pod of the set of pods is running

▼ **labelSelector** `object`

A label query over a set of resources, in this case pods. If it's null, this PodAffinityTerm matches with no Pods.

▼ **matchExpressions**

`[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**

`string`

required

key is the label key that the selector applies to.

▼ **operator**

`string`

required

operator represents a key's relationship to a set of values. Valid operators

are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic

merge patch.

▼ matchLabels

`object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ matchLabelKeys

`[]string`

MatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as

`key in (value)` to select the group of existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MatchLabelKeys and LabelSelector. Also, MatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysInPodAffinity feature gate.

▼ **mismatchLabelKeys** `[]string`

MismatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key notin (value)` to select the group of existing pods

which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MismatchLabelKeys and LabelSelector. Also, MismatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysInPodAffinity feature gate.

▼ **namespaceSelector** `object`

A label query over the set of namespaces that the term applies to. The term is applied to the union of the namespaces selected by this field and the ones listed in the namespaces field. null selector and null or empty namespaces list means "this pod's namespace". An empty selector ({}) matches all namespaces.

▼ **matchExpressions** `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string` required

key is the label key that the selector applies to.

▼ **operator** `string` required

operator represents a key's relationship to a set of values. Valid operators

are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic

merge patch.

▼ **matchLabels**
`object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **namespaces**
`[]string`

namespaces specifies a static list of namespace names that the term applies to. The term is applied to the union of the namespaces listed in this field and the ones selected by namespaceSelector. null or empty namespaces

list and null namespaceSelector means "this pod's namespace".

▼ **topologyKey**

`string` required

This pod should be co-located (affinity) or not co-located (anti-affinity) with the pods matching the labelSelector in the specified namespaces, where co-located is defined as running on a node whose value of the label with key topologyKey matches that of any node on which any of the selected pods is running. Empty topologyKey is not allowed.

▼ **automountServiceAccountToken**

`boolean`

AutomountServiceAccountToken indicates whether a service account token should be automatically mounted.

▼ **containers** `[]object` required

A single application container that you want to run within a pod.

▼ **args** `[]string`

Arguments to the entrypoint. The container image's CMD is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: https://kubernetes.io/docs/tasks/inject-data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ **command** `[]string`

Entrypoint array. Not executed within a shell. The container image's ENTRYPOINT is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e.

"$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: https://kubernetes.io/docs/tasks/inject-data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ **env** `[]object`

EnvVar represents an environment variable present in a Container.

▼ **name** `string` required

Name of the environment variable. Must be a C_IDENTIFIER.

▼ **value** `string`

Variable references $(VAR_NAME) are expanded using the previously defined environment variables in the container and any service environment variables. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped

references will never be expanded, regardless of whether the variable exists or not. Defaults to "".

▼ **valueFrom** `object`

Source for the environment variable's value. Cannot be used if value is not empty.

▼ **configMapKeyRef** `object`

Selects a key of a ConfigMap.

▼ **key** `string`

required

The key to select.

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the ConfigMap or its key must be defined

▼ **fieldRef** `object`

Selects a field of the pod: supports metadata.name, metadata.namespace, `metadata.labels['<KEY>']`, `metadata.annotations['<KEY>']`, spec.nodeName, spec.serviceAccountName, status.hostIP, status.podIP, status.podIPs.

▼ **apiVersion** `string`

Version of the schema the FieldPath is written in terms of, defaults to "v1".

▼ **fieldPath** `string`

required

Path of the field to select in the specified API version.

▼ resourceFieldRef

`object`

Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, limits.ephemeral-storage, requests.cpu, requests.memory and requests.ephemeral-storage) are currently supported.

▼ containerName

`string`

Container name: required for volumes, optional for env vars

▼ divisor

Specifies the output format of the exposed

resources, defaults to "1"

▼ **resource**
`string`
required

Required: resource to select

▼ **secretKeyRef**
`object`

Selects a key of a secret in the pod's namespace

▼ **key** `string`
required

The key of the secret to select from. Must be a valid secret key.

▼ **name**
`string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-

objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the Secret or its key must be defined

▼ **envFrom** `[]object`

EnvFromSource represents the source of a set of ConfigMaps

▼ **configMapRef** `object`

The ConfigMap to select from

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the ConfigMap must be defined

▼ **prefix** `string`

An optional identifier to prepend to each key in the ConfigMap. Must be a C_IDENTIFIER.

▼ **secretRef** `object`

The Secret to select from

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the Secret must be defined

▼ **image** `string`

Container image name. More info: https://kubernetes.io/docs/concepts/contai

ners/images↗ This field is optional to allow higher level config management to default or override container images in workload controllers like Deployments and StatefulSets.

▼ imagePullPolicy `string`

Image pull policy. One of Always, Never, IfNotPresent. Defaults to Always if :latest tag is specified, or IfNotPresent otherwise. Cannot be updated. More info: https://kubernetes.io/docs/concepts/containers/images#updating-images↗

▼ lifecycle `object`

Actions that the management system should take in response to container lifecycle events. Cannot be updated.

▼ postStart `object`

PostStart is called immediately after a container is created. If the handler fails, the container is terminated and restarted according to its restart policy. Other management of the container blocks until the hook completes. More info: https://kubernetes.io/docs/concepts/containers/container-lifecycle-hooks/#container-hooks↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host**

`string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders**

`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**

`string`

required

The header field name. This will be canonicalized upon output, so

case-variant names will be understood as the same header.

▼ **value**

`string`

required

The header field value

▼ **path**

`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme**
`string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **sleep** `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ **seconds**
`integer`
required

Seconds is the number of seconds to sleep.

▼ **tcpSocket** `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept for the backward compatibility. There are no validation of this field and lifecycle hooks will fail in runtime when tcp handler is specified.

▼ host

`string`

Optional: Host name to connect to, defaults to the pod IP.

▼ port required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ preStop `object`

PreStop is called immediately before a container is terminated due to an API request or management event such as liveness/startup probe failure, preemption, resource contention, etc. The handler is not called if the container crashes or exits. The Pod's termination grace period countdown begins before the PreStop hook is executed. Regardless of the outcome of the handler, the container will

eventually terminate within the Pod's termination grace period (unless delayed by finalizers). Other management of the container blocks until the hook completes or until the termination grace period is reached. More info: https://kubernetes.io/docs/concepts/containers/container-lifecycle-hooks/#container-hooks ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to

that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host**
`string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders**
`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path**
`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **sleep** `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ **seconds** `integer`

required

Seconds is the number of seconds to sleep.

▼ **tcpSocket** `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept for the backward compatibility. There are no validation of this field and lifecycle hooks will fail in runtime when tcp handler is specified.

▼ **host**
`string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **livenessProbe** `object`

Periodic probe of container liveness. Container will be restarted if the probe fails. Cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ **failureThreshold** `integer`

Minimum consecutive failures for the probe to be considered failed

after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ service `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ httpGet `object`

HTTPGet specifies the http request to perform.

▼ host `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ httpHeaders `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ name `string`

required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ value `string`

required

The header field value

▼ path `string`

Path to access on the HTTP server.

▼ port required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ scheme `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ initialDelaySeconds `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ periodSeconds `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ successThreshold `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness and startup. Minimum value is 1.

▼ tcpSocket `object`

TCPSocket specifies an action involving a TCP port.

▼ host `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ port required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼

terminationGracePeriodSeconds

`integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ **timeoutSeconds**

`integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More

info:
https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ name `string` required

Name of the container specified as a DNS_LABEL. Each container in a pod must have a unique name (DNS_LABEL). Cannot be updated.

▼ ports `[]object`

ContainerPort represents a network port in a single container.

▼ containerPort `integer` required

Number of port to expose on the pod's IP address. This must be a valid port number, 0 < x < 65536.

▼ hostIP `string`

What host IP to bind the external port to.

▼ hostPort `integer`

Number of port to expose on the host. If specified, this must be a valid port number, 0 < x < 65536. If

HostNetwork is specified, this must match ContainerPort. Most containers do not need this.

▼ **name** `string`

If specified, this must be an IANA_SVC_NAME and unique within the pod. Each named port in a pod must have a unique name. Name for the port that can be referred to by services.

▼ **protocol** `string`

Protocol for port. Must be UDP, TCP, or SCTP. Defaults to "TCP".

▼ **readinessProbe** `object`

Periodic probe of container service readiness. Container will be removed from service endpoints if the probe fails. Cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders** `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must

be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for

liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes

are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ timeoutSeconds `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ resizePolicy `[]object`

ContainerResizePolicy represents resource resize policy for the container.

▼ **resourceName** `string`

required

Name of the resource to which this resource resize policy applies. Supported values: cpu, memory.

▼ **restartPolicy** `string`

required

Restart policy to apply when specified resource is resized. If not specified, it defaults to NotRequired.

▼ **resources** `object`

Compute Resources required by this container. Cannot be updated. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/↗

▼ **claims** `[]object`

ResourceClaim references one entry in PodSpec.ResourceClaims.

▼ **name** `string`

required

Name must match the name of one entry in pod.spec.resourceClaims of the Pod where this field

is used. It makes that resource available inside a container.

▼ limits `object`

Limits describes the maximum amount of compute resources allowed. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/ ↗

▼ requests `object`

Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. Requests cannot exceed Limits. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/ ↗

▼ restartPolicy `string`

RestartPolicy defines the restart behavior of individual containers in a pod. This field may only be set for init containers, and the only allowed value is "Always". For non-init containers or when this field is not

specified, the restart behavior is defined by the Pod's restart policy and the container type. Setting the RestartPolicy as "Always" for the init container will have the following effect: this init container will be continually restarted on exit until all regular containers have terminated. Once all regular containers have completed, all init containers with restartPolicy "Always" will be shut down. This lifecycle differs from normal init containers and is often referred to as a "sidecar" container. Although this init container still starts in the init container sequence, it does not wait for the container to complete before proceeding to the next init container. Instead, the next init container starts immediately after this init container is started, or after any startupProbe has successfully completed.

▼ **securityContext** `object`

SecurityContext defines the security options the container should be run with. If set, the fields of SecurityContext override the equivalent fields of PodSecurityContext. More info: https://kubernetes.io/docs/tasks/configure-pod-container/security-context/ ↗

▼ **allowPrivilegeEscalation** `boolean`

AllowPrivilegeEscalation controls whether a process can gain more privileges than its parent process. This bool directly controls if the

no_new_privs flag will be set on the container process. AllowPrivilegeEscalation is true always when the container is:

1. run as Privileged
2. has CAP_SYS_ADMIN Note that this field cannot be set when spec.os.name is windows.

▼ capabilities `object`

The capabilities to add/drop when running containers. Defaults to the default set of capabilities granted by the container runtime. Note that this field cannot be set when spec.os.name is windows.

▼ add `[]string`

Added capabilities

▼ drop `[]string`

Removed capabilities

▼ privileged `boolean`

Run container in privileged mode. Processes in privileged containers are essentially equivalent to root on the host. Defaults to false. Note

that this field cannot be set when spec.os.name is windows.

▼ procMount `string`

procMount denotes the type of proc mount to use for the containers. The default is DefaultProcMount which uses the container runtime defaults for readonly paths and masked paths. This requires the ProcMountType feature flag to be enabled. Note that this field cannot be set when spec.os.name is windows.

▼ readOnlyRootFilesystem `boolean`

Whether this container has a read-only root filesystem. Default is false. Note that this field cannot be set when spec.os.name is windows.

▼ runAsGroup `integer`

The GID to run the entrypoint of the container process. Uses runtime default if unset. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field

cannot be set when spec.os.name is windows.

▼ **runAsNonRoot** `boolean`

Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ **runAsUser** `integer`

The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ **seLinuxOptions** `object`

The SELinux context to be applied to the container. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ **level** `string`

Level is SELinux level label that applies to the container.

▼ **role** `string`

Role is a SELinux role label that applies to the container.

▼ **type** `string`

Type is a SELinux type label that applies to the container.

▼ **user** `string`

User is a SELinux user label that applies to the

container.

▼ seccompProfile `object`

The seccomp options to use by this container. If seccomp options are provided at both the pod & container level, the container options override the pod options. Note that this field cannot be set when spec.os.name is windows.

▼ localhostProfile `string`

localhostProfile indicates a profile defined in a file on the node should be used. The profile must be preconfigured on the node to work. Must be a descending path, relative to the kubelet's configured seccomp profile location. Must be set if type is "Localhost". Must NOT be set for any other type.

▼ type `string`

required

type indicates which kind of seccomp profile will be applied. Valid options are:

Localhost - a profile defined in a file on the node should be used. RuntimeDefault - the container runtime default profile should be used. Unconfined - no profile should be applied.

▼ **windowsOptions** `object`

The Windows specific settings applied to all containers. If unspecified, the options from the PodSecurityContext will be used. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is linux.

▼ **gmsaCredentialSpec** `string`

GMSACredentialSpec is where the GMSA admission webhook (https://github.com/kubernetes-sigs/windows-gmsa↗) inlines the contents of the GMSA credential spec named by the

GMSACredentialSpecNam
e field.

▼ **gmsaCredentialSpecName**
`string`

GMSACredentialSpecNam
e is the name of the
GMSA credential spec to
use.

▼ **hostProcess**
`boolean`

HostProcess determines if a container should be run as a 'Host Process' container. All of a Pod's containers must have the same effective HostProcess value (it is not allowed to have a mix of HostProcess containers and non-HostProcess containers). In addition, if HostProcess is true then HostNetwork must also be set to true.

▼ **runAsUserName**
`string`

The UserName in
Windows to run the

entrypoint of the container process. Defaults to the user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ startupProbe `object`

StartupProbe indicates that the Pod has successfully initialized. If specified, no other probes are executed until this completes successfully. If this probe fails, the Pod will be restarted, just as if the livenessProbe failed. This can be used to provide different probe parameters at the beginning of a Pod's lifecycle, when it might take a long time to load data or warm a cache, than during steady-state operation. This cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ exec `object`

Exec specifies the action to take.

▼ command `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders** `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must

be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for

liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes

are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ timeoutSeconds `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ stdin `boolean`

Whether this container should allocate a buffer for stdin in the container runtime. If this is not set, reads from stdin in the

container will always result in EOF. Default is false.

▼ **stdinOnce** `boolean`

Whether the container runtime should close the stdin channel after it has been opened by a single attach. When stdin is true the stdin stream will remain open across multiple attach sessions. If stdinOnce is set to true, stdin is opened on container start, is empty until the first client attaches to stdin, and then remains open and accepts data until the client disconnects, at which time stdin is closed and remains closed until the container is restarted. If this flag is false, a container processes that reads from stdin will never receive an EOF. Default is false

▼ **terminationMessagePath** `string`

Optional: Path at which the file to which the container's termination message will be written is mounted into the container's filesystem. Message written is intended to be brief final status, such as an assertion failure message. Will be truncated by the node if greater than 4096 bytes. The total message length across all containers will be limited to 12kb. Defaults to /dev/termination-log. Cannot be updated.

▼ terminationMessagePolicy `string`

Indicate how the termination message should be populated. File will use the contents of terminationMessagePath to populate the container status message on both success and failure. FallbackToLogsOnError will use the last chunk of container log output if the termination message file is empty and the container exited with an error. The log output is limited to 2048 bytes or 80 lines, whichever is smaller. Defaults to File. Cannot be updated.

▼ tty `boolean`

Whether this container should allocate a TTY for itself, also requires 'stdin' to be true. Default is false.

▼ volumeDevices `[]object`

volumeDevice describes a mapping of a raw block device within a container.

▼ devicePath `string`

required

devicePath is the path inside of the container that the device will be mapped to.

▼ **name** `string` required

name must match the name of a persistentVolumeClaim in the pod

▼ **volumeMounts** `[]object`

VolumeMount describes a mounting of a Volume within a container.

▼ **mountPath** `string`

required

Path within the container at which the volume should be mounted. Must not contain ':'.

▼ **mountPropagation** `string`

mountPropagation determines how mounts are propagated from the host to container and the other way around. When not set, MountPropagationNone is used. This field is beta in 1.10.

▼ **name** `string` required

This must match the Name of a Volume.

▼ **readOnly** `boolean`

Mounted read-only if true, read-write otherwise (false or unspecified). Defaults to false.

▼ **subPath** `string`

Path within the volume from which the container's volume should be mounted. Defaults to "" (volume's root).

▼ **subPathExpr** `string`

Expanded path within the volume from which the container's volume should be mounted. Behaves similarly to SubPath but environment variable references $(VAR_NAME) are expanded using the container's environment. Defaults to "" (volume's root). SubPathExpr and SubPath are mutually exclusive.

▼ **workingDir** `string`

Container's working directory. If not specified, the container runtime's default will be used, which might be configured in the container image. Cannot be updated.

▼ **dnsConfig** `object`

Specifies the DNS parameters of a pod. Parameters specified here will be merged to the generated DNS configuration based on DNSPolicy.

▼ **nameservers** `[]string`

A list of DNS name server IP addresses. This will be appended to the base nameservers generated from DNSPolicy. Duplicated nameservers will be removed.

▼ **options** `[]object`

PodDNSConfigOption defines DNS resolver options of a pod.

▼ **name** `string`

Required.

▼ **value** `string`

▼ **searches** `[]string`

A list of DNS search domains for host-name lookup. This will be appended to the base search paths generated from DNSPolicy. Duplicated search paths will be removed.

▼ dnsPolicy `string`

Set DNS policy for the pod. Defaults to "ClusterFirst". Valid values are 'ClusterFirstWithHostNet', 'ClusterFirst', 'Default' or 'None'. DNS parameters given in DNSConfig will be merged with the policy selected with DNSPolicy. To have DNS options set along with hostNetwork, you have to specify DNS policy explicitly to 'ClusterFirstWithHostNet'.

▼ enableServiceLinks `boolean`

EnableServiceLinks indicates whether information about services should be injected into pod's environment variables, matching the syntax of Docker links. Optional: Defaults to true.

▼ ephemeralContainers `[]object`

An EphemeralContainer is a temporary container that you may add to an existing Pod for user-initiated activities such as debugging. Ephemeral containers have no resource or scheduling guarantees, and they will not be restarted when they exit or when a Pod is removed or restarted. The kubelet may evict a Pod if an ephemeral container causes the Pod to exceed its resource allocation.

To add an ephemeral container, use the ephemeralcontainers subresource of an existing Pod. Ephemeral containers may not be removed or restarted.

▼ args `[]string`

Arguments to the entrypoint. The image's CMD is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: https://kubernetes.io/docs/tasks/inject-data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ command `[]string`

Entrypoint array. Not executed within a shell. The image's ENTRYPOINT is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: https://kubernetes.io/docs/tasks/inject-

data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ **env** `[]object`

EnvVar represents an environment variable present in a Container.

▼ **name** `string` required

Name of the environment variable. Must be a C_IDENTIFIER.

▼ **value** `string`

Variable references $(VAR_NAME) are expanded using the previously defined environment variables in the container and any service environment variables. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Defaults to "".

▼ valueFrom `object`

Source for the environment variable's value. Cannot be used if value is not empty.

▼ configMapKeyRef `object`

Selects a key of a ConfigMap.

▼ key `string`

required

The key to select.

▼ name `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ optional `boolean`

Specify whether the ConfigMap or

its key must be defined

▼ **fieldRef** `object`

Selects a field of the pod: supports metadata.name, metadata.namespace, `metadata.labels['<KEY>']`, `metadata.annotations['<KEY>']`, spec.nodeName, spec.serviceAccountName, status.hostIP, status.podIP, status.podIPs.

▼ **apiVersion** `string`

Version of the schema the FieldPath is written in terms of, defaults to "v1".

▼ **fieldPath** `string`

required

Path of the field to select in the

specified API version.

▼ **resourceFieldRef** `object`

Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, limits.ephemeral-storage, requests.cpu, requests.memory and requests.ephemeral-storage) are currently supported.

▼ **containerName** `string`

Container name: required for volumes, optional for env vars

▼ **divisor**

Specifies the output format of the exposed resources, defaults to "1"

▼ **resource**

`string`

required

Required:

resource to select

▼ **secretKeyRef**

`object`

Selects a key of a secret in the pod's namespace

▼ **key** `string`

required

The key of the secret to select from. Must be a valid secret key.

▼ **name**

`string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the Secret or its key must be defined

▼ **envFrom** `[]object`

EnvFromSource represents the source of a set of ConfigMaps

▼ **configMapRef** `object`

The ConfigMap to select from

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the ConfigMap must be defined

▼ **prefix** `string`

An optional identifier to prepend to each key in the ConfigMap. Must be a C_IDENTIFIER.

▼ **secretRef** `object`

The Secret to select from

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the Secret must be defined

▼ **image** `string`

Container image name. More info: https://kubernetes.io/docs/concepts/containers/images ↗

▼ **imagePullPolicy** `string`

Image pull policy. One of Always, Never, IfNotPresent. Defaults to Always if :latest tag is specified, or IfNotPresent otherwise. Cannot be updated. More info: https://kubernetes.io/docs/concepts/containers/images#updating-images ↗

▼ **lifecycle** `object`

Lifecycle is not allowed for ephemeral containers.

▼ **postStart** `object`

PostStart is called immediately after a container is created. If the handler fails, the container is terminated and restarted according to its restart policy. Other management of the container blocks until the hook completes. More info: https://kubernetes.io/docs/concepts/containers/container-lifecycle-hooks/#container-hooks ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to

execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ httpGet `object`

HTTPGet specifies the http request to perform.

▼ host `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host"

in httpHeaders instead.

▼ **httpHeaders**

`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**

`string`

required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**

`string`

required

The header field value

▼ **path**

`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme**

`string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **sleep** `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ **seconds**
`integer`
required

Seconds is the number of seconds to sleep.

▼ **tcpSocket** `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept for the backward compatibility. There are no validation of this field and lifecycle hooks will fail in runtime when tcp handler is specified.

▼ **host**
`string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **preStop** `object`

PreStop is called immediately before a container is terminated due to an API request or management event such as liveness/startup probe failure, preemption, resource contention, etc. The handler is not called if the container crashes or exits. The Pod's termination grace period countdown begins before the PreStop hook is executed. Regardless of the outcome of the handler, the container will eventually terminate within the Pod's termination grace period (unless delayed by finalizers). Other management of the container blocks until the hook completes or until the termination grace period is reached. More info: https://kubernetes.io/docs/concept

s/containers/container-lifecycle-hooks/#container-hooks ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host**
`string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders**
`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicali

zed upon output, so case-variant names will be understood as the same header.

▼ **value**

`string`

required

The header field value

▼ **path**

`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an

IANA_SVC_NAM
E.

▼ **scheme**
`string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **sleep** `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ **seconds**
`integer`
required

Seconds is the number of seconds to sleep.

▼ **tcpSocket** `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept for the backward compatibility. There are no validation of this field and

lifecycle hooks will fail in runtime when tcp handler is specified.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **livenessProbe** `object`

Probes are not allowed for ephemeral containers.

▼ **exec** `object`

Exec specifies the action to take.

▼ command

`[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold

`integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md ↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders** `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must

be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for

liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes

are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ timeoutSeconds `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ name `string` required

Name of the ephemeral container specified as a DNS_LABEL. This name must be

unique among all containers, init containers and ephemeral containers.

▼ ports `[]object`

ContainerPort represents a network port in a single container.

▼ containerPort `integer`

required

Number of port to expose on the pod's IP address. This must be a valid port number, 0 < x < 65536.

▼ hostIP `string`

What host IP to bind the external port to.

▼ hostPort `integer`

Number of port to expose on the host. If specified, this must be a valid port number, 0 < x < 65536. If HostNetwork is specified, this must match ContainerPort. Most containers do not need this.

▼ name `string`

If specified, this must be an IANA_SVC_NAME and unique within the pod. Each named port in a pod must have a unique name.

Name for the port that can be referred to by services.

▼ **protocol** `string`

Protocol for port. Must be UDP, TCP, or SCTP. Defaults to "TCP".

▼ **readinessProbe** `object`

Probes are not allowed for ephemeral containers.

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of

0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ service `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ httpGet `object`

HTTPGet specifies the http request to perform.

▼ host `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ httpHeaders `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ name `string`

required

The header field name. This will be canonicalized upon output, so case-variant names will be

understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds**
`integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1.

spec.terminationGracePeriodSeconds is used if unset.

▼ timeoutSeconds `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ resizePolicy `[]object`

ContainerResizePolicy represents resource resize policy for the container.

▼ resourceName `string`

required

Name of the resource to which this resource resize policy applies. Supported values: cpu, memory.

▼ restartPolicy `string`

required

Restart policy to apply when specified resource is resized. If not specified, it defaults to NotRequired.

▼ resources `object`

Resources are not allowed for ephemeral containers. Ephemeral containers use spare resources already allocated to the pod.

▼ claims `[]object`

ResourceClaim references one entry in PodSpec.ResourceClaims.

▼ name `string`

required

Name must match the name of one entry in pod.spec.resourceClaims of the Pod where this field is used. It makes that resource available inside a container.

▼ limits `object`

Limits describes the maximum amount of compute resources allowed. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/↗

▼ requests `object`

Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. Requests cannot exceed Limits. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/↗

▼ restartPolicy `string`

Restart policy for the container to manage the restart behavior of each container within a pod. This may only be set for init containers. You cannot set this field on ephemeral containers.

▼ securityContext `object`

Optional: SecurityContext defines the security options the ephemeral container should be run with. If set, the fields of SecurityContext override the equivalent fields of PodSecurityContext.

▼ allowPrivilegeEscalation `boolean`

AllowPrivilegeEscalation controls whether a process can gain more privileges than its parent process. This bool directly controls if the

no_new_privs flag will be set on the container process. AllowPrivilegeEscalation is true always when the container is:

1. run as Privileged
2. has CAP_SYS_ADMIN Note that this field cannot be set when spec.os.name is windows.

▼ capabilities `object`

The capabilities to add/drop when running containers. Defaults to the default set of capabilities granted by the container runtime. Note that this field cannot be set when spec.os.name is windows.

▼ add `[]string`

Added capabilities

▼ drop `[]string`

Removed capabilities

▼ privileged `boolean`

Run container in privileged mode. Processes in privileged containers are essentially equivalent to root on the host. Defaults to false. Note

that this field cannot be set when spec.os.name is windows.

▼ procMount `string`

procMount denotes the type of proc mount to use for the containers. The default is DefaultProcMount which uses the container runtime defaults for readonly paths and masked paths. This requires the ProcMountType feature flag to be enabled. Note that this field cannot be set when spec.os.name is windows.

▼ readOnlyRootFilesystem `boolean`

Whether this container has a read-only root filesystem. Default is false. Note that this field cannot be set when spec.os.name is windows.

▼ runAsGroup `integer`

The GID to run the entrypoint of the container process. Uses runtime default if unset. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field

cannot be set when spec.os.name is windows.

▼ **runAsNonRoot** `boolean`

Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ **runAsUser** `integer`

The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ **seLinuxOptions** `object`

The SELinux context to be applied to the container. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ **level** `string`

Level is SELinux level label that applies to the container.

▼ **role** `string`

Role is a SELinux role label that applies to the container.

▼ **type** `string`

Type is a SELinux type label that applies to the container.

▼ **user** `string`

User is a SELinux user label that applies to the

container.

▼ seccompProfile `object`

The seccomp options to use by this container. If seccomp options are provided at both the pod & container level, the container options override the pod options. Note that this field cannot be set when spec.os.name is windows.

▼ localhostProfile `string`

localhostProfile indicates a profile defined in a file on the node should be used. The profile must be preconfigured on the node to work. Must be a descending path, relative to the kubelet's configured seccomp profile location. Must be set if type is "Localhost". Must NOT be set for any other type.

▼ type `string`

required

type indicates which kind of seccomp profile will be applied. Valid options are:

Localhost - a profile defined in a file on the node should be used. RuntimeDefault - the container runtime default profile should be used. Unconfined - no profile should be applied.

▼ **windowsOptions** `object`

The Windows specific settings applied to all containers. If unspecified, the options from the PodSecurityContext will be used. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is linux.

▼ **gmsaCredentialSpec** `string`

GMSACredentialSpec is where the GMSA admission webhook (https://github.com/kubernetes-sigs/windows-gmsa↗) inlines the contents of the GMSA credential spec named by the

GMSACredentialSpecNam
e field.

▼ **gmsaCredentialSpecName**
`string`

GMSACredentialSpecNam
e is the name of the
GMSA credential spec to
use.

▼ **hostProcess**
`boolean`

HostProcess determines if a container should be run as a 'Host Process' container. All of a Pod's containers must have the same effective HostProcess value (it is not allowed to have a mix of HostProcess containers and non-HostProcess containers). In addition, if HostProcess is true then HostNetwork must also be set to true.

▼ **runAsUserName**
`string`

The UserName in
Windows to run the

entrypoint of the container process. Defaults to the user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ **startupProbe** `object`

Probes are not allowed for ephemeral containers.

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out

to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ service `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined

by gRPC.

▼ httpGet `object`

HTTPGet specifies the http request to perform.

▼ host `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ httpHeaders `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ name `string`

required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds**
`integer`

Number of seconds after the container has started before liveness probes are initiated. More

info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ periodSeconds `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ successThreshold `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness and startup. Minimum value is 1.

▼ tcpSocket `object`

TCPSocket specifies an action involving a TCP port.

▼ host `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ port required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1.

spec.terminationGracePeriodSeconds is used if unset.

▼ timeoutSeconds `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ stdin `boolean`

Whether this container should allocate a buffer for stdin in the container runtime. If this is not set, reads from stdin in the container will always result in EOF. Default is false.

▼ stdinOnce `boolean`

Whether the container runtime should close the stdin channel after it has been opened by a single attach. When stdin is true the stdin stream will remain open across multiple attach sessions. If stdinOnce is set to true, stdin is opened on container start, is empty until the first client attaches to stdin, and then remains open and accepts data until the client disconnects, at which time stdin is closed and remains closed until the container is

restarted. If this flag is false, a container processes that reads from stdin will never receive an EOF. Default is false

▼ **targetContainerName** `string`

If set, the name of the container from PodSpec that this ephemeral container targets. The ephemeral container will be run in the namespaces (IPC, PID, etc) of this container. If not set then the ephemeral container uses the namespaces configured in the Pod spec.

The container runtime must implement support for this feature. If the runtime does not support namespace targeting then the result of setting this field is undefined.

▼ **terminationMessagePath** `string`

Optional: Path at which the file to which the container's termination message will be written is mounted into the container's filesystem. Message written is intended to be brief final status, such as an assertion failure message. Will be truncated by the node if greater than 4096 bytes. The total message length across all containers will be limited to 12kb. Defaults to /dev/termination-log. Cannot be updated.

▼ **terminationMessagePolicy** `string`

Indicate how the termination message should be populated. File will use the contents of terminationMessagePath to populate the container status message on both success and failure. FallbackToLogsOnError will use the last chunk of container log output if the termination message file is empty and the container exited with an error. The log output is limited to 2048 bytes or 80 lines, whichever is smaller. Defaults to File. Cannot be updated.

▼ tty `boolean`

Whether this container should allocate a TTY for itself, also requires 'stdin' to be true. Default is false.

▼ volumeDevices `[]object`

volumeDevice describes a mapping of a raw block device within a container.

▼ devicePath `string`

required

devicePath is the path inside of the container that the device will be mapped to.

▼ name `string` required

name must match the name of a persistentVolumeClaim in the pod

▼ volumeMounts `[]object`

VolumeMount describes a mounting of a Volume within a container.

▼ mountPath `string`

required

Path within the container at which the volume should be mounted. Must not contain ':'.

▼ mountPropagation `string`

mountPropagation determines how mounts are propagated from the host to container and the other way around. When not set, MountPropagationNone is used. This field is beta in 1.10.

▼ name `string` required

This must match the Name of a Volume.

▼ readOnly `boolean`

Mounted read-only if true, read-write otherwise (false or

unspecified). Defaults to false.

▼ **subPath** `string`

Path within the volume from which the container's volume should be mounted. Defaults to "" (volume's root).

▼ **subPathExpr** `string`

Expanded path within the volume from which the container's volume should be mounted. Behaves similarly to SubPath but environment variable references $(VAR_NAME) are expanded using the container's environment. Defaults to "" (volume's root). SubPathExpr and SubPath are mutually exclusive.

▼ **workingDir** `string`

Container's working directory. If not specified, the container runtime's default will be used, which might be configured in the container image. Cannot be updated.

▼ **hostAliases** `[]object`

HostAlias holds the mapping between IP and hostnames that will be injected as an entry in the pod's hosts file.

▼ **hostnames** `[]string`

Hostnames for the above IP address.

▼ **ip** `string`

IP address of the host file entry.

▼ **hostIPC** `boolean`

Use the host's ipc namespace. Optional: Default to false.

▼ **hostNetwork** `boolean`

Host networking requested for this pod. Use the host's network namespace. If this option is set, the ports that will be used must be specified. Default to false.

▼ **hostPID** `boolean`

Use the host's pid namespace. Optional: Default to false.

▼ **hostUsers** `boolean`

Use the host's user namespace. Optional: Default to true. If set to true or not present, the pod will be run in the host user namespace, useful for when the pod needs a feature only available to the host user namespace, such as loading a kernel module with CAP_SYS_MODULE. When set to false, a

new userns is created for the pod. Setting false is useful for mitigating container breakout vulnerabilities even allowing users to run their containers as root without actually having root privileges on the host. This field is alpha-level and is only honored by servers that enable the UserNamespacesSupport feature.

▼ **hostname** `string`

Specifies the hostname of the Pod If not specified, the pod's hostname will be set to a system-defined value.

▼ **imagePullSecrets** `[]object`

LocalObjectReference contains enough information to let you locate the referenced object inside the same namespace.

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **initContainers** `[]object`

A single application container that you want to run within a pod.

▼ **args** `[]string`

Arguments to the entrypoint. The container image's CMD is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: https://kubernetes.io/docs/tasks/inject-data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ command `[]string`

Entrypoint array. Not executed within a shell. The container image's ENTRYPOINT is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info:

https://kubernetes.io/docs/tasks/inject-data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ **env** `[]object`

EnvVar represents an environment variable present in a Container.

▼ **name** `string` required

Name of the environment variable. Must be a C_IDENTIFIER.

▼ **value** `string`

Variable references $(VAR_NAME) are expanded using the previously defined environment variables in the container and any service environment variables. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Defaults to "".

▼ **valueFrom** `object`

Source for the environment variable's value. Cannot be used if value is not empty.

▼ **configMapKeyRef** `object`

Selects a key of a ConfigMap.

▼ **key** `string`

required

The key to select.

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the ConfigMap or

its key must be defined

▼ **fieldRef** `object`

Selects a field of the pod: supports metadata.name, metadata.namespace, `metadata.labels['<KEY>']`, `metadata.annotations['<KEY>']`, spec.nodeName, spec.serviceAccountName, status.hostIP, status.podIP, status.podIPs.

▼ **apiVersion** `string`

Version of the schema the FieldPath is written in terms of, defaults to "v1".

▼ **fieldPath** `string`

required

Path of the field to select in the

specified API version.

▼ **resourceFieldRef**
`object`

Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, limits.ephemeral-storage, requests.cpu, requests.memory and requests.ephemeral-storage) are currently supported.

▼ **containerName**
`string`

Container name: required for volumes, optional for env vars

▼ **divisor**

Specifies the output format of the exposed resources, defaults to "1"

▼ **resource**

`string`

required

Required:

resource to select

▼ **secretKeyRef**

`object`

Selects a key of a secret in the pod's namespace

▼ **key** `string`

required

The key of the secret to select from. Must be a valid secret key.

▼ **name**

`string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the Secret or its key must be defined

▼ **envFrom** `[]object`

EnvFromSource represents the source of a set of ConfigMaps

▼ **configMapRef** `object`

The ConfigMap to select from

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the ConfigMap must be defined

▼ **prefix** `string`

An optional identifier to prepend to each key in the ConfigMap. Must be a C_IDENTIFIER.

▼ **secretRef** `object`

The Secret to select from

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the Secret must be defined

▼ **image** `string`

Container image name. More info: https://kubernetes.io/docs/concepts/containers/images ↗ This field is optional to allow higher level config management to default or override container images in

workload controllers like Deployments and StatefulSets.

▼ **imagePullPolicy** `string`

Image pull policy. One of Always, Never, IfNotPresent. Defaults to Always if :latest tag is specified, or IfNotPresent otherwise. Cannot be updated. More info: https://kubernetes.io/docs/concepts/containers/images#updating-images ↗

▼ **lifecycle** `object`

Actions that the management system should take in response to container lifecycle events. Cannot be updated.

▼ **postStart** `object`

PostStart is called immediately after a container is created. If the handler fails, the container is terminated and restarted according to its restart policy. Other management of the container blocks until the hook completes. More info: https://kubernetes.io/docs/concepts/containers/container-lifecycle-hooks/#container-hooks ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders**
`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the

same header.

▼ **value**

`string`

required

The header field value

▼ **path**

`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme**

`string`

Scheme to use for connecting to the

host. Defaults to HTTP.

▼ **sleep** `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ **seconds**
`integer`
required

Seconds is the number of seconds to sleep.

▼ **tcpSocket** `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept for the backward compatibility. There are no validation of this field and lifecycle hooks will fail in runtime when tcp handler is specified.

▼ **host**
`string`

Optional: Host name to connect to, defaults to the pod IP.

▼ port required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ preStop `object`

PreStop is called immediately before a container is terminated due to an API request or management event such as liveness/startup probe failure, preemption, resource contention, etc. The handler is not called if the container crashes or exits. The Pod's termination grace period countdown begins before the PreStop hook is executed. Regardless of the outcome of the handler, the container will eventually terminate within the Pod's termination grace period (unless delayed by finalizers).

Other management of the container blocks until the hook completes or until the termination grace period is reached. More info: https://kubernetes.io/docs/concepts/containers/container-lifecycle-hooks/#container-hooks ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as

live/healthy and non-zero is unhealthy.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host**
`string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders**
`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field

name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**

`string`

required

The header field value

▼ **path**

`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number

must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **sleep** `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ **seconds** `integer`

required

Seconds is the number of seconds to sleep.

▼ **tcpSocket** `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept

for the backward compatibility. There are no validation of this field and lifecycle hooks will fail in runtime when tcp handler is specified.

▼ **host**
`string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAM E.

▼ **livenessProbe** `object`

Periodic probe of container liveness. Container will be restarted if the probe fails. Cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ exec `object`

Exec specifies the action to take.

▼ command `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ **port** `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set

"Host" in httpHeaders instead.

▼ httpHeaders

`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ name

`string`

required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ value

`string`

required

The header field value

▼ path `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ successThreshold `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness and startup. Minimum value is 1.

▼ tcpSocket `object`

TCPSocket specifies an action involving a TCP port.

▼ host `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ port required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds**

`integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ **timeoutSeconds**

`integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More

info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ name `string` required

Name of the container specified as a DNS_LABEL. Each container in a pod must have a unique name (DNS_LABEL). Cannot be updated.

▼ ports `[]object`

ContainerPort represents a network port in a single container.

▼ containerPort `integer` required

Number of port to expose on the pod's IP address. This must be a valid port number, 0 < x < 65536.

▼ hostIP `string`

What host IP to bind the external port to.

▼ hostPort `integer`

Number of port to expose on the host. If specified, this must be a valid port number, 0 < x < 65536. If

HostNetwork is specified, this must match ContainerPort. Most containers do not need this.

▼ **name** `string`

If specified, this must be an IANA_SVC_NAME and unique within the pod. Each named port in a pod must have a unique name. Name for the port that can be referred to by services.

▼ **protocol** `string`

Protocol for port. Must be UDP, TCP, or SCTP. Defaults to "TCP".

▼ **readinessProbe** `object`

Periodic probe of container service readiness. Container will be removed from service endpoints if the probe fails. Cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders** `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must

be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for

liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes

are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ **timeoutSeconds** `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **resizePolicy** `[]object`

ContainerResizePolicy represents resource resize policy for the container.

▼ **resourceName** `string`

required

Name of the resource to which this resource resize policy applies. Supported values: cpu, memory.

▼ **restartPolicy** `string`

required

Restart policy to apply when specified resource is resized. If not specified, it defaults to NotRequired.

▼ **resources** `object`

Compute Resources required by this container. Cannot be updated. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/↗

▼ **claims** `[]object`

ResourceClaim references one entry in PodSpec.ResourceClaims.

▼ **name** `string`

required

Name must match the name of one entry in pod.spec.resourceClaims of the Pod where this field

is used. It makes that resource available inside a container.

▼ limits `object`

Limits describes the maximum amount of compute resources allowed. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/ ↗

▼ requests `object`

Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. Requests cannot exceed Limits. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/ ↗

▼ restartPolicy `string`

RestartPolicy defines the restart behavior of individual containers in a pod. This field may only be set for init containers, and the only allowed value is "Always". For non-init containers or when this field is not

specified, the restart behavior is defined by the Pod's restart policy and the container type. Setting the RestartPolicy as "Always" for the init container will have the following effect: this init container will be continually restarted on exit until all regular containers have terminated. Once all regular containers have completed, all init containers with restartPolicy "Always" will be shut down. This lifecycle differs from normal init containers and is often referred to as a "sidecar" container. Although this init container still starts in the init container sequence, it does not wait for the container to complete before proceeding to the next init container. Instead, the next init container starts immediately after this init container is started, or after any startupProbe has successfully completed.

▼ **securityContext** `object`

SecurityContext defines the security options the container should be run with. If set, the fields of SecurityContext override the equivalent fields of PodSecurityContext. More info: https://kubernetes.io/docs/tasks/configure-pod-container/security-context/↗

▼ **allowPrivilegeEscalation** `boolean`

AllowPrivilegeEscalation controls whether a process can gain more privileges than its parent process. This bool directly controls if the

no_new_privs flag will be set on the container process. AllowPrivilegeEscalation is true always when the container is:

1. run as Privileged
2. has CAP_SYS_ADMIN Note that this field cannot be set when spec.os.name is windows.

▼ capabilities `object`

The capabilities to add/drop when running containers. Defaults to the default set of capabilities granted by the container runtime. Note that this field cannot be set when spec.os.name is windows.

▼ add `[]string`

Added capabilities

▼ drop `[]string`

Removed capabilities

▼ privileged `boolean`

Run container in privileged mode. Processes in privileged containers are essentially equivalent to root on the host. Defaults to false. Note

that this field cannot be set when spec.os.name is windows.

▼ procMount `string`

procMount denotes the type of proc mount to use for the containers. The default is DefaultProcMount which uses the container runtime defaults for readonly paths and masked paths. This requires the ProcMountType feature flag to be enabled. Note that this field cannot be set when spec.os.name is windows.

▼ readOnlyRootFilesystem `boolean`

Whether this container has a read-only root filesystem. Default is false. Note that this field cannot be set when spec.os.name is windows.

▼ runAsGroup `integer`

The GID to run the entrypoint of the container process. Uses runtime default if unset. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field

cannot be set when spec.os.name is windows.

▼ runAsNonRoot `boolean`

Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ runAsUser `integer`

The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ seLinuxOptions `object`

The SELinux context to be applied to the container. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ **level** `string`

Level is SELinux level label that applies to the container.

▼ **role** `string`

Role is a SELinux role label that applies to the container.

▼ **type** `string`

Type is a SELinux type label that applies to the container.

▼ **user** `string`

User is a SELinux user label that applies to the

container.

▼ seccompProfile `object`

The seccomp options to use by this container. If seccomp options are provided at both the pod & container level, the container options override the pod options. Note that this field cannot be set when spec.os.name is windows.

▼ localhostProfile `string`

localhostProfile indicates a profile defined in a file on the node should be used. The profile must be preconfigured on the node to work. Must be a descending path, relative to the kubelet's configured seccomp profile location. Must be set if type is "Localhost". Must NOT be set for any other type.

▼ type `string`

required

type indicates which kind of seccomp profile will be applied. Valid options are:

Localhost - a profile defined in a file on the node should be used. RuntimeDefault - the container runtime default profile should be used. Unconfined - no profile should be applied.

▼ **windowsOptions** `object`

The Windows specific settings applied to all containers. If unspecified, the options from the PodSecurityContext will be used. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is linux.

▼ **gmsaCredentialSpec** `string`

GMSACredentialSpec is where the GMSA admission webhook (https://github.com/kubernetes-sigs/windows-gmsa↗) inlines the contents of the GMSA credential spec named by the

GMSACredentialSpecNam
e field.

▼ **gmsaCredentialSpecName**
`string`

GMSACredentialSpecNam
e is the name of the
GMSA credential spec to
use.

▼ **hostProcess**
`boolean`

HostProcess determines if a container should be run as a 'Host Process' container. All of a Pod's containers must have the same effective HostProcess value (it is not allowed to have a mix of HostProcess containers and non-HostProcess containers). In addition, if HostProcess is true then HostNetwork must also be set to true.

▼ **runAsUserName**
`string`

The UserName in
Windows to run the

entrypoint of the container process. Defaults to the user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ startupProbe `object`

StartupProbe indicates that the Pod has successfully initialized. If specified, no other probes are executed until this completes successfully. If this probe fails, the Pod will be restarted, just as if the livenessProbe failed. This can be used to provide different probe parameters at the beginning of a Pod's lifecycle, when it might take a long time to load data or warm a cache, than during steady-state operation. This cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ exec `object`

Exec specifies the action to take.

▼ command `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders** `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must

be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for

liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes

are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ **timeoutSeconds** `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **stdin** `boolean`

Whether this container should allocate a buffer for stdin in the container runtime. If this is not set, reads from stdin in the

container will always result in EOF. Default is false.

▼ **stdinOnce** `boolean`

Whether the container runtime should close the stdin channel after it has been opened by a single attach. When stdin is true the stdin stream will remain open across multiple attach sessions. If stdinOnce is set to true, stdin is opened on container start, is empty until the first client attaches to stdin, and then remains open and accepts data until the client disconnects, at which time stdin is closed and remains closed until the container is restarted. If this flag is false, a container processes that reads from stdin will never receive an EOF. Default is false

▼ **terminationMessagePath** `string`

Optional: Path at which the file to which the container's termination message will be written is mounted into the container's filesystem. Message written is intended to be brief final status, such as an assertion failure message. Will be truncated by the node if greater than 4096 bytes. The total message length across all containers will be limited to 12kb. Defaults to /dev/termination-log. Cannot be updated.

▼ terminationMessagePolicy `string`

Indicate how the termination message should be populated. File will use the contents of terminationMessagePath to populate the container status message on both success and failure. FallbackToLogsOnError will use the last chunk of container log output if the termination message file is empty and the container exited with an error. The log output is limited to 2048 bytes or 80 lines, whichever is smaller. Defaults to File. Cannot be updated.

▼ tty `boolean`

Whether this container should allocate a TTY for itself, also requires 'stdin' to be true. Default is false.

▼ volumeDevices `[]object`

volumeDevice describes a mapping of a raw block device within a container.

▼ devicePath `string`

required

devicePath is the path inside of the container that the device will be mapped to.

▼ **name** `string` required

name must match the name of a persistentVolumeClaim in the pod

▼ **volumeMounts** `[]object`

VolumeMount describes a mounting of a Volume within a container.

▼ **mountPath** `string`

required

Path within the container at which the volume should be mounted. Must not contain ':'.

▼ **mountPropagation** `string`

mountPropagation determines how mounts are propagated from the host to container and the other way around. When not set, MountPropagationNone is used. This field is beta in 1.10.

▼ **name** `string` required

This must match the Name of a Volume.

▼ **readOnly** `boolean`

Mounted read-only if true, read-write otherwise (false or unspecified). Defaults to false.

▼ **subPath** `string`

Path within the volume from which the container's volume should be mounted. Defaults to "" (volume's root).

▼ **subPathExpr** `string`

Expanded path within the volume from which the container's volume should be mounted. Behaves similarly to SubPath but environment variable references $(VAR_NAME) are expanded using the container's environment. Defaults to "" (volume's root). SubPathExpr and SubPath are mutually exclusive.

▼ **workingDir** `string`

Container's working directory. If not specified, the container runtime's default will be used, which might be configured in the container image. Cannot be updated.

▼ **nodeName** `string`

NodeName is a request to schedule this pod onto a specific node. If it is non-empty, the scheduler simply schedules this pod onto that node, assuming that it fits resource requirements.

▼ nodeSelector `object`

NodeSelector is a selector which must be true for the pod to fit on a node. Selector which must match a node's labels for the pod to be scheduled on that node. More info: https://kubernetes.io/docs/concepts/configuration/assign-pod-node/ ↗

▼ os `object`

Specifies the OS of the containers in the pod. Some pod and container fields are restricted if this is set.

If the OS field is set to linux, the following fields must be unset: -securityContext.windowsOptions

If the OS field is set to windows, following fields must be unset:

- spec.hostPID
- spec.hostIPC
- spec.hostUsers
- spec.securityContext.seLinuxOptions
- spec.securityContext.seccompProfile
- spec.securityContext.fsGroup
- spec.securityContext.fsGroupChangePolicy
- spec.securityContext.sysctls
- spec.shareProcessNamespace

- spec.securityContext.runAsUser
- spec.securityContext.runAsGroup
- spec.securityContext.supplementalGroups
- spec.containers[*].securityContext.seLinuxOptions
- spec.containers[*].securityContext.seccompProfile
- spec.containers[*].securityContext.capabilities
- spec.containers[*].securityContext.readOnlyRootFilesystem
- spec.containers[*].securityContext.privileged
- spec.containers[*].securityContext.allowPrivilegeEscalation
- spec.containers[*].securityContext.procMount
- spec.containers[*].securityContext.runAsUser
- spec.containers[*].securityContext.runAsGroup

▼ **name** `string` required

Name is the name of the operating system. The currently supported values are linux and windows. Additional value may be defined in future and can be one of: https://github.com/opencontainers/runtime-spec/blob/master/config.md#platform-specific-configuration ↗ Clients should expect to handle additional values and treat unrecognized values in this field as os: null

▼ **overhead** `object`

Overhead represents the resource overhead associated with running a pod for a given RuntimeClass. This field will be autopopulated at admission time by the RuntimeClass admission controller. If the RuntimeClass admission controller is enabled, overhead must not be set in Pod create requests. The RuntimeClass admission controller will reject Pod create requests which have the overhead already set. If RuntimeClass is configured and selected in the PodSpec, Overhead will be set to the value defined in the corresponding RuntimeClass, otherwise it will remain unset and treated as zero. More info: https://git.k8s.io/enhancements/keps/sig-node/688-pod-overhead/README.md↗

▼ **preemptionPolicy** `string`

PreemptionPolicy is the Policy for preempting pods with lower priority. One of Never, PreemptLowerPriority. Defaults to PreemptLowerPriority if unset.

▼ **priority** `integer`

The priority value. Various system components use this field to find the priority of the pod. When Priority Admission Controller is enabled, it prevents users from setting this field. The admission controller populates this field from PriorityClassName. The higher the value, the higher the priority.

▼ **priorityClassName** `string`

If specified, indicates the pod's priority. "system-node-critical" and "system-cluster-critical" are two special keywords which indicate the highest priorities with the former being the highest priority. Any other name must be defined by creating a PriorityClass object with that name. If not specified, the pod priority will be default or zero if there is no default.

▼ readinessGates `[]object`

PodReadinessGate contains the reference to a pod condition

▼ conditionType `string` required

ConditionType refers to a condition in the pod's condition list with matching type.

▼ resourceClaims `[]object`

PodResourceClaim references exactly one ResourceClaim through a ClaimSource. It adds a name to it that uniquely identifies the ResourceClaim inside the Pod. Containers that need access to the ResourceClaim reference it with this name.

▼ name `string` required

Name uniquely identifies this resource claim inside the pod. This must be a DNS_LABEL.

▼ **source** `object`

Source describes where to find the ResourceClaim.

▼ **resourceClaimName** `string`

ResourceClaimName is the name of a ResourceClaim object in the same namespace as this pod.

▼ **resourceClaimTemplateName** `string`

ResourceClaimTemplateName is the name of a ResourceClaimTemplate object in the same namespace as this pod.

The template will be used to create a new ResourceClaim, which will be bound to this pod. When this pod is deleted, the ResourceClaim will also be deleted. The pod name and resource name, along with a generated component, will be used to form a unique name for the ResourceClaim, which will be recorded in pod.status.resourceClaimStatuses .

This field is immutable and no changes will be made to the corresponding ResourceClaim by

the control plane after creating the ResourceClaim.

▼ restartPolicy `string`

Restart policy for all containers within the pod. One of Always, OnFailure, Never. In some contexts, only a subset of those values may be permitted. Default to Always. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle/#restart-policy ↗

▼ runtimeClassName `string`

RuntimeClassName refers to a RuntimeClass object in the node.k8s.io group, which should be used to run this pod. If no RuntimeClass resource matches the named class, the pod will not be run. If unset or empty, the "legacy" RuntimeClass will be used, which is an implicit class with an empty definition that uses the default runtime handler. More info: https://git.k8s.io/enhancements/keps/sig-node/585-runtime-class ↗

▼ schedulerName `string`

If specified, the pod will be dispatched by specified scheduler. If not specified, the pod will be dispatched by default scheduler.

▼ schedulingGates `[]object`

PodSchedulingGate is associated to a Pod to guard its scheduling.

▼ **name** `string` required

Name of the scheduling gate. Each scheduling gate must have a unique name field.

▼ **securityContext** `object`

SecurityContext holds pod-level security attributes and common container settings. Optional: Defaults to empty. See type description for default values of each field.

▼ **fsGroup** `integer`

A special supplemental group that applies to all containers in a pod. Some volume types allow the Kubelet to change the ownership of that volume to be owned by the pod:

1. The owning GID will be the FSGroup
2. The setgid bit is set (new files created in the volume will be owned by FSGroup)
3. The permission bits are OR'd with rw-rw----

If unset, the Kubelet will not modify the ownership and permissions of any volume. Note that this field cannot be set when spec.os.name is windows.

▼ fsGroupChangePolicy `string`

fsGroupChangePolicy defines behavior of changing ownership and permission of the volume before being exposed inside Pod. This field will only apply to volume types which support fsGroup based ownership(and permissions). It will have no effect on ephemeral volume types such as: secret, configmaps and emptydir. Valid values are "OnRootMismatch" and "Always". If not specified, "Always" is used. Note that this field cannot be set when spec.os.name is windows.

▼ runAsGroup `integer`

The GID to run the entrypoint of the container process. Uses runtime default if unset. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container. Note that this field cannot be set when spec.os.name is windows.

▼ runAsNonRoot `boolean`

Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in SecurityContext. If set

in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ runAsUser `integer`

The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container. Note that this field cannot be set when spec.os.name is windows.

▼ seLinuxOptions `object`

The SELinux context to be applied to all containers. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container. Note that this field cannot be set when spec.os.name is windows.

▼ level `string`

Level is SELinux level label that applies to the container.

▼ role `string`

Role is a SELinux role label that applies to the container.

▼ **type** `string`

Type is a SELinux type label that applies to the container.

▼ **user** `string`

User is a SELinux user label that applies to the container.

▼ **seccompProfile** `object`

The seccomp options to use by the containers in this pod. Note that this field cannot be set when spec.os.name is windows.

▼ **localhostProfile** `string`

localhostProfile indicates a profile defined in a file on the node should be used. The profile must be preconfigured on the node to work. Must be a descending path, relative to the kubelet's configured seccomp profile location. Must be set if type is "Localhost". Must NOT be set for any other type.

▼ **type** `string` required

type indicates which kind of seccomp profile will be applied. Valid options are:

Localhost - a profile defined in a file on the node should be used. RuntimeDefault - the container runtime default profile should be used. Unconfined - no profile should be applied.

▼ supplementalGroups `[]integer`

A list of groups applied to the first process run in each container, in addition to the container's primary GID, the fsGroup (if specified), and group memberships defined in the container image for the uid of the container process. If unspecified, no additional groups are added to any container. Note that group memberships defined in the container image for the uid of the container process are still effective, even if they are not included in this list. Note that this field cannot be set when spec.os.name is windows.

▼ sysctls `[]object`

Sysctl defines a kernel parameter to be set

▼ name `string` required

Name of a property to set

▼ **value** `string` required

Value of a property to set

▼ **windowsOptions** `object`

The Windows specific settings applied to all containers. If unspecified, the options within a container's SecurityContext will be used. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is linux.

▼ **gmsaCredentialSpec** `string`

GMSACredentialSpec is where the GMSA admission webhook (https://github.com/kubernetes-sigs/windows-gmsa↗) inlines the contents of the GMSA credential spec named by the GMSACredentialSpecName field.

▼ **gmsaCredentialSpecName** `string`

GMSACredentialSpecName is the name of the GMSA credential spec to use.

▼ hostProcess `boolean`

HostProcess determines if a container should be run as a 'Host Process' container. All of a Pod's containers must have the same effective HostProcess value (it is not allowed to have a mix of HostProcess containers and non-HostProcess containers). In addition, if HostProcess is true then HostNetwork must also be set to true.

▼ runAsUserName `string`

The UserName in Windows to run the entrypoint of the container process. Defaults to the user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ serviceAccount `string`

DeprecatedServiceAccount is a depreciated alias for ServiceAccountName. Deprecated: Use serviceAccountName instead.

▼ serviceAccountName `string`

ServiceAccountName is the name of the ServiceAccount to use to run this pod. More info: https://kubernetes.io/docs/tasks/configure-pod-container/configure-service-account/ ↗

▼ setHostnameAsFQDN `boolean`

If true the pod's hostname will be configured as the pod's FQDN, rather than the leaf name (the default). In Linux containers, this means setting the FQDN in the hostname field of the kernel (the nodename field of struct utsname). In Windows containers, this means setting the registry value of hostname for the registry key HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\Tcpip\Parameters to FQDN. If a pod does not have FQDN, this has no effect. Default to false.

▼ shareProcessNamespace `boolean`

Share a single process namespace between all of the containers in a pod. When this is set containers will be able to view and signal processes from other containers in the same pod, and the first process in each container will not be assigned PID 1. HostPID and ShareProcessNamespace cannot both be set. Optional: Default to false.

▼ subdomain `string`

If specified, the fully qualified Pod hostname will be "...svc.". If not specified, the pod will not have a

domainname at all.

▼ terminationGracePeriodSeconds `integer`

Optional duration in seconds the pod needs to terminate gracefully. May be decreased in delete request. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). If this value is nil, the default grace period will be used instead. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. Defaults to 30 seconds.

▼ tolerations `[]object`

The pod this Toleration is attached to tolerates any taint that matches the triple <key,value,effect> using the matching operator .

▼ effect `string`

Effect indicates the taint effect to match. Empty means match all taint effects. When specified, allowed values are NoSchedule, PreferNoSchedule and NoExecute.

▼ key `string`

Key is the taint key that the toleration applies to. Empty means match all taint

keys. If the key is empty, operator must be Exists; this combination means to match all values and all keys.

▼ **operator** `string`

Operator represents a key's relationship to the value. Valid operators are Exists and Equal. Defaults to Equal. Exists is equivalent to wildcard for value, so that a pod can tolerate all taints of a particular category.

▼ **tolerationSeconds** `integer`

TolerationSeconds represents the period of time the toleration (which must be of effect NoExecute, otherwise this field is ignored) tolerates the taint. By default, it is not set, which means tolerate the taint forever (do not evict). Zero and negative values will be treated as 0 (evict immediately) by the system.

▼ **value** `string`

Value is the taint value the toleration matches to. If the operator is Exists, the value should be empty, otherwise just a regular string.

▼ **topologySpreadConstraints** `[]object`

TopologySpreadConstraint specifies how to spread matching pods among the given topology.

▼ **labelSelector** `object`

LabelSelector is used to find matching pods. Pods that match this label selector are counted to determine the number of pods in their corresponding topology domain.

▼ **matchExpressions** `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string`

required

key is the label key that the selector applies to.

▼ **operator** `string`

required

operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.

▼ matchLabels `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ matchLabelKeys `[]string`

MatchLabelKeys is a set of pod label keys to select the pods over which spreading will be calculated. The keys are used to lookup values from the incoming pod labels, those key-value labels are ANDed with labelSelector to select the group of existing pods over which spreading will be calculated for the incoming pod. The same key is forbidden to exist in both MatchLabelKeys and LabelSelector. MatchLabelKeys cannot be set when

LabelSelector isn't set. Keys that don't exist in the incoming pod labels will be ignored. A null or empty list means only match against labelSelector.

This is a beta field and requires the MatchLabelKeysInPodTopologySpread feature gate to be enabled (enabled by default).

▼ maxSkew `integer` required

MaxSkew describes the degree to which pods may be unevenly distributed. When `whenUnsatisfiable=DoNotSchedule`, it is the maximum permitted difference between the number of matching pods in the target topology and the global minimum. The global minimum is the minimum number of matching pods in an eligible domain or zero if the number of eligible domains is less than MinDomains. For example, in a 3-zone cluster, MaxSkew is set to 1, and pods with the same labelSelector spread as 2/2/1: In this case, the global minimum is 1. | zone1 | zone2 | zone3 | | P P | P P | P |

- if MaxSkew is 1, incoming pod can only be scheduled to zone3 to become 2/2/2; scheduling it onto zone1(zone2) would make the ActualSkew(3-1) on zone1(zone2) violate MaxSkew(1).
- if MaxSkew is 2, incoming pod can be scheduled onto any zone. When `whenUnsatisfiable=ScheduleAnyway`, it is used to give higher precedence

to topologies that satisfy it. It's a required field. Default value is 1 and 0 is not allowed.

▼ minDomains `integer`

MinDomains indicates a minimum number of eligible domains. When the number of eligible domains with matching topology keys is less than minDomains, Pod Topology Spread treats "global minimum" as 0, and then the calculation of Skew is performed. And when the number of eligible domains with matching topology keys equals or greater than minDomains, this value has no effect on scheduling. As a result, when the number of eligible domains is less than minDomains, scheduler won't schedule more than maxSkew Pods to those domains. If value is nil, the constraint behaves as if MinDomains is equal to 1. Valid values are integers greater than 0. When value is not nil, WhenUnsatisfiable must be DoNotSchedule.

For example, in a 3-zone cluster, MaxSkew is set to 2, MinDomains is set to 5 and pods with the same labelSelector spread as 2/2/2: | zone1 | zone2 | zone3 | | P P | P P | P P | The number of domains is less than 5(MinDomains), so "global minimum" is treated as 0. In this situation, new pod with the same labelSelector cannot be scheduled, because computed skew will be 3(3 - 0) if new Pod is

scheduled to any of the three zones, it will violate MaxSkew.

This is a beta field and requires the MinDomainsInPodTopologySpread feature gate to be enabled (enabled by default).

▼ nodeAffinityPolicy `string`

NodeAffinityPolicy indicates how we will treat Pod's nodeAffinity/nodeSelector when calculating pod topology spread skew. Options are:

- Honor: only nodes matching nodeAffinity/nodeSelector are included in the calculations.
- Ignore: nodeAffinity/nodeSelector are ignored. All nodes are included in the calculations.

If this value is nil, the behavior is equivalent to the Honor policy. This is a beta-level feature default enabled by the NodeInclusionPolicyInPodTopologySpread feature flag.

▼ nodeTaintsPolicy `string`

NodeTaintsPolicy indicates how we will treat node taints when calculating pod topology spread skew. Options are:

- Honor: nodes without taints, along with tainted nodes for which the incoming pod has a toleration, are included.

- Ignore: node taints are ignored. All nodes are included.

If this value is nil, the behavior is equivalent to the Ignore policy. This is a beta-level feature default enabled by the NodeInclusionPolicyInPodTopologySpread feature flag.

▼ topologyKey `string` required

TopologyKey is the key of node labels. Nodes that have a label with this key and identical values are considered to be in the same topology. We consider each <key, value> as a "bucket", and try to put balanced number of pods into each bucket. We define a domain as a particular instance of a topology. Also, we define an eligible domain as a domain whose nodes meet the requirements of nodeAffinityPolicy and nodeTaintsPolicy. e.g. If TopologyKey is "kubernetes.io/hostname", each Node is a domain of that topology. And, if TopologyKey is "topology.kubernetes.io/zone", each zone is a domain of that topology. It's a required field.

▼ whenUnsatisfiable `string`

required

WhenUnsatisfiable indicates how to deal with a pod if it doesn't satisfy the spread constraint.

- DoNotSchedule (default) tells the scheduler not to schedule it.
- ScheduleAnyway tells the scheduler to schedule the pod in any location, but giving higher precedence to topologies that would help reduce the skew. A constraint is considered "Unsatisfiable" for an incoming pod if and only if every possible node assignment for that pod would violate "MaxSkew" on some topology. For example, in a 3-zone cluster, MaxSkew is set to 1, and pods with the same labelSelector spread as 3/1/1: | zone1 | zone2 | zone3 | | P P P | P | P | If WhenUnsatisfiable is set to DoNotSchedule, incoming pod can only be scheduled to zone2(zone3) to become 3/2/1(3/1/2) as ActualSkew(2-1) on zone2(zone3) satisfies MaxSkew(1). In other words, the cluster can still be imbalanced, but scheduler won't make it *more* imbalanced. It's a required field.

▼ volumes `[]object`

Volume represents a named volume in a pod that may be accessed by any container in the pod.

▼ awsElasticBlockStore `object`

awsElasticBlockStore represents an AWS Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info:

https://kubernetes.io/docs/concepts/storage/volumes#awselasticblockstore↗

▼ **fsType** `string`

fsType is the filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: https://kubernetes.io/docs/concepts/storage/volumes#awselasticblockstore↗

▼ **partition** `integer`

partition is the partition in the volume that you want to mount. If omitted, the default is to mount by volume name. Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty).

▼ **readOnly** `boolean`

readOnly value true will force the readOnly setting in VolumeMounts. More info: https://kubernetes.io/docs/concept

s/storage/volumes#awselasticblockstore↗

▼ **volumeID** `string`

required

volumeID is unique ID of the persistent disk resource in AWS (Amazon EBS volume). More info: https://kubernetes.io/docs/concepts/storage/volumes#awselasticblockstore↗

▼ **azureDisk** `object`

azureDisk represents an Azure Data Disk mount on the host and bind mount to the pod.

▼ **cachingMode** `string`

cachingMode is the Host Caching mode: None, Read Only, Read Write.

▼ **diskName** `string`

required

diskName is the Name of the data disk in the blob storage

▼ **diskURI** `string` required

diskURI is the URI of data disk in the blob storage

▼ **fsType** `string`

fsType is Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.

▼ **kind** `string`

kind expected values are Shared: multiple blob disks per storage account Dedicated: single blob disk per storage account Managed: azure managed data disk (only in managed availability set). defaults to shared

▼ **readOnly** `boolean`

readOnly Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ **azureFile** `object`

azureFile represents an Azure File Service mount on the host and bind mount to the pod.

▼ **readOnly** `boolean`

readOnly defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ **secretName** `string`

required

secretName is the name of secret that contains Azure Storage Account Name and Key

▼ **shareName** `string`

required

shareName is the azure share Name

▼ **cephfs** `object`

cephFS represents a Ceph FS mount on the host that shares a pod's lifetime

▼ **monitors** `[]string`

required

monitors is Required: Monitors is a collection of Ceph monitors More info: https://examples.k8s.io/volumes/cephfs/README.md#how-to-use-it ↗

▼ path `string`

path is Optional: Used as the mounted root, rather than the full Ceph tree, default is /

▼ readOnly `boolean`

readOnly is Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: https://examples.k8s.io/volumes/cephfs/README.md#how-to-use-it ↗

▼ secretFile `string`

secretFile is Optional: SecretFile is the path to key ring for User, default is /etc/ceph/user.secret More info: https://examples.k8s.io/volumes/cephfs/README.md#how-to-use-it ↗

▼ secretRef `object`

secretRef is Optional: SecretRef is reference to the authentication secret for User, default is empty. More info: https://examples.k8s.io/volumes/cephfs/README.md#how-to-use-it ↗

▼ **name** `string`

Name of the referent.
More info:
https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **user** `string`

user is optional: User is the rados user name, default is admin More info:
https://examples.k8s.io/volumes/cephfs/README.md#how-to-use-it ↗

▼ **cinder** `object`

cinder represents a cinder volume attached and mounted on kubelets host machine. More info:
https://examples.k8s.io/mysql-cinder-pd/README.md ↗

▼ **fsType** `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info:

https://examples.k8s.io/mysql-cinder-pd/README.md↗

▼ readOnly `boolean`

readOnly defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: https://examples.k8s.io/mysql-cinder-pd/README.md↗

▼ secretRef `object`

secretRef is optional: points to a secret object containing parameters used to connect to OpenStack.

▼ name `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names↗

▼ volumeID `string`

required

volumeID used to identify the volume in cinder. More info:

https://examples.k8s.io/mysql-cinder-pd/README.md ↗

▼ **configMap** `object`

configMap represents a configMap that should populate this volume

▼ **defaultMode** `integer`

defaultMode is optional: mode bits used to set permissions on created files by default. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **items** `[]object`

Maps a string key to a path within a volume.

▼ **key** `string`

required

key is the key to project.

▼ mode `integer`

mode is Optional: mode bits used to set permissions on this file. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ path `string`

required

path is the relative path of the file to map the key to. May not be an absolute path. May not contain the path element '..'. May not start with the string '..'.

▼ name `string`

Name of the referent. More info: https://kubernetes.io/docs/concept

s/overview/working-with-objects/names/#names↗

▼ **optional** `boolean`

optional specify whether the ConfigMap or its keys must be defined

▼ **csi** `object`

csi (Container Storage Interface) represents ephemeral storage that is handled by certain external CSI drivers (Beta feature).

▼ **driver** `string` required

driver is the name of the CSI driver that handles this volume. Consult with your admin for the correct name as registered in the cluster.

▼ **fsType** `string`

fsType to mount. Ex. "ext4", "xfs", "ntfs". If not provided, the empty value is passed to the associated CSI driver which will determine the default filesystem to apply.

▼ **nodePublishSecretRef** `object`

nodePublishSecretRef is a reference to the secret object containing sensitive information to pass to the CSI driver to complete the CSI NodePublishVolume and NodeUnpublishVolume calls. This field is optional, and may be empty if no secret is required. If the secret object contains more than one secret, all secret references are passed.

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **readOnly** `boolean`

readOnly specifies a read-only configuration for the volume. Defaults to false (read/write).

▼ **volumeAttributes** `object`

volumeAttributes stores driver-specific properties that are passed to the CSI driver. Consult your

driver's documentation for supported values.

▼ **downwardAPI** `object`

downwardAPI represents downward API about the pod that should populate this volume

▼ **defaultMode** `integer`

Optional: mode bits to use on created files by default. Must be a Optional: mode bits used to set permissions on created files by default. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **items** `[]object`

DownwardAPIVolumeFile represents information to create the file containing the pod field

▼ **fieldRef** `object`

Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.

▼ **apiVersion**
`string`

Version of the schema the FieldPath is written in terms of, defaults to "v1".

▼ **fieldPath**
`string`
required

Path of the field to select in the specified API version.

▼ **mode** `integer`

Optional: mode bits used to set permissions on this file, must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires

decimal values for mode bits. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **path** `string`

required

Required: Path is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the relative path must not start with '..'

▼ **resourceFieldRef** `object`

Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.

▼ **containerName**

`string`

Container name: required for volumes, optional for env vars

▼ **divisor**

Specifies the output format of the exposed resources, defaults to "1"

▼ **resource** `string`

required

Required: resource to select

▼ **emptyDir** `object`

emptyDir represents a temporary directory that shares a pod's lifetime. More info: https://kubernetes.io/docs/concepts/storage/volumes#emptydir↗

▼ **medium** `string`

medium represents what type of storage medium should back this directory. The default is "" which

means to use the node's default medium. Must be an empty string (default) or Memory. More info: https://kubernetes.io/docs/concepts/storage/volumes#emptydir ↗

▼ sizeLimit

sizeLimit is the total amount of local storage required for this EmptyDir volume. The size limit is also applicable for memory medium. The maximum usage on memory medium EmptyDir would be the minimum value between the SizeLimit specified here and the sum of memory limits of all containers in a pod. The default is nil which means that the limit is undefined. More info: https://kubernetes.io/docs/concepts/storage/volumes#emptydir ↗

▼ ephemeral `object`

ephemeral represents a volume that is handled by a cluster storage driver. The volume's lifecycle is tied to the pod that defines it - it will be created before the pod starts, and deleted when the pod is removed.

Use this if: a) the volume is only needed while the pod runs, b) features of normal volumes like restoring from snapshot or capacity tracking are needed, c) the

storage driver is specified through a storage class, and d) the storage driver supports dynamic volume provisioning through a PersistentVolumeClaim (see EphemeralVolumeSource for more information on the connection between this volume type and PersistentVolumeClaim).

Use PersistentVolumeClaim or one of the vendor-specific APIs for volumes that persist for longer than the lifecycle of an individual pod.

Use CSI for light-weight local ephemeral volumes if the CSI driver is meant to be used that way - see the documentation of the driver for more information.

A pod can use both types of ephemeral volumes and persistent volumes at the same time.

▼ **volumeClaimTemplate** `object`

Will be used to create a stand-alone PVC to provision the volume. The pod in which this EphemeralVolumeSource is embedded will be the owner of the PVC, i.e. the PVC will be deleted together with the pod. The name of the PVC will be `<pod name>-<volume name>` where `<volume name>` is the name from the `PodSpec.Volumes` array entry. Pod validation will reject the pod if the concatenated name is not valid for a PVC (for example, too long).

An existing PVC with that name that is not owned by the pod will *not* be used for the pod to avoid using an unrelated volume by mistake. Starting the pod is then blocked until the unrelated PVC is removed. If such a pre-created PVC is meant to be used by the pod, the PVC has to updated with an owner reference to the pod once the pod exists. Normally this should not be necessary, but it may be useful when manually reconstructing a broken cluster.

This field is read-only and no changes will be made by Kubernetes to the PVC after it has been created.

Required, must not be nil.

▼ **metadata** `object`

May contain labels and annotations that will be copied into the PVC when creating it. No other fields are allowed and will be rejected during validation.

▼ **spec** `object`

required

The specification for the PersistentVolumeClaim. The entire content is copied unchanged into the

PVC that gets created from this template. The same fields as in a PersistentVolumeClaim are also valid here.

▼ **accessModes** `[]string`

accessModes contains the desired access modes the volume should have. More info: https://kubernetes.io/docs/concepts/storage/persistent-volumes#access-modes-1↗

▼ **dataSource** `object`

dataSource field can be used to specify either:

- An existing VolumeSnapshot object (snapshot.storage.k8s.io/VolumeSnapshot)

- An existing PVC (PersistentVolumeClaim) If the provisioner or an external controller can support the specified data source, it will create a new volume based on the contents of the specified data source. When the AnyVolumeDataSource feature gate is enabled, dataSource contents will be copied to dataSourceRef, and dataSourceRef contents will be copied to dataSource when dataSourceRef.namespace is not specified. If the namespace is specified, then dataSourceRef

will not be copied to dataSource.

▼ **apiGroup** `string`

APIGroup is the group for the resource being referenced. If APIGroup is not specified, the specified Kind must be in the core API group. For any other third-party types, APIGroup is required.

▼ **kind** `string`

required

Kind is the type of resource being referenced

▼ **name**

`string`

required

Name is the name of resource being referenced

▼ **dataSourceRef**

`object`

dataSourceRef specifies the object from which to populate the volume with data, if a non-empty volume is desired. This may be any object from a non-empty API group (non core object) or a PersistentVolumeClaim object.

When this field is specified, volume binding will only succeed if the type of the specified object matches some installed volume populator or dynamic provisioner. This field will replace the functionality of the dataSource field and as such if both fields are non-empty, they must have the same value. For backwards compatibility, when namespace isn't specified in dataSourceRef, both fields (dataSource and dataSourceRef) will be set to the same value automatically if one of them is empty and the other is non-empty. When namespace is specified in dataSourceRef, dataSource isn't

| | | |

- While dataSource only allows local objects, dataSourceRef allows objects in any namespaces. (Beta) Using this field requires the AnyVolumeDataSource feature gate to be enabled. (Alpha) Using the namespace field of dataSourceRef requires the CrossNamespaceVolumeDataSource feature gate to be enabled.

▼ **apiGroup** `string`

APIGroup is the group for the resource being referenced

. If APIGroup is not specified, the specified Kind must be in the core API group. For any other third-party types, APIGroup is required.

▼ **kind**

`string`

required

Kind is the type of resource being referenced

▼ **name**

`string`

required

Name is the name of resource

being referenced

▼ **namespace** `string`

Namespace is the namespace of resource being referenced Note that when a namespace is specified, a gateway.networking.k8s.io/ReferenceGrant object is required in the referent namespace to allow that namespace's owner to accept the reference.

See the Reference Grant documentation for details. (Alpha) This field requires the CrossNamespaceVolumeDataSource feature gate to be enabled.

▼ resources

`object`

resources represents the minimum resources the volume should have. If RecoverVolumeExpansionFailure feature is enabled users are allowed to specify resource requirements that are lower than previous value but

must still be higher than capacity recorded in the status field of the claim. More info: https://kubernetes.io/docs/concepts/storage/persistent-volumes#resources↗

▼ **limits**
`object`

Limits describes the maximum amount of compute resources allowed. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/↗

▼ **requests**

			`object`	Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. Requests cannot exceed Limits. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-

containers/↗

▼ **selector** `object`

selector is a label query over volumes to consider for binding.

▼ **matchExpressions** `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `s`

key `string` required

key is the label key that the selector applies to.

▼ **operator** `string` required

operator represents a key's relationship to a set of values. Valid operators are In, N

otIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string va

lu
es
. If
th
e
op
er
at
or
is
In
or
N
otI
n,
th
e
va
lu
es
ar
ra
y
m
us
t
be
no
n-
e
m
pt
y.
If
th
e
op

er
at
or
is
Ex
ist
s
or
D
oe
s
N
ot
Ex
ist
,
th
e
va
lu
es
ar
ra
y
m
us
t
be
e
m
pt
y.
Th
is
ar
ra
y

is replaced during a strategic merge patch.

▼ **matchLabels** `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an

element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **storageClassName** `string`

storageClassName is the name of the StorageClass required by the claim. More info: https://kubernetes.io/docs/concepts/storage/persistent-volumes#class-1 ↗

▼ **volumeAttributesClassName**

`string`

volumeAttributesClassName may be used to set the VolumeAttributesClass used by this claim. If specified, the CSI driver will create or update the volume with the attributes defined in the corresponding VolumeAttributesClass. This has a different purpose than storageClassName, it can be changed after the claim is created. An empty string value means that no VolumeAttributesClass will be applied to the claim but it's not allowed to reset this field to empty string once it is set. If unspecified and the PersistentVolumeClaim is unbound, the default VolumeAttributesC

lass will be set by the persistentvolume controller if it exists. If the resource referred to by volumeAttributesClass does not exist, this PersistentVolumeClaim will be set to a Pending state, as reflected by the modifyVolumeStatus field, until such as a resource exists. More info: https://kubernetes.io/docs/concepts/storage/persistent-volumes#volumeattributesclass↗ (Alpha) Using this field requires the VolumeAttributesClass feature gate to be enabled.

▼ volumeMode

`string`

volumeMode defines what type of volume is required by the

claim. Value of Filesystem is implied when not included in claim spec.

▼ **volumeName** `string`

volumeName is the binding reference to the PersistentVolume backing this claim.

▼ **fc** `object`

fc represents a Fibre Channel resource that is attached to a kubelet's host machine and then exposed to the pod.

▼ **fsType** `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.

▼ **lun** `integer`

lun is Optional: FC target lun number

▼ **readOnly** `boolean`

readOnly is Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ **targetWWNs** `[]string`

targetWWNs is Optional: FC target worldwide names (WWNs)

▼ **wwids** `[]string`

wwids Optional: FC volume world wide identifiers (wwids) Either wwids or combination of targetWWNs and lun must be set, but not both simultaneously.

▼ **flexVolume** `object`

flexVolume represents a generic volume resource that is provisioned/attached using an exec based plugin.

▼ **driver** `string` required

driver is the name of the driver to use for this volume.

▼ fsType `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". The default filesystem depends on FlexVolume script.

▼ options `object`

options is Optional: this field holds extra command options if any.

▼ readOnly `boolean`

readOnly is Optional: defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ secretRef `object`

secretRef is Optional: secretRef is reference to the secret object containing sensitive information to pass to the plugin scripts. This may be empty if no secret object is specified. If the secret object contains more than one secret, all secrets are passed to the plugin scripts.

▼ name `string`

Name of the referent.
More info:
https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ flocker `object`

flocker represents a Flocker volume attached to a kubelet's host machine. This depends on the Flocker control service being running

▼ datasetName `string`

datasetName is Name of the dataset stored as metadata -> name on the dataset for Flocker should be considered as deprecated

▼ datasetUUID `string`

datasetUUID is the UUID of the dataset. This is unique identifier of a Flocker dataset

▼ gcePersistentDisk `object`

gcePersistentDisk represents a GCE Disk resource that is attached to a kubelet's host machine and then exposed to the

pod. More info: https://kubernetes.io/docs/concepts/storage/volumes#gcepersistentdisk ↗

▼ **fsType** `string`

fsType is filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: https://kubernetes.io/docs/concepts/storage/volumes#gcepersistentdisk ↗

▼ **partition** `integer`

partition is the partition in the volume that you want to mount. If omitted, the default is to mount by volume name. Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty). More info: https://kubernetes.io/docs/concepts/storage/volumes#gcepersistentdisk ↗

▼ **pdName** `string` required

pdName is unique name of the PD resource in GCE. Used to identify the disk in GCE. More info: https://kubernetes.io/docs/concepts/storage/volumes#gcepersistentdisk ↗

▼ **readOnly** `boolean`

readOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: https://kubernetes.io/docs/concepts/storage/volumes#gcepersistentdisk ↗

▼ **gitRepo** `object`

gitRepo represents a git repository at a particular revision. DEPRECATED: GitRepo is deprecated. To provision a container with a git repo, mount an EmptyDir into an InitContainer that clones the repo using git, then mount the EmptyDir into the Pod's container.

▼ **directory** `string`

directory is the target directory name. Must not contain or start with '..'. If '.' is supplied, the volume directory will be the git repository. Otherwise, if specified, the volume

will contain the git repository in the subdirectory with the given name.

▼ **repository** `string`

required

repository is the URL

▼ **revision** `string`

revision is the commit hash for the specified revision.

▼ **glusterfs** `object`

glusterfs represents a Glusterfs mount on the host that shares a pod's lifetime. More info: https://examples.k8s.io/volumes/glusterfs/README.md ↗

▼ **endpoints** `string`

required

endpoints is the endpoint name that details Glusterfs topology. More info: https://examples.k8s.io/volumes/glusterfs/README.md#create-a-pod ↗

▼ **path** `string` required

path is the Glusterfs volume path. More info: https://examples.k8s.io/volumes/glusterfs/README.md#create-a-pod ↗

▼ **readOnly** `boolean`

readOnly here will force the Glusterfs volume to be mounted with read-only permissions. Defaults to false. More info: https://examples.k8s.io/volumes/glusterfs/README.md#create-a-pod ↗

▼ **hostPath** `object`

hostPath represents a pre-existing file or directory on the host machine that is directly exposed to the container. This is generally used for system agents or other privileged things that are allowed to see the host machine. Most containers will NOT need this. More info: https://kubernetes.io/docs/concepts/storage/volumes#hostpath ↗

▼ **path** `string` required

path of the directory on the host. If the path is a symlink, it will follow the link to the real path. More info:

https://kubernetes.io/docs/concepts/storage/volumes#hostpath ↗

▼ **type** `string`

type for HostPath Volume Defaults to "" More info: https://kubernetes.io/docs/concepts/storage/volumes#hostpath ↗

▼ **iscsi** `object`

iscsi represents an ISCSI Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: https://examples.k8s.io/volumes/iscsi/README.md ↗

▼ **chapAuthDiscovery** `boolean`

chapAuthDiscovery defines whether support iSCSI Discovery CHAP authentication

▼ **chapAuthSession** `boolean`

chapAuthSession defines whether support iSCSI Session CHAP authentication

▼ fsType `string`

fsType is the filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: https://kubernetes.io/docs/concepts/storage/volumes#iscsi ↗

▼ initiatorName `string`

initiatorName is the custom iSCSI Initiator Name. If initiatorName is specified with iscsiInterface simultaneously, new iSCSI interface : will be created for the connection.

▼ iqn `string` required

iqn is the target iSCSI Qualified Name.

▼ iscsiInterface `string`

iscsiInterface is the interface Name that uses an iSCSI transport. Defaults to 'default' (tcp).

▼ **lun** `integer` required

lun represents iSCSI Target Lun number.

▼ **portals** `[]string`

portals is the iSCSI Target Portal List. The portal is either an IP or ip_addr:port if the port is other than default (typically TCP ports 860 and 3260).

▼ **readOnly** `boolean`

readOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false.

▼ **secretRef** `object`

secretRef is the CHAP Secret for iSCSI target and initiator authentication

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **targetPortal** `string`

required

targetPortal is iSCSI Target Portal. The Portal is either an IP or ip_addr:port if the port is other than default (typically TCP ports 860 and 3260).

▼ **name** `string` required

name of the volume. Must be a DNS_LABEL and unique within the pod. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **nfs** `object`

nfs represents an NFS mount on the host that shares a pod's lifetime More info: https://kubernetes.io/docs/concepts/storage/volumes#nfs ↗

▼ **path** `string` required

path that is exported by the NFS server. More info: https://kubernetes.io/docs/concepts/storage/volumes#nfs ↗

▼ **readOnly** `boolean`

readOnly here will force the NFS export to be mounted with read-only permissions. Defaults to false. More info: https://kubernetes.io/docs/concepts/storage/volumes#nfs ↗

▼ **server** `string` required

server is the hostname or IP address of the NFS server. More info: https://kubernetes.io/docs/concepts/storage/volumes#nfs ↗

▼ **persistentVolumeClaim** `object`

persistentVolumeClaimVolumeSource represents a reference to a PersistentVolumeClaim in the same namespace. More info: https://kubernetes.io/docs/concepts/storage/persistent-volumes#persistentvolumeclaims ↗

▼ **claimName** `string` required

claimName is the name of a PersistentVolumeClaim in the same namespace as the pod using this volume. More info: https://kubernetes.io/docs/concepts/storage/persistent-

volumes#persistentvolumeclaims ↗

▼ **readOnly** `boolean`

readOnly Will force the ReadOnly setting in VolumeMounts. Default false.

▼ **photonPersistentDisk** `object`

photonPersistentDisk represents a PhotonController persistent disk attached and mounted on kubelets host machine

▼ **fsType** `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.

▼ **pdID** `string` required

pdID is the ID that identifies Photon Controller persistent disk

▼ **portworxVolume** `object`

portworxVolume represents a portworx volume attached and mounted on kubelets

host machine

▼ **fsType** `string`

fSType represents the filesystem type to mount Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs". Implicitly inferred to be "ext4" if unspecified.

▼ **readOnly** `boolean`

readOnly defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ **volumeID** `string`

required

volumeID uniquely identifies a Portworx volume

▼ **projected** `object`

projected items for all in one resources secrets, configmaps, and downward API

▼ **defaultMode** `integer`

defaultMode are the mode bits used to set permissions on created files by default. Must be an octal value between 0000 and

0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ sources `[]object`

Projection that may be projected along with other supported volume types

▼ clusterTrustBundle `object`

ClusterTrustBundle allows a pod to access the `.spec.trustBundle` field of ClusterTrustBundle objects in an auto-updating file.

Alpha, gated by the ClusterTrustBundleProjection feature gate.

ClusterTrustBundle objects can either be selected by name, or by the combination of signer name and a label selector.

Kubelet performs aggressive normalization

of the PEM contents written into the pod filesystem. Esoteric PEM features such as inter-block comments and block headers are stripped. Certificates are deduplicated. The ordering of certificates within the file is arbitrary, and Kubelet may change the order over time.

▼ **labelSelector**
`object`

Select all ClusterTrustBundles that match this label selector. Only has effect if signerName is set. Mutually-exclusive with name. If unset, interpreted as "match nothing". If set but empty, interpreted as "match everything".

▼ **matchExpressions**
`[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string` required

key is the label key that th

e se le ct or ap pli es to.

▼ **operator** `string` required

op er at or re pr es en ts a ke y's rel ati on sh ip to a

set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values**

`[]string`

values is an array of string values. If the operator is In or NotIn, the valu

esarraymustbenon-empty.Ifthe operatorisExistsorDoesNotExist,theva

lu
es
ar
ra
y
m
us
t
be
e
m
pt
y.
Th
is
ar
ra
y
is
re
pl
ac
ed
du
rin
g
a
str
at
eg
ic
m
er
ge
pa
tc
h.

▼ **matchLabels** `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **name**

`string`

Select a single ClusterTrustBundle by object name. Mutually-exclusive with signerName and labelSelector.

▼ **optional**

`boolean`

If true, don't block pod startup if the referenced ClusterTrustBundle(s) aren't available. If using name, then the named ClusterTrustBundle is allowed not to exist. If using signerName, then the combination of signerName and labelSelector is allowed to match zero ClusterTrustBundles.

▼ **path**

`string`

required

Relative path from the volume root to write the bundle.

▼ **signerName** `string`

Select all ClusterTrustBundles that match this signer name. Mutually-exclusive with name. The contents of all selected ClusterTrustBundles will be unified and deduplicated.

▼ **configMap** `object`

configMap information about the configMap data to project

▼ **items** `[]object`

Maps a string key to a path within a volume.

▼ **key**

`string`

required

key is the key to project.

▼ **mode**

`integer`

mode is Optional: mode bits used to set permissions on this file. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON

requires decimal values for mode bits. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **path**

`string`

required

path is the relative path of the file to map the key to. May not be an

absolute path. May not contain the path element '..'. May not start with the string '..'.

▼ name

`string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ optional

`boolean`

optional specify whether the ConfigMap or its keys must be defined

▼ **downwardAPI**
`object`

downwardAPI information about the downwardAPI data to project

▼ **items**
`[]object`

DownwardAPIVolumeFile represents information to create the file containing the pod field

▼ **fieldRef**
`object`

Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.

▼ **apiVersion**
`str`

`string`

Version of the schema the Field Path is written in terms of, defaults to "v1".

▼ **fieldPath** `string` required

Path of the field to select in the specified API version.

▼ **mode** `integer`

Optional: mode bits used to set permissions on this file, must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. If not specified, the volume defaultMode will be

used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **path**

`string`

required

Required: Path is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the

relative path must not start with '..'

▼ **resourceFieldRef** `object`

Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.

▼ **containerName** `string`

C on

tainer name: required for volumes, optional for env vars

▼ **divisor**

Specifies the

output format of the exposed resources, defaults to "1"

▼ **resource** `string` required

Requir

ed
:
re
so
ur
ce
to
se
le
ct

▼ **secret** `object`

secret information about the secret data to project

▼ **items** `[]object`

Maps a string key to a path within a volume.

▼ **key** `string` required

key is the key to project.

▼ **mode** `integer`

| | | |

with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **path**

`string`

required

path is the relative path of the file to map the key to. May not be an absolute path. May not contain the path element '..'. May not start with the string '..'.

▼ **name**

`string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional**

`boolean`

optional field specify whether the Secret or its key must be defined

▼ **serviceAccountToken**

`object`

serviceAccountToken is information about the serviceAccountToken data to project

▼ **audience**

`string`

audience is the intended audience of the token. A recipient of a token must identify itself with an identifier specified in the audience of the token, and otherwise should reject the token. The audience defaults to the identifier of the apiserver.

▼ **expirationSeconds** `integer`

expirationSeconds is the requested duration of validity of the service account token. As the token approaches expiration, the kubelet volume plugin will proactively rotate the service account token. The kubelet will start trying to rotate the token if

the token is older than 80 percent of its time to live or if the token is older than 24 hours.Defaults to 1 hour and must be at least 10 minutes.

▼ **path** `string`

required

path is the path relative to the mount point of the file to project the token into.

▼ **quobyte** `object`

quobyte represents a Quobyte mount on the host that shares a pod's lifetime

▼ **group** `string`

group to map volume access to Default is no group

▼ **readOnly** `boolean`

readOnly here will force the Quobyte volume to be mounted

with read-only permissions.
Defaults to false.

▼ **registry** `string` required

registry represents a single or multiple Quobyte Registry services specified as a string as host:port pair (multiple entries are separated with commas) which acts as the central registry for volumes

▼ **tenant** `string`

tenant owning the given Quobyte volume in the Backend Used with dynamically provisioned Quobyte volumes, value is set by the plugin

▼ **user** `string`

user to map volume access to
Defaults to serivceaccount user

▼ **volume** `string` required

volume is a string that references an already created Quobyte volume by name.

▼ **rbd** `object`

rbd represents a Rados Block Device mount on the host that shares a pod's lifetime. More info: https://examples.k8s.io/volumes/rbd/README.md ↗

▼ fsType `string`

fsType is the filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: https://kubernetes.io/docs/concepts/storage/volumes#rbd ↗

▼ image `string` required

image is the rados image name. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ keyring `string`

keyring is the path to key ring for RBDUser. Default is /etc/ceph/keyring. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ monitors `[]string`

required

monitors is a collection of Ceph monitors. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ pool `string`

pool is the rados pool name. Default is rbd. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ readOnly `boolean`

readOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ secretRef `object`

secretRef is name of the authentication secret for RBDUser. If provided overrides keyring. Default is nil. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ name `string`

Name of the referent.

More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **user** `string`

user is the rados user name. Default is admin. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ **scaleIO** `object`

scaleIO represents a ScaleIO persistent volume attached and mounted on Kubernetes nodes.

▼ **fsType** `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Default is "xfs".

▼ **gateway** `string` required

gateway is the host address of the ScaleIO API Gateway.

▼ protectionDomain `string`

protectionDomain is the name of the ScaleIO Protection Domain for the configured storage.

▼ readOnly `boolean`

readOnly Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ secretRef `object`

required

secretRef references to the secret for ScaleIO user and other sensitive information. If this is not provided, Login operation will fail.

▼ name `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ sslEnabled `boolean`

sslEnabled Flag enable/disable SSL communication with Gateway, default false

▼ **storageMode** `string`

storageMode indicates whether the storage for a volume should be ThickProvisioned or ThinProvisioned. Default is ThinProvisioned.

▼ **storagePool** `string`

storagePool is the ScaleIO Storage Pool associated with the protection domain.

▼ **system** `string` required

system is the name of the storage system as configured in ScaleIO.

▼ **volumeName** `string`

volumeName is the name of a volume already created in the ScaleIO system that is associated with this volume source.

▼ **secret** `object`

secret represents a secret that should populate this volume. More info: https://kubernetes.io/docs/concepts/storage/volumes#secret ↗

▼ **defaultMode** `integer`

defaultMode is Optional: mode bits used to set permissions on created files by default. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **items** `[]object`

Maps a string key to a path within a volume.

▼ **key** `string`

required

key is the key to project.

▼ **mode** `integer`

mode is Optional: mode bits used to set permissions on this file. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **path** `string`

required

path is the relative path of the file to map the key to. May not be an absolute path. May not contain the path element '..'. May not start with the string '..'.

▼ **optional** `boolean`

optional field specify whether the Secret or its keys must be defined

▼ secretName `string`

secretName is the name of the secret in the pod's namespace to use. More info: https://kubernetes.io/docs/concepts/storage/volumes#secret ↗

▼ storageos `object`

storageOS represents a StorageOS volume attached and mounted on Kubernetes nodes.

▼ fsType `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.

▼ readOnly `boolean`

readOnly defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ secretRef `object`

secretRef specifies the secret to use for obtaining the StorageOS

API credentials. If not specified, default values will be attempted.

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **volumeName** `string`

volumeName is the human-readable name of the StorageOS volume. Volume names are only unique within a namespace.

▼ **volumeNamespace** `string`

volumeNamespace specifies the scope of the volume within StorageOS. If no namespace is specified then the Pod's namespace will be used. This allows the Kubernetes name scoping to be mirrored within StorageOS for tighter integration. Set VolumeName to any name to override the default behaviour. Set to "default" if you are not using namespaces within StorageOS.

Namespaces that do not pre-exist within StorageOS will be created.

▼ vsphereVolume `object`

vsphereVolume represents a vSphere volume attached and mounted on kubelets host machine

▼ fsType `string`

fsType is filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.

▼ storagePolicyID `string`

storagePolicyID is the storage Policy Based Management (SPBM) profile ID associated with the StoragePolicyName.

▼ storagePolicyName `string`

storagePolicyName is the storage Policy Based Management (SPBM) profile name.

▼ volumePath `string`

required

volumePath is the path that identifies vSphere volume vmdk

▼ serviceAccountName `string`

▼ triggers `[]object` required

EventListenerTrigger represents a connection between TriggerBinding, Params, and TriggerTemplate; TriggerBinding provides extracted values for TriggerTemplate to then create resources from. TriggerRef can also be provided instead of TriggerBinding, Interceptors and TriggerTemplate

▼ bindings `[]object`

▼ apiversion `string`

APIVersion of the binding ref

▼ kind `string`

Kind can only be provided if Ref is also provided. Defaults to TriggerBinding

▼ name `string`

Name is the name of the binding param Mutually exclusive with Ref

▼ ref `string`

Ref is a reference to a TriggerBinding kind. Mutually exclusive with Name

▼ **value** `string`

Value is the value of the binding param. Can contain JSONPath Has to be pointer since "" is a valid value Required if Name is also specified.

▼ **interceptors** `[]object`

TriggerInterceptor provides a hook to intercept and pre-process events

▼ **bitbucket** `object`

BitbucketInterceptor provides a webhook to intercept and pre-process events

▼ **eventTypes** `[]string`

▼ **secretRef** `object`

SecretRef contains the information required to reference a single secret string This is needed because the other secretRef types are not cross-namespace and do not actually contain the "SecretName" field, which allows us to access a single secret value.

▼ **secretKey** `string`

▼ **secretName** `string`

▼ cel `object`

CELInterceptor provides a webhook to intercept and pre-process events

▼ filter `string`

▼ overlays `[]object`

CELOverlay provides a way to modify the request body using DeprecatedCEL expressions

▼ expression `string`

▼ key `string`

▼ github `object`

Deprecated old fields below

▼ eventTypes `[]string`

▼ secretRef `object`

SecretRef contains the information required to reference a single secret string This is needed because the other secretRef types are not cross-namespace and do not actually contain the "SecretName" field, which allows us to access a single secret value.

▼ **secretKey** `string`

▼ **secretName** `string`

▼ **gitlab** `object`

GitLabInterceptor provides a webhook to intercept and pre-process events

▼ **eventTypes** `[]string`

▼ **secretRef** `object`

SecretRef contains the information required to reference a single secret string This is needed because the other secretRef types are not cross-namespace and do not actually contain the "SecretName" field, which allows us to access a single secret value.

▼ **secretKey** `string`

▼ **secretName** `string`

▼ **name** `string`

Optional name to identify the current interceptor configuration

▼ params `[]object`

InterceptorParams defines a key-value pair that can be passed on an interceptor

▼ name `string` required

▼ value required

▼ ref `object` required

Ref refers to the Interceptor to use

▼ apiVersion `string`

API version of the referent

▼ kind `string`

InterceptorKind indicates the kind of the Interceptor, namespaced or cluster scoped.

▼ name `string`

Name of the referent; More info: http://kubernetes.io/docs/user-guide/identifiers#names ↗

▼ webhook `object`

WebhookInterceptor refers to an old style webhook interceptor service

▼ header `[]object`

Param declares an ParamValues to use for the parameter called name.

▼ name `string` required

▼ value `object` required

ParamValue is a type that can hold a single string or string array. Used in JSON unmarshalling so that a single JSON field can accept either an individual string or an array of strings.

▼ objectRef `object`

ObjectRef is a reference to an object that will resolve to a cluster DNS name to use as the EventInterceptor. Either objectRef or url can be specified

▼ apiVersion `string`

API version of the referent.

▼ fieldPath `string`

If referring to a piece of an object instead of an entire object, this string should contain a valid JSON/Go field access statement, such as desiredState.manifest.containers[2]. For example, if the object reference is to a container within a pod, this would take on a value like: "spec.containers{name}" (where "name" refers to the name of the container that triggered

the event) or if no container name is specified "spec.containers[2]" (container with index 2 in this pod). This syntax is chosen only to have some well-defined way of referencing a part of an object.

▼ kind `string`

Kind of the referent. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds ↗

▼ name `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ namespace `string`

Namespace of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/namespaces/ ↗

▼ resourceVersion `string`

Specific resourceVersion to which this reference is made, if any. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#concurrency-control-and-consistency ↗

▼ uid `string`

UID of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#uids ↗

▼ **url** `string`

▼ **name** `string`

▼ **serviceAccountName** `string`

ServiceAccountName optionally associates credentials with each trigger; more granular authorization for who is allowed to utilize the associated pipeline vs. defaulting to whatever permissions are associated with the entire EventListener and associated sink facilitates multi-tenant model based scenarios

▼ **template** `object`

▼ **apiversion** `string`

▼ **ref** `string`

▼ **spec** `object`

TriggerTemplateSpec holds the desired state of TriggerTemplate

▼ **params** `[]object`

ParamSpec defines an arbitrary named input whose value can be supplied by a `Param`.

▼ **default** `string`

Default is the value a parameter takes if no input value via a Param is supplied.

▼ **description** `string`

Description is a user-facing description of the parameter that may be used to populate a UI.

▼ **name** `string` required

Name declares the name by which a parameter is referenced.

▼ **resourcetemplates** `[]object`

TriggerResourceTemplate describes a resource to create

▼ **triggerRef** `string`

▼ **status** `object`

EventListenerStatus holds the status of the EventListener

▼ **address** `object`

Address is a single Addressable address. If Addresses is present, Address will be ignored by clients.

▼ **CACerts** `string`

CACerts is the Certification Authority (CA) certificates in PEM format according to https://www.rfc-editor.org/rfc/rfc7468↗.

▼ **hostname** `string`

▼ **name** `string`

Name is the name of the address.

▼ **url** `string`

▼ **addresses** `[]object`

Addressable provides a generic mechanism for a custom resource definition to indicate a destination for message delivery.

Addressable is the schema for the destination information. This is typically stored in the object's `status`, as this information may be generated by the controller.

▼ **CACerts** `string`

CACerts is the Certification Authority (CA) certificates in PEM format according to https://www.rfc-editor.org/rfc/rfc7468↗.

▼ **hostname** `string`

▼ name `string`

Name is the name of the address.

▼ url `string`

▼ annotations `object`

Annotations is additional Status fields for the Resource to save some additional State as well as convey more information to the user. This is roughly akin to Annotations on any k8s resource, just the reconciler conveying richer information outwards.

▼ conditions `[]object`

Condition defines a readiness condition for a Knative resource. See: https://github.com/kubernetes/community/blob/master/contributors/devel/sig-architecture/api-conventions.md#typical-status-properties ↗

▼ lastTransitionTime `string`

LastTransitionTime is the last time the condition transitioned from one status to another. We use VolatileTime in place of metav1.Time to exclude this from creating equality.Semantic differences (all other things held constant).

▼ message `string`

A human readable message indicating details about the transition.

▼ reason `string`

The reason for the condition's last transition.

▼ **severity** `string`

Severity with which to treat failures of this type of condition. When this is not specified, it defaults to Error.

▼ **status** `string` required

Status of the condition, one of True, False, Unknown.

▼ **type** `string` required

Type of condition.

▼ **configuration** `object` required

Configuration stores configuration for the EventListener service

▼ **generatedName** `string` required

GeneratedResourceName is the name given to all resources reconciled by the EventListener

▼ **observedGeneration** `integer`

ObservedGeneration is the 'Generation' of the Service that was last processed by the controller.

EventListener exposes a service to accept HTTP event payloads.

`v1beta1` version

▼ spec `object`

Spec holds the desired state of the EventListener from the client

▼ cloudEventURI `string`

▼ labelSelector `object`

A label selector is a label query over a set of resources. The result of matchLabels and matchExpressions are ANDed. An empty label selector matches all objects. A null label selector matches no objects.

▼ matchExpressions `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ key `string` required

key is the label key that the selector applies to.

▼ operator `string` required

operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ values `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.

▼ **matchLabels** `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **namespaceSelector** `object`

NamespaceSelector is a selector for selecting either all namespaces or a list of namespaces.

▼ **matchNames** `[]string`

List of namespace names.

▼ **resources** `object`

▼ **customResource** `object`

▼ **kubernetesResource** `object`

▼ **replicas** `integer`

▼ **serviceLoadBalancerClass** `string`

▼ **servicePort** `integer`

▼ serviceType `string`

Service Type string describes ingress methods for a service

▼ spec `object`

WithPodSpec is the shell around the PodSpecable within WithPod.

▼ template `object`

PodSpecable is implemented by types containing a PodTemplateSpec in the manner of ReplicaSet, Deployment, DaemonSet, StatefulSet.

▼ metadata `object`

Standard object's metadata. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#metadata ↗

▼ spec `object`

Specification of the desired behavior of the pod. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#spec-and-status ↗

▼ activeDeadlineSeconds `integer`

Optional duration in seconds the pod may be active on the node relative to StartTime before the system will actively try to mark it failed and kill associated containers. Value must be a positive integer.

▼ **affinity** `object`

If specified, the pod's scheduling constraints

▼ **nodeAffinity** `object`

Describes node affinity scheduling rules for the pod.

▼ **preferredDuringSchedulingIgnoredDuringExecution** `[]object`

An empty preferred scheduling term matches all objects with implicit weight 0 (i.e. it's a no-op). A null preferred scheduling term matches no objects (i.e. is also a no-op).

▼ **preference** `object` required

A node selector term, associated with the corresponding weight.

▼ **matchExpressions** `[]object`

A node selector requirement is a selector that contains values, a key, and an operator that

relates the key and values.

▼ **key**
`string`
required

The label key that the selector applies to.

▼ **operator**
`string`
required

Represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists, DoesNotExist. Gt, and Lt.

▼ **values**
`[]string`

| | | |

merge patch.

▼ **matchFields**
`[]object`

A node selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**
`string`
required

The label key that the selector applies to.

▼ **operator**
`string`
required

Represents a key's relationship to a set of values. Valid

operators are In, NotIn, Exists, DoesNotExist. Gt, and Lt.

▼ **values** `[]string`

An array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. If the operator is Gt or Lt, the values array must

have a single element, which will be interpreted as an integer. This array is replaced during a strategic merge patch.

▼ **weight** `integer`

required

Weight associated with matching the corresponding nodeSelectorTerm, in the range 1-100.

▼ **requiredDuringSchedulingIgnoredDuringExecution** `object`

If the affinity requirements specified by this field are not met at scheduling time, the pod will not be scheduled onto the node. If the affinity requirements specified by

this field cease to be met at some point during pod execution (e.g. due to an update), the system may or may not try to eventually evict the pod from its node.

▼ **nodeSelectorTerms**

`[]object` required

A null or empty node selector term matches no objects. The requirements of them are ANDed. The TopologySelectorTerm type implements a subset of the NodeSelectorTerm.

▼ **matchExpressions**

`[]object`

A node selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**

`string`

required

The label key that the

selector applies to.

▼ **operator** `string`

required

Represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists, DoesNotExist. Gt, and Lt.

▼ **values** `[]string`

An array of string values. If the operator is In or NotIn, the values array must be non-

empty. If the operator is Exists or DoesNotExist, the values array must be empty. If the operator is Gt or Lt, the values array must have a single element, which will be interpreted as an integer. This array is replaced during a strategic merge patch.

▼ **matchFields** `[]object`

A node selector requirement is a selector that

contains values, a key, and an operator that relates the key and values.

▼ **key**

`string`

required

The label key that the selector applies to.

▼ **operator**

`string`

required

Represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists, DoesNotExist. Gt, and Lt.

▼ **values** `[]string`

An array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. If the operator is Gt or Lt, the values array must have a single element, which will be interpreted as an integer. This array

is replaced during a strategic merge patch.

▼ **podAffinity** `object`

Describes pod affinity scheduling rules (e.g. co-locate this pod in the same node, zone, etc. as some other pod(s)).

▼ **preferredDuringSchedulingIgnoredDuringExecution** `[]object`

The weights of all of the matched WeightedPodAffinityTerm fields are added per-node to find the most preferred node(s)

▼ **podAffinityTerm** `object` required

Required. A pod affinity term, associated with the corresponding weight.

▼ **labelSelector** `object`

A label query over a set of resources, in this case pods.

If it's null, this PodAffinityTerm matches with no Pods.

▼ **matchExpressions** `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string` required

key is

th
e
la
be
l
ke
y
th
at
th
e
se
le
ct
or
ap
pli
es
to.

▼ **operator** `string` required

op
er
at
or
re
pr
es
en
ts

a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoeNot

s
N
ot
Ex
ist
.

▼ **values** `[]string`

va
lu
es
is
an
ar
ra
y
of
str
in
g
va
lu
es
. If
th
e
op
er
at
or

is In or N otI n, th e va lu es ar ra y m us t be no n- e m pt y. If th e op er at or is Ex ist s or D

oe
s
N
ot
Ex
ist
,
th
e
va
lu
es
ar
ra
y
m
us
t
be
e
m
pt
y.
Th
is
ar
ra
y
is
re
pl
ac
ed
du
rin
g
a

str
at
eg
ic
m
er
ge
pa
tc
h.

▼ **matchLabels** `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values

array contains only "value". The requirements are ANDed.

▼ **matchLabelKeys** `[]string`

MatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key in (value)` to select the group of existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't

exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MatchLabelKeys and LabelSelector. Also, MatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysIn PodAffinity feature gate.

▼ **mismatchLabelKeys** `[]string`

MismatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those

key-value labels are merged with `LabelSelector` as `key notin (value)` to select the group of existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MismatchLabelKeys and LabelSelector. Also, MismatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysInPodAffinity feature gate.

▼

namespaceSelector `object`

A label query over the set of namespaces that the term applies to. The term is applied to the union of the namespaces selected by this field and the ones listed in the namespaces field. null selector and null or empty namespaces list means "this pod's namespace". An empty selector ({}) matches all namespaces.

▼

matchExpressions `[]object`

A label selector requirement is a selector that contains

values, a key, and an operator that relates the key and values.

▼ **key** `string` required

key is the label key that the selector applies

es
to.

▼ **operator** `string` required

op
er
at
or
re
pr
es
en
ts
a
ke
y's
rel
ati
on
sh
ip
to
a
se
t
of
va
lu
es
.

Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

valu

es is an array of string values. If the operator is In or NotIn, the values array must

be
no
n-
e
m
pt
y.
If
th
e
op
er
at
or
is
Ex
ist
s
or
D
oe
s
N
ot
Ex
ist
,
th
e
va
lu
es
ar
ra
y
m
us

t
be
e
m
pt
y.
Th
is
ar
ra
y
is
re
pl
ac
ed
du
rin
g
a
str
at
eg
ic
m
er
ge
pa
tc
h.

▼ **matchLabels** `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **namespaces** `[]string`

namespaces specifies a static list of namespace

names that the term applies to. The term is applied to the union of the namespaces listed in this field and the ones selected by namespaceSelect or. null or empty namespaces list and null namespaceSelect or means "this pod's namespace".

▼ topologyKey

`string`

required

This pod should be co-located (affinity) or not co-located (anti-affinity) with the pods matching the labelSelector in the specified namespaces, where co-located is defined as running on a node whose value of the label with key topologyKey

matches that of any node on which any of the selected pods is running. Empty topologyKey is not allowed.

▼ **weight** `integer`

required

weight associated with matching the corresponding podAffinityTerm, in the range 1-100.

▼ **requiredDuringSchedulingIgnoredDuringExecution** `[]object`

Defines a set of pods (namely those matching the labelSelector relative to the given namespace(s)) that this pod should be co-located (affinity) or not co-located (anti-affinity) with, where co-located is defined as running on a node whose value of the label with key matches that of any node on which a pod of the set of pods is running

▼ **labelSelector**

`object`

A label query over a set of resources, in this case pods. If it's null, this PodAffinityTerm matches with no Pods.

▼ **matchExpressions**

`[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**

`string`

required

key is the label key that the selector applies to.

▼ **operator**

`string`

required

operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values

array must be empty. This array is replaced during a strategic merge patch.

▼ matchLabels

`object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ matchLabelKeys

`[]string`

MatchLabelKeys is a set of pod label keys to select

which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key in (value)` to select the group of existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MatchLabelKeys and LabelSelector. Also, MatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysInPodAffinity feature gate.

▼ **mismatchLabelKeys** `[]string`

MismatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to

lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key notin (value)` to select the group of existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MismatchLabelKeys and LabelSelector. Also, MismatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysInPodAffinity feature gate.

▼ **namespaceSelector** `object`

A label query over the set of namespaces that the term applies to. The term is applied to the union of the namespaces selected by this field and the ones

listed in the namespaces field. null selector and null or empty namespaces list means "this pod's namespace". An empty selector ({}) matches all namespaces.

▼ **matchExpressions**
`[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**
`string`
required

key is the label key that the selector applies to.

▼ **operator**
`string`
required

operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values

array must be empty. This array is replaced during a strategic merge patch.

▼ matchLabels

`object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ namespaces

`[]string`

namespaces specifies a static list of namespace

names that the term applies to. The term is applied to the union of the namespaces listed in this field and the ones selected by namespaceSelector. null or empty namespaces list and null namespaceSelector means "this pod's namespace".

▼ **topologyKey**

`string` required

This pod should be co-located (affinity) or not co-located (anti-affinity) with the pods matching the labelSelector in the specified namespaces, where co-located is defined as running on a node whose value of the label with key topologyKey matches that of any node on which any of the selected pods is running. Empty topologyKey is not allowed.

▼ **podAntiAffinity** `object`

Describes pod anti-affinity scheduling rules (e.g. avoid putting this pod in the same

node, zone, etc. as some other pod(s)).

▼ **preferredDuringSchedulingIgnoredDuringExecution** `[]object`

The weights of all of the matched WeightedPodAffinityTerm fields are added per-node to find the most preferred node(s)

▼ **podAffinityTerm** `object` required

Required. A pod affinity term, associated with the corresponding weight.

▼ **labelSelector** `object`

A label query over a set of resources, in this case pods. If it's null, this PodAffinityTerm matches with no Pods.

▼ **matchExpressions** `[]object`

A label selector requireme

nt is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string` required

key is the label key that the selector

ct
or
ap
pli
es
to.

▼ **operator** `string` required

op
er
at
or
re
pr
es
en
ts
a
ke
y's
rel
ati
on
sh
ip
to
a
se
t
of

values.Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]str`

`string` values is an array of string values. If the operator is In or NotIn, the values array

y
m
us
t
be
no
n-
e
m
pt
y.
If
th
e
op
er
at
or
is
Ex
ist
s
or
D
oe
s
N
ot
Ex
ist
,
th
e
va
lu
es
ar

array must be empty. This array is replaced during a strategic merge patch.

▼

matchLabels

`object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼

matchLabelKeys `[]string`

MatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key in (value)` to select the group of existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MatchLabelKeys and LabelSelector.

Also, MatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysIn PodAffinity feature gate.

▼ **mismatchLabelKeys** `[]string`

MismatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key notin (value)` to select the group of existing pods which pods will be taken into consideration for

the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MismatchLabelKeys and LabelSelector. Also, MismatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysInPodAffinity feature gate.

▼ **namespaceSelector** `object`

A label query over the set of namespaces that the term applies to. The term is applied to the

union of the namespaces selected by this field and the ones listed in the namespaces field. null selector and null or empty namespaces list means "this pod's namespace". An empty selector ({}) matches all namespaces.

▼ **matchExpressions** `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string` required

key is the label key that the selector applies to.

▼ **operator** `string`

g

required

operator represents a key's relationship to a set of values. Valid operators are

In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of strin

g
va
lu
es
. If
th
e
op
er
at
or
is
In
or
N
otI
n,
th
e
va
lu
es
ar
ra
y
m
us
t
be
no
n-
e
m
pt
y.
If
th

e
op
er
at
or
is
Ex
ist
s
or
D
oe
s
N
ot
Ex
ist
,
th
e
va
lu
es
ar
ra
y
m
us
t
be
e
m
pt
y.
Th
is
ar

ra
y
is
re
pl
ac
ed
du
rin
g
a
str
at
eg
ic
m
er
ge
pa
tc
h.

▼ **matchLabels** `object`

matchLab
els is a
map of
{key,value
} pairs. A
single
{key,value
} in the
matchLab
els map is

equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **namespaces** `[]string`

namespaces specifies a static list of namespace names that the term applies to. The term is applied to the union of the namespaces listed in this field and the ones selected by namespaceSelector. null or empty

namespaces list and null namespaceSelect or means "this pod's namespace".

▼ **topologyKey**

`string`

required

This pod should be co-located (affinity) or not co-located (anti-affinity) with the pods matching the labelSelector in the specified namespaces, where co-located is defined as running on a node whose value of the label with key topologyKey matches that of any node on which any of the selected pods is running. Empty topologyKey is not allowed.

▼ **weight** `integer`

required

weight associated with matching the corresponding podAffinityTerm, in the range 1-100.

▼ **requiredDuringSchedulingIgnoredDuringExecution** `[]object`

Defines a set of pods (namely those matching the labelSelector relative to the given namespace(s)) that this pod should be co-located (affinity) or not co-located (anti-affinity) with, where co-located is defined as running on a node whose value of the label with key matches that of any node on which a pod of the set of pods is running

▼ **labelSelector** `object`

A label query over a set of resources, in this case pods. If it's null, this PodAffinityTerm matches with no Pods.

▼ **matchExpressions**
`[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key**
`string`
required

key is the label key that the selector applies to.

▼ **operator**
`string`
required

operator represents a key's relationship to a set of values. Valid operators

are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic

merge patch.

▼ matchLabels

`object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ matchLabelKeys

`[]string`

MatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as

`key in (value)` to select the group of existing pods which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MatchLabelKeys and LabelSelector. Also, MatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysInPodAffinity feature gate.

▼ **mismatchLabelKeys** `[]string`

MismatchLabelKeys is a set of pod label keys to select which pods will be taken into consideration. The keys are used to lookup values from the incoming pod labels, those key-value labels are merged with `LabelSelector` as `key notin (value)` to select the group of existing pods

which pods will be taken into consideration for the incoming pod's pod (anti) affinity. Keys that don't exist in the incoming pod labels will be ignored. The default value is empty. The same key is forbidden to exist in both MismatchLabelKeys and LabelSelector. Also, MismatchLabelKeys cannot be set when LabelSelector isn't set. This is an alpha field and requires enabling MatchLabelKeysInPodAffinity feature gate.

▼ **namespaceSelector** `object`

A label query over the set of namespaces that the term applies to. The term is applied to the union of the namespaces selected by this field and the ones listed in the namespaces field. null selector and null or empty namespaces list means "this pod's namespace". An empty selector ({}) matches all namespaces.

▼ **matchExpressions** `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string` required

key is the label key that the selector applies to.

▼ **operator** `string` required

operator represents a key's relationship to a set of values. Valid operators

are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic

merge patch.

▼ matchLabels

`object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ namespaces

`[]string`

namespaces specifies a static list of namespace names that the term applies to. The term is applied to the union of the namespaces listed in this field and the ones selected by namespaceSelector. null or empty namespaces

list and null namespaceSelector means "this pod's namespace".

▼ **topologyKey**

`string` required

This pod should be co-located (affinity) or not co-located (anti-affinity) with the pods matching the labelSelector in the specified namespaces, where co-located is defined as running on a node whose value of the label with key topologyKey matches that of any node on which any of the selected pods is running. Empty topologyKey is not allowed.

▼ **automountServiceAccountToken**

`boolean`

AutomountServiceAccountToken indicates whether a service account token should be automatically mounted.

▼ **containers** `[]object` required

A single application container that you want to run within a pod.

▼ args `[]string`

Arguments to the entrypoint. The container image's CMD is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: https://kubernetes.io/docs/tasks/inject-data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ command `[]string`

Entrypoint array. Not executed within a shell. The container image's ENTRYPOINT is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e.

"$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: https://kubernetes.io/docs/tasks/inject-data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ **env** `[]object`

EnvVar represents an environment variable present in a Container.

▼ **name** `string` required

Name of the environment variable. Must be a C_IDENTIFIER.

▼ **value** `string`

Variable references $(VAR_NAME) are expanded using the previously defined environment variables in the container and any service environment variables. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped

references will never be expanded, regardless of whether the variable exists or not. Defaults to "".

▼ **valueFrom** `object`

Source for the environment variable's value. Cannot be used if value is not empty.

▼ **configMapKeyRef** `object`

Selects a key of a ConfigMap.

▼ **key** `string` required

The key to select.

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the ConfigMap or its key must be defined

▼ **fieldRef** `object`

Selects a field of the pod: supports metadata.name, metadata.namespace, `metadata.labels['<KEY>']`, `metadata.annotations['<KEY>']`, spec.nodeName, spec.serviceAccountName, status.hostIP, status.podIP, status.podIPs.

▼ **apiVersion** `string`

Version of the schema the FieldPath is written in terms of, defaults to "v1".

▼ **fieldPath** `string`

required

Path of the field to select in the specified API version.

▼ resourceFieldRef

`object`

Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, limits.ephemeral-storage, requests.cpu, requests.memory and requests.ephemeral-storage) are currently supported.

▼ containerName

`string`

Container name: required for volumes, optional for env vars

▼ divisor

Specifies the output format of the exposed

resources, defaults to "1"

▼ **resource**
`string`
required

Required: resource to select

▼ **secretKeyRef**
`object`

Selects a key of a secret in the pod's namespace

▼ **key** `string`
required

The key of the secret to select from. Must be a valid secret key.

▼ **name**
`string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-

objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the Secret or its key must be defined

▼ **envFrom** `[]object`

EnvFromSource represents the source of a set of ConfigMaps

▼ **configMapRef** `object`

The ConfigMap to select from

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the ConfigMap must be defined

▼ **prefix** `string`

An optional identifier to prepend to each key in the ConfigMap. Must be a C_IDENTIFIER.

▼ **secretRef** `object`

The Secret to select from

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the Secret must be defined

▼ **image** `string`

Container image name. More info: https://kubernetes.io/docs/concepts/contai

ners/images↗ This field is optional to allow higher level config management to default or override container images in workload controllers like Deployments and StatefulSets.

▼ imagePullPolicy `string`

Image pull policy. One of Always, Never, IfNotPresent. Defaults to Always if :latest tag is specified, or IfNotPresent otherwise. Cannot be updated. More info: https://kubernetes.io/docs/concepts/containers/images#updating-images↗

▼ lifecycle `object`

Actions that the management system should take in response to container lifecycle events. Cannot be updated.

▼ postStart `object`

PostStart is called immediately after a container is created. If the handler fails, the container is terminated and restarted according to its restart policy. Other management of the container blocks until the hook completes. More info: https://kubernetes.io/docs/concepts/containers/container-lifecycle-hooks/#container-hooks↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host**

`string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders**

`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**

`string`

required

The header field name. This will be canonicalized upon output, so

case-variant names will be understood as the same header.

▼ **value**

`string`

required

The header field value

▼ **path**

`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme**
`string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **sleep** `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ **seconds**
`integer`
required

Seconds is the number of seconds to sleep.

▼ **tcpSocket** `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept for the backward compatibility. There are no validation of this field and lifecycle hooks will fail in runtime when tcp handler is specified.

▼ host

`string`

Optional: Host name to connect to, defaults to the pod IP.

▼ port required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ preStop `object`

PreStop is called immediately before a container is terminated due to an API request or management event such as liveness/startup probe failure, preemption, resource contention, etc. The handler is not called if the container crashes or exits. The Pod's termination grace period countdown begins before the PreStop hook is executed. Regardless of the outcome of the handler, the container will

eventually terminate within the Pod's termination grace period (unless delayed by finalizers). Other management of the container blocks until the hook completes or until the termination grace period is reached. More info: https://kubernetes.io/docs/concepts/containers/container-lifecycle-hooks/#container-hooks ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to

that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host**
`string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders**
`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path**
`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **sleep** `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ **seconds** `integer`

required

Seconds is the number of seconds to sleep.

▼ **tcpSocket** `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept for the backward compatibility. There are no validation of this field and lifecycle hooks will fail in runtime when tcp handler is specified.

▼ **host**
`string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAM E.

▼ **livenessProbe** `object`

Periodic probe of container liveness. Container will be restarted if the probe fails. Cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ **failureThreshold** `integer`

Minimum consecutive failures for the probe to be considered failed

after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ service `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md ↗).

If this is not specified, the default behavior is defined by gRPC.

▼ httpGet `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders** `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name** `string`

required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value** `string`

required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ successThreshold `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness and startup. Minimum value is 1.

▼ tcpSocket `object`

TCPSocket specifies an action involving a TCP port.

▼ host `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ port required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds**

`integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ **timeoutSeconds**

`integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More

info:
https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ name `string` required

Name of the container specified as a DNS_LABEL. Each container in a pod must have a unique name (DNS_LABEL). Cannot be updated.

▼ ports `[]object`

ContainerPort represents a network port in a single container.

▼ containerPort `integer` required

Number of port to expose on the pod's IP address. This must be a valid port number, 0 < x < 65536.

▼ hostIP `string`

What host IP to bind the external port to.

▼ hostPort `integer`

Number of port to expose on the host. If specified, this must be a valid port number, 0 < x < 65536. If

HostNetwork is specified, this must match ContainerPort. Most containers do not need this.

▼ **name** `string`

If specified, this must be an IANA_SVC_NAME and unique within the pod. Each named port in a pod must have a unique name. Name for the port that can be referred to by services.

▼ **protocol** `string`

Protocol for port. Must be UDP, TCP, or SCTP. Defaults to "TCP".

▼ **readinessProbe** `object`

Periodic probe of container service readiness. Container will be removed from service endpoints if the probe fails. Cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders** `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must

be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for

liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes

are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ **timeoutSeconds** `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **resizePolicy** `[]object`

ContainerResizePolicy represents resource resize policy for the container.

▼ **resourceName** `string`

required

Name of the resource to which this resource resize policy applies. Supported values: cpu, memory.

▼ **restartPolicy** `string`

required

Restart policy to apply when specified resource is resized. If not specified, it defaults to NotRequired.

▼ **resources** `object`

Compute Resources required by this container. Cannot be updated. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/↗

▼ **claims** `[]object`

ResourceClaim references one entry in PodSpec.ResourceClaims.

▼ **name** `string`

required

Name must match the name of one entry in pod.spec.resourceClaims of the Pod where this field

is used. It makes that resource available inside a container.

▼ limits `object`

Limits describes the maximum amount of compute resources allowed. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/ ↗

▼ requests `object`

Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. Requests cannot exceed Limits. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/ ↗

▼ restartPolicy `string`

RestartPolicy defines the restart behavior of individual containers in a pod. This field may only be set for init containers, and the only allowed value is "Always". For non-init containers or when this field is not

specified, the restart behavior is defined by the Pod's restart policy and the container type. Setting the RestartPolicy as "Always" for the init container will have the following effect: this init container will be continually restarted on exit until all regular containers have terminated. Once all regular containers have completed, all init containers with restartPolicy "Always" will be shut down. This lifecycle differs from normal init containers and is often referred to as a "sidecar" container. Although this init container still starts in the init container sequence, it does not wait for the container to complete before proceeding to the next init container. Instead, the next init container starts immediately after this init container is started, or after any startupProbe has successfully completed.

▼ **securityContext** `object`

SecurityContext defines the security options the container should be run with. If set, the fields of SecurityContext override the equivalent fields of PodSecurityContext. More info: https://kubernetes.io/docs/tasks/configure-pod-container/security-context/ ↗

▼ **allowPrivilegeEscalation** `boolean`

AllowPrivilegeEscalation controls whether a process can gain more privileges than its parent process. This bool directly controls if the

no_new_privs flag will be set on the container process. AllowPrivilegeEscalation is true always when the container is:

1. run as Privileged
2. has CAP_SYS_ADMIN Note that this field cannot be set when spec.os.name is windows.

▼ capabilities `object`

The capabilities to add/drop when running containers. Defaults to the default set of capabilities granted by the container runtime. Note that this field cannot be set when spec.os.name is windows.

▼ add `[]string`

Added capabilities

▼ drop `[]string`

Removed capabilities

▼ privileged `boolean`

Run container in privileged mode. Processes in privileged containers are essentially equivalent to root on the host. Defaults to false. Note

that this field cannot be set when spec.os.name is windows.

▼ procMount `string`

procMount denotes the type of proc mount to use for the containers. The default is DefaultProcMount which uses the container runtime defaults for readonly paths and masked paths. This requires the ProcMountType feature flag to be enabled. Note that this field cannot be set when spec.os.name is windows.

▼ readOnlyRootFilesystem `boolean`

Whether this container has a read-only root filesystem. Default is false. Note that this field cannot be set when spec.os.name is windows.

▼ runAsGroup `integer`

The GID to run the entrypoint of the container process. Uses runtime default if unset. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field

cannot be set when spec.os.name is windows.

▼ **runAsNonRoot** `boolean`

Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ **runAsUser** `integer`

The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ **seLinuxOptions** `object`

The SELinux context to be applied to the container. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ **level** `string`

Level is SELinux level label that applies to the container.

▼ **role** `string`

Role is a SELinux role label that applies to the container.

▼ **type** `string`

Type is a SELinux type label that applies to the container.

▼ **user** `string`

User is a SELinux user label that applies to the

container.

▼ seccompProfile `object`

The seccomp options to use by this container. If seccomp options are provided at both the pod & container level, the container options override the pod options. Note that this field cannot be set when spec.os.name is windows.

▼ localhostProfile `string`

localhostProfile indicates a profile defined in a file on the node should be used. The profile must be preconfigured on the node to work. Must be a descending path, relative to the kubelet's configured seccomp profile location. Must be set if type is "Localhost". Must NOT be set for any other type.

▼ type `string`

required

type indicates which kind of seccomp profile will be applied. Valid options are:

Localhost - a profile defined in a file on the node should be used. RuntimeDefault - the container runtime default profile should be used. Unconfined - no profile should be applied.

▼ **windowsOptions** `object`

The Windows specific settings applied to all containers. If unspecified, the options from the PodSecurityContext will be used. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is linux.

▼ **gmsaCredentialSpec** `string`

GMSACredentialSpec is where the GMSA admission webhook (https://github.com/kubernetes-sigs/windows-gmsa↗) inlines the contents of the GMSA credential spec named by the

GMSACredentialSpecNam
e field.

▼ **gmsaCredentialSpecName**
`string`

GMSACredentialSpecNam
e is the name of the
GMSA credential spec to
use.

▼ **hostProcess**
`boolean`

HostProcess determines if a container should be run as a 'Host Process' container. All of a Pod's containers must have the same effective HostProcess value (it is not allowed to have a mix of HostProcess containers and non-HostProcess containers). In addition, if HostProcess is true then HostNetwork must also be set to true.

▼ **runAsUserName**
`string`

The UserName in
Windows to run the

entrypoint of the container process. Defaults to the user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ startupProbe `object`

StartupProbe indicates that the Pod has successfully initialized. If specified, no other probes are executed until this completes successfully. If this probe fails, the Pod will be restarted, just as if the livenessProbe failed. This can be used to provide different probe parameters at the beginning of a Pod's lifecycle, when it might take a long time to load data or warm a cache, than during steady-state operation. This cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ exec `object`

Exec specifies the action to take.

▼ command `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders** `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must

be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for

liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes

are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ **timeoutSeconds** `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **stdin** `boolean`

Whether this container should allocate a buffer for stdin in the container runtime. If this is not set, reads from stdin in the

container will always result in EOF. Default is false.

▼ **stdinOnce** `boolean`

Whether the container runtime should close the stdin channel after it has been opened by a single attach. When stdin is true the stdin stream will remain open across multiple attach sessions. If stdinOnce is set to true, stdin is opened on container start, is empty until the first client attaches to stdin, and then remains open and accepts data until the client disconnects, at which time stdin is closed and remains closed until the container is restarted. If this flag is false, a container processes that reads from stdin will never receive an EOF. Default is false

▼ **terminationMessagePath** `string`

Optional: Path at which the file to which the container's termination message will be written is mounted into the container's filesystem. Message written is intended to be brief final status, such as an assertion failure message. Will be truncated by the node if greater than 4096 bytes. The total message length across all containers will be limited to 12kb. Defaults to /dev/termination-log. Cannot be updated.

▼ terminationMessagePolicy `string`

Indicate how the termination message should be populated. File will use the contents of terminationMessagePath to populate the container status message on both success and failure. FallbackToLogsOnError will use the last chunk of container log output if the termination message file is empty and the container exited with an error. The log output is limited to 2048 bytes or 80 lines, whichever is smaller. Defaults to File. Cannot be updated.

▼ tty `boolean`

Whether this container should allocate a TTY for itself, also requires 'stdin' to be true. Default is false.

▼ volumeDevices `[]object`

volumeDevice describes a mapping of a raw block device within a container.

▼ devicePath `string`

required

devicePath is the path inside of the container that the device will be mapped to.

▼ **name** `string` required

name must match the name of a persistentVolumeClaim in the pod

▼ **volumeMounts** `[]object`

VolumeMount describes a mounting of a Volume within a container.

▼ **mountPath** `string`

required

Path within the container at which the volume should be mounted. Must not contain ':'.

▼ **mountPropagation** `string`

mountPropagation determines how mounts are propagated from the host to container and the other way around. When not set, MountPropagationNone is used. This field is beta in 1.10.

▼ **name** `string` required

This must match the Name of a Volume.

▼ **readOnly** `boolean`

Mounted read-only if true, read-write otherwise (false or unspecified). Defaults to false.

▼ **subPath** `string`

Path within the volume from which the container's volume should be mounted. Defaults to "" (volume's root).

▼ **subPathExpr** `string`

Expanded path within the volume from which the container's volume should be mounted. Behaves similarly to SubPath but environment variable references $(VAR_NAME) are expanded using the container's environment. Defaults to "" (volume's root). SubPathExpr and SubPath are mutually exclusive.

▼ **workingDir** `string`

Container's working directory. If not specified, the container runtime's default will be used, which might be configured in the container image. Cannot be updated.

▼ **dnsConfig** `object`

Specifies the DNS parameters of a pod. Parameters specified here will be merged to the generated DNS configuration based on DNSPolicy.

▼ **nameservers** `[]string`

A list of DNS name server IP addresses. This will be appended to the base nameservers generated from DNSPolicy. Duplicated nameservers will be removed.

▼ **options** `[]object`

PodDNSConfigOption defines DNS resolver options of a pod.

▼ **name** `string`

Required.

▼ **value** `string`

▼ **searches** `[]string`

A list of DNS search domains for host-name lookup. This will be appended to the base search paths generated from DNSPolicy. Duplicated search paths will be removed.

▼ dnsPolicy `string`

Set DNS policy for the pod. Defaults to "ClusterFirst". Valid values are 'ClusterFirstWithHostNet', 'ClusterFirst', 'Default' or 'None'. DNS parameters given in DNSConfig will be merged with the policy selected with DNSPolicy. To have DNS options set along with hostNetwork, you have to specify DNS policy explicitly to 'ClusterFirstWithHostNet'.

▼ enableServiceLinks `boolean`

EnableServiceLinks indicates whether information about services should be injected into pod's environment variables, matching the syntax of Docker links. Optional: Defaults to true.

▼ ephemeralContainers `[]object`

An EphemeralContainer is a temporary container that you may add to an existing Pod for user-initiated activities such as debugging. Ephemeral containers have no resource or scheduling guarantees, and they will not be restarted when they exit or when a Pod is removed or restarted. The kubelet may evict a Pod if an ephemeral container causes the Pod to exceed its resource allocation.

To add an ephemeral container, use the ephemeralcontainers subresource of an existing Pod. Ephemeral containers may not be removed or restarted.

▼ args `[]string`

Arguments to the entrypoint. The image's CMD is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: https://kubernetes.io/docs/tasks/inject-data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ command `[]string`

Entrypoint array. Not executed within a shell. The image's ENTRYPOINT is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: https://kubernetes.io/docs/tasks/inject-

data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ **env** `[]object`

EnvVar represents an environment variable present in a Container.

▼ **name** `string` required

Name of the environment variable. Must be a C_IDENTIFIER.

▼ **value** `string`

Variable references $(VAR_NAME) are expanded using the previously defined environment variables in the container and any service environment variables. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Defaults to "".

▼ **valueFrom** `object`

Source for the environment variable's value. Cannot be used if value is not empty.

▼ **configMapKeyRef** `object`

Selects a key of a ConfigMap.

▼ **key** `string`

required

The key to select.

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the ConfigMap or

its key must be defined

▼ **fieldRef** `object`

Selects a field of the pod: supports metadata.name, metadata.namespace, `metadata.labels['<KEY>']`, `metadata.annotations['<KEY>']`, spec.nodeName, spec.serviceAccountName, status.hostIP, status.podIP, status.podIPs.

▼ **apiVersion** `string`

Version of the schema the FieldPath is written in terms of, defaults to "v1".

▼ **fieldPath** `string`

required

Path of the field to select in the

specified API version.

▼ **resourceFieldRef** `object`

Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, limits.ephemeral-storage, requests.cpu, requests.memory and requests.ephemeral-storage) are currently supported.

▼ **containerName** `string`

Container name: required for volumes, optional for env vars

▼ **divisor**

Specifies the output format of the exposed resources, defaults to "1"

▼ **resource**

`string`

required

Required:

resource to select

▼ **secretKeyRef**

`object`

Selects a key of a secret in the pod's namespace

▼ **key** `string`

required

The key of the secret to select from. Must be a valid secret key.

▼ **name**

`string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the Secret or its key must be defined

▼ **envFrom** `[]object`

EnvFromSource represents the source of a set of ConfigMaps

▼ **configMapRef** `object`

The ConfigMap to select from

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the ConfigMap must be defined

▼ **prefix** `string`

An optional identifier to prepend to each key in the ConfigMap. Must be a C_IDENTIFIER.

▼ **secretRef** `object`

The Secret to select from

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the Secret must be defined

▼ **image** `string`

Container image name. More info: https://kubernetes.io/docs/concepts/containers/images ↗

▼ **imagePullPolicy** `string`

Image pull policy. One of Always, Never, IfNotPresent. Defaults to Always if :latest tag is specified, or IfNotPresent otherwise. Cannot be updated. More info: https://kubernetes.io/docs/concepts/containers/images#updating-images ↗

▼ **lifecycle** `object`

Lifecycle is not allowed for ephemeral containers.

▼ **postStart** `object`

PostStart is called immediately after a container is created. If the handler fails, the container is terminated and restarted according to its restart policy. Other management of the container blocks until the hook completes. More info: https://kubernetes.io/docs/concepts/containers/container-lifecycle-hooks/#container-hooks ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to

execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ httpGet `object`

HTTPGet specifies the http request to perform.

▼ host `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host"

in httpHeaders instead.

▼ **httpHeaders**

`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**

`string`

required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**

`string`

required

The header field value

▼ **path**

`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme**

`string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ sleep `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ seconds

`integer`

required

Seconds is the number of seconds to sleep.

▼ tcpSocket `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept for the backward compatibility. There are no validation of this field and lifecycle hooks will fail in runtime when tcp handler is specified.

▼ host

`string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **preStop** `object`

PreStop is called immediately before a container is terminated due to an API request or management event such as liveness/startup probe failure, preemption, resource contention, etc. The handler is not called if the container crashes or exits. The Pod's termination grace period countdown begins before the PreStop hook is executed. Regardless of the outcome of the handler, the container will eventually terminate within the Pod's termination grace period (unless delayed by finalizers). Other management of the container blocks until the hook completes or until the termination grace period is reached. More info: https://kubernetes.io/docs/concept

s/containers/container-lifecycle-hooks/#container-hooks ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host**
`string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders**
`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicali

zed upon output, so case-variant names will be understood as the same header.

▼ **value**

`string`

required

The header field value

▼ **path**

`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an

IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **sleep** `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ **seconds** `integer`

required

Seconds is the number of seconds to sleep.

▼ **tcpSocket** `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept for the backward compatibility. There are no validation of this field and

lifecycle hooks will fail in runtime when tcp handler is specified.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **livenessProbe** `object`

Probes are not allowed for ephemeral containers.

▼ **exec** `object`

Exec specifies the action to take.

▼ command

`[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold

`integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders** `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must

be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for

liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes

are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ timeoutSeconds `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ name `string` required

Name of the ephemeral container specified as a DNS_LABEL. This name must be

unique among all containers, init containers and ephemeral containers.

▼ ports `[]object`

ContainerPort represents a network port in a single container.

▼ containerPort `integer`

required

Number of port to expose on the pod's IP address. This must be a valid port number, 0 < x < 65536.

▼ hostIP `string`

What host IP to bind the external port to.

▼ hostPort `integer`

Number of port to expose on the host. If specified, this must be a valid port number, 0 < x < 65536. If HostNetwork is specified, this must match ContainerPort. Most containers do not need this.

▼ name `string`

If specified, this must be an IANA_SVC_NAME and unique within the pod. Each named port in a pod must have a unique name.

Name for the port that can be referred to by services.

▼ **protocol** `string`

Protocol for port. Must be UDP, TCP, or SCTP. Defaults to "TCP".

▼ **readinessProbe** `object`

Probes are not allowed for ephemeral containers.

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of

0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ service `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ httpGet `object`

HTTPGet specifies the http request to perform.

▼ host `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ httpHeaders `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ name `string`

required

The header field name. This will be canonicalized upon output, so case-variant names will be

understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds**
`integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1.

spec.terminationGracePeriodSeconds is used if unset.

▼ timeoutSeconds `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ resizePolicy `[]object`

ContainerResizePolicy represents resource resize policy for the container.

▼ resourceName `string`

required

Name of the resource to which this resource resize policy applies. Supported values: cpu, memory.

▼ restartPolicy `string`

required

Restart policy to apply when specified resource is resized. If not specified, it defaults to NotRequired.

▼ resources `object`

Resources are not allowed for ephemeral containers. Ephemeral containers use spare resources already allocated to the pod.

▼ claims `[]object`

ResourceClaim references one entry in PodSpec.ResourceClaims.

▼ name `string`

required

Name must match the name of one entry in pod.spec.resourceClaims of the Pod where this field is used. It makes that resource available inside a container.

▼ limits `object`

Limits describes the maximum amount of compute resources allowed. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/↗

▼ requests `object`

Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. Requests cannot exceed Limits. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/↗

▼ restartPolicy `string`

Restart policy for the container to manage the restart behavior of each container within a pod. This may only be set for init containers. You cannot set this field on ephemeral containers.

▼ securityContext `object`

Optional: SecurityContext defines the security options the ephemeral container should be run with. If set, the fields of SecurityContext override the equivalent fields of PodSecurityContext.

▼ allowPrivilegeEscalation `boolean`

AllowPrivilegeEscalation controls whether a process can gain more privileges than its parent process. This bool directly controls if the

no_new_privs flag will be set on the container process. AllowPrivilegeEscalation is true always when the container is:

1. run as Privileged
2. has CAP_SYS_ADMIN Note that this field cannot be set when spec.os.name is windows.

▼ capabilities `object`

The capabilities to add/drop when running containers. Defaults to the default set of capabilities granted by the container runtime. Note that this field cannot be set when spec.os.name is windows.

▼ add `[]string`

Added capabilities

▼ drop `[]string`

Removed capabilities

▼ privileged `boolean`

Run container in privileged mode. Processes in privileged containers are essentially equivalent to root on the host. Defaults to false. Note

that this field cannot be set when spec.os.name is windows.

▼ procMount `string`

procMount denotes the type of proc mount to use for the containers. The default is DefaultProcMount which uses the container runtime defaults for readonly paths and masked paths. This requires the ProcMountType feature flag to be enabled. Note that this field cannot be set when spec.os.name is windows.

▼ readOnlyRootFilesystem `boolean`

Whether this container has a read-only root filesystem. Default is false. Note that this field cannot be set when spec.os.name is windows.

▼ runAsGroup `integer`

The GID to run the entrypoint of the container process. Uses runtime default if unset. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field

cannot be set when spec.os.name is windows.

▼ runAsNonRoot `boolean`

Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ runAsUser `integer`

The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ seLinuxOptions `object`

The SELinux context to be applied to the container. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ **level** `string`

Level is SELinux level label that applies to the container.

▼ **role** `string`

Role is a SELinux role label that applies to the container.

▼ **type** `string`

Type is a SELinux type label that applies to the container.

▼ **user** `string`

User is a SELinux user label that applies to the

container.

▼ seccompProfile `object`

The seccomp options to use by this container. If seccomp options are provided at both the pod & container level, the container options override the pod options. Note that this field cannot be set when spec.os.name is windows.

▼ localhostProfile `string`

localhostProfile indicates a profile defined in a file on the node should be used. The profile must be preconfigured on the node to work. Must be a descending path, relative to the kubelet's configured seccomp profile location. Must be set if type is "Localhost". Must NOT be set for any other type.

▼ type `string`

required

type indicates which kind of seccomp profile will be applied. Valid options are:

Localhost - a profile defined in a file on the node should be used. RuntimeDefault - the container runtime default profile should be used. Unconfined - no profile should be applied.

▼ **windowsOptions** `object`

The Windows specific settings applied to all containers. If unspecified, the options from the PodSecurityContext will be used. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is linux.

▼ **gmsaCredentialSpec** `string`

GMSACredentialSpec is where the GMSA admission webhook (https://github.com/kubernetes-sigs/windows-gmsa↗) inlines the contents of the GMSA credential spec named by the

GMSACredentialSpecNam
e field.

▼ **gmsaCredentialSpecName**
`string`

GMSACredentialSpecNam
e is the name of the
GMSA credential spec to
use.

▼ **hostProcess**
`boolean`

HostProcess determines if a container should be run as a 'Host Process' container. All of a Pod's containers must have the same effective HostProcess value (it is not allowed to have a mix of HostProcess containers and non-HostProcess containers). In addition, if HostProcess is true then HostNetwork must also be set to true.

▼ **runAsUserName**
`string`

The UserName in
Windows to run the

entrypoint of the container process. Defaults to the user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ **startupProbe** `object`

Probes are not allowed for ephemeral containers.

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out

to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ service `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined

by gRPC.

▼ httpGet `object`

HTTPGet specifies the http request to perform.

▼ host `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ httpHeaders `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ name `string`

required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds**
`integer`

Number of seconds after the container has started before liveness probes are initiated. More

info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ periodSeconds `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ successThreshold `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness and startup. Minimum value is 1.

▼ tcpSocket `object`

TCPSocket specifies an action involving a TCP port.

▼ host `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ port required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1.

spec.terminationGracePeriodSeconds is used if unset.

▼ timeoutSeconds `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ stdin `boolean`

Whether this container should allocate a buffer for stdin in the container runtime. If this is not set, reads from stdin in the container will always result in EOF. Default is false.

▼ stdinOnce `boolean`

Whether the container runtime should close the stdin channel after it has been opened by a single attach. When stdin is true the stdin stream will remain open across multiple attach sessions. If stdinOnce is set to true, stdin is opened on container start, is empty until the first client attaches to stdin, and then remains open and accepts data until the client disconnects, at which time stdin is closed and remains closed until the container is

restarted. If this flag is false, a container processes that reads from stdin will never receive an EOF. Default is false

▼ **targetContainerName** `string`

If set, the name of the container from PodSpec that this ephemeral container targets. The ephemeral container will be run in the namespaces (IPC, PID, etc) of this container. If not set then the ephemeral container uses the namespaces configured in the Pod spec.

The container runtime must implement support for this feature. If the runtime does not support namespace targeting then the result of setting this field is undefined.

▼ **terminationMessagePath** `string`

Optional: Path at which the file to which the container's termination message will be written is mounted into the container's filesystem. Message written is intended to be brief final status, such as an assertion failure message. Will be truncated by the node if greater than 4096 bytes. The total message length across all containers will be limited to 12kb. Defaults to /dev/termination-log. Cannot be updated.

▼ **terminationMessagePolicy** `string`

Indicate how the termination message should be populated. File will use the contents of terminationMessagePath to populate the container status message on both success and failure. FallbackToLogsOnError will use the last chunk of container log output if the termination message file is empty and the container exited with an error. The log output is limited to 2048 bytes or 80 lines, whichever is smaller. Defaults to File. Cannot be updated.

▼ tty `boolean`

Whether this container should allocate a TTY for itself, also requires 'stdin' to be true. Default is false.

▼ volumeDevices `[]object`

volumeDevice describes a mapping of a raw block device within a container.

▼ devicePath `string`

required

devicePath is the path inside of the container that the device will be mapped to.

▼ name `string` required

name must match the name of a persistentVolumeClaim in the pod

▼ volumeMounts `[]object`

VolumeMount describes a mounting of a Volume within a container.

▼ mountPath `string`

required

Path within the container at which the volume should be mounted. Must not contain ':'.

▼ mountPropagation `string`

mountPropagation determines how mounts are propagated from the host to container and the other way around. When not set, MountPropagationNone is used. This field is beta in 1.10.

▼ name `string` required

This must match the Name of a Volume.

▼ readOnly `boolean`

Mounted read-only if true, read-write otherwise (false or

unspecified). Defaults to false.

▼ subPath `string`

Path within the volume from which the container's volume should be mounted. Defaults to "" (volume's root).

▼ subPathExpr `string`

Expanded path within the volume from which the container's volume should be mounted. Behaves similarly to SubPath but environment variable references $(VAR_NAME) are expanded using the container's environment. Defaults to "" (volume's root). SubPathExpr and SubPath are mutually exclusive.

▼ workingDir `string`

Container's working directory. If not specified, the container runtime's default will be used, which might be configured in the container image. Cannot be updated.

▼ hostAliases `[]object`

HostAlias holds the mapping between IP and hostnames that will be injected as an entry in the pod's hosts file.

▼ **hostnames** `[]string`

Hostnames for the above IP address.

▼ **ip** `string`

IP address of the host file entry.

▼ **hostIPC** `boolean`

Use the host's ipc namespace. Optional: Default to false.

▼ **hostNetwork** `boolean`

Host networking requested for this pod. Use the host's network namespace. If this option is set, the ports that will be used must be specified. Default to false.

▼ **hostPID** `boolean`

Use the host's pid namespace. Optional: Default to false.

▼ **hostUsers** `boolean`

Use the host's user namespace. Optional: Default to true. If set to true or not present, the pod will be run in the host user namespace, useful for when the pod needs a feature only available to the host user namespace, such as loading a kernel module with CAP_SYS_MODULE. When set to false, a

new userns is created for the pod. Setting false is useful for mitigating container breakout vulnerabilities even allowing users to run their containers as root without actually having root privileges on the host. This field is alpha-level and is only honored by servers that enable the UserNamespacesSupport feature.

▼ **hostname** `string`

Specifies the hostname of the Pod If not specified, the pod's hostname will be set to a system-defined value.

▼ **imagePullSecrets** `[]object`

LocalObjectReference contains enough information to let you locate the referenced object inside the same namespace.

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **initContainers** `[]object`

A single application container that you want to run within a pod.

▼ **args** `[]string`

Arguments to the entrypoint. The container image's CMD is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info: https://kubernetes.io/docs/tasks/inject-data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ command `[]string`

Entrypoint array. Not executed within a shell. The container image's ENTRYPOINT is used if this is not provided. Variable references $(VAR_NAME) are expanded using the container's environment. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Cannot be updated. More info:

https://kubernetes.io/docs/tasks/inject-data-application/define-command-argument-container/#running-a-command-in-a-shell↗

▼ **env** `[]object`

EnvVar represents an environment variable present in a Container.

▼ **name** `string` required

Name of the environment variable. Must be a C_IDENTIFIER.

▼ **value** `string`

Variable references $(VAR_NAME) are expanded using the previously defined environment variables in the container and any service environment variables. If a variable cannot be resolved, the reference in the input string will be unchanged. Double $$ are reduced to a single $, which allows for escaping the $(VAR_NAME) syntax: i.e. "$$(VAR_NAME)" will produce the string literal "$(VAR_NAME)". Escaped references will never be expanded, regardless of whether the variable exists or not. Defaults to "".

▼ valueFrom `object`

Source for the environment variable's value. Cannot be used if value is not empty.

▼ configMapKeyRef `object`

Selects a key of a ConfigMap.

▼ key `string`

required

The key to select.

▼ name `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ optional `boolean`

Specify whether the ConfigMap or

its key must be defined

▼ **fieldRef** `object`

Selects a field of the pod: supports metadata.name, metadata.namespace, `metadata.labels['<KEY>']`, `metadata.annotations['<KEY>']`, spec.nodeName, spec.serviceAccountName, status.hostIP, status.podIP, status.podIPs.

▼ **apiVersion** `string`

Version of the schema the FieldPath is written in terms of, defaults to "v1".

▼ **fieldPath** `string`

required

Path of the field to select in the

specified API version.

▼ **resourceFieldRef** `object`

Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, limits.ephemeral-storage, requests.cpu, requests.memory and requests.ephemeral-storage) are currently supported.

▼ **containerName** `string`

Container name: required for volumes, optional for env vars

▼ **divisor**

Specifies the output format of the exposed resources, defaults to "1"

▼ **resource**

`string`

required

Required:

resource to select

▼ **secretKeyRef**

`object`

Selects a key of a secret in the pod's namespace

▼ **key** `string`

required

The key of the secret to select from. Must be a valid secret key.

▼ **name**

`string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional**
`boolean`

Specify whether the Secret or its key must be defined

▼ **envFrom** `[]object`

EnvFromSource represents the source of a set of ConfigMaps

▼ **configMapRef** `object`

The ConfigMap to select from

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the ConfigMap must be defined

▼ **prefix** `string`

An optional identifier to prepend to each key in the ConfigMap. Must be a C_IDENTIFIER.

▼ **secretRef** `object`

The Secret to select from

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

Specify whether the Secret must be defined

▼ **image** `string`

Container image name. More info: https://kubernetes.io/docs/concepts/containers/images ↗ This field is optional to allow higher level config management to default or override container images in

workload controllers like Deployments and StatefulSets.

▼ **imagePullPolicy** `string`

Image pull policy. One of Always, Never, IfNotPresent. Defaults to Always if :latest tag is specified, or IfNotPresent otherwise. Cannot be updated. More info: https://kubernetes.io/docs/concepts/containers/images#updating-images ↗

▼ **lifecycle** `object`

Actions that the management system should take in response to container lifecycle events. Cannot be updated.

▼ **postStart** `object`

PostStart is called immediately after a container is created. If the handler fails, the container is terminated and restarted according to its restart policy. Other management of the container blocks until the hook completes. More info: https://kubernetes.io/docs/concepts/containers/container-lifecycle-hooks/#container-hooks ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders**
`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the

same header.

▼ **value**

`string`

required

The header field value

▼ **path**

`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme**

`string`

Scheme to use for connecting to the

host. Defaults to HTTP.

▼ **sleep** `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ **seconds**
`integer`
required

Seconds is the number of seconds to sleep.

▼ **tcpSocket** `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept for the backward compatibility. There are no validation of this field and lifecycle hooks will fail in runtime when tcp handler is specified.

▼ **host**
`string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **preStop** `object`

PreStop is called immediately before a container is terminated due to an API request or management event such as liveness/startup probe failure, preemption, resource contention, etc. The handler is not called if the container crashes or exits. The Pod's termination grace period countdown begins before the PreStop hook is executed. Regardless of the outcome of the handler, the container will eventually terminate within the Pod's termination grace period (unless delayed by finalizers).

Other management of the container blocks until the hook completes or until the termination grace period is reached. More info: https://kubernetes.io/docs/concepts/containers/container-lifecycle-hooks/#container-hooks ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as

live/healthy and non-zero is unhealthy.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host**
`string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders**
`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field

name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**

`string`

required

The header field value

▼ **path**

`string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number

must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **sleep** `object`

Sleep represents the duration that the container should sleep before being terminated.

▼ **seconds** `integer`

required

Seconds is the number of seconds to sleep.

▼ **tcpSocket** `object`

Deprecated. TCPSocket is NOT supported as a LifecycleHandler and kept

for the backward compatibility. There are no validation of this field and lifecycle hooks will fail in runtime when tcp handler is specified.

▼ **host**
`string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAM E.

▼ **livenessProbe** `object`

Periodic probe of container liveness. Container will be restarted if the probe fails. Cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command**
`[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ **failureThreshold**
`integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ **grpc** `object`

GRPC specifies an action involving a GRPC port.

▼ **port** `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set

"Host" in httpHeaders instead.

▼ httpHeaders

`[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ name

`string`

required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ value

`string`

required

The header field value

▼ path `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ successThreshold `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for liveness and startup. Minimum value is 1.

▼ tcpSocket `object`

TCPSocket specifies an action involving a TCP port.

▼ host `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ port required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds**

`integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ **timeoutSeconds**

`integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More

info:
https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ name `string` required

Name of the container specified as a DNS_LABEL. Each container in a pod must have a unique name (DNS_LABEL). Cannot be updated.

▼ ports `[]object`

ContainerPort represents a network port in a single container.

▼ containerPort `integer` required

Number of port to expose on the pod's IP address. This must be a valid port number, 0 < x < 65536.

▼ hostIP `string`

What host IP to bind the external port to.

▼ hostPort `integer`

Number of port to expose on the host. If specified, this must be a valid port number, 0 < x < 65536. If

HostNetwork is specified, this must match ContainerPort. Most containers do not need this.

▼ **name** `string`

If specified, this must be an IANA_SVC_NAME and unique within the pod. Each named port in a pod must have a unique name. Name for the port that can be referred to by services.

▼ **protocol** `string`

Protocol for port. Must be UDP, TCP, or SCTP. Defaults to "TCP".

▼ **readinessProbe** `object`

Periodic probe of container service readiness. Container will be removed from service endpoints if the probe fails. Cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **exec** `object`

Exec specifies the action to take.

▼ **command** `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders** `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must

be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for

liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes

are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ timeoutSeconds `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ resizePolicy `[]object`

ContainerResizePolicy represents resource resize policy for the container.

▼ **resourceName** `string`

required

Name of the resource to which this resource resize policy applies. Supported values: cpu, memory.

▼ **restartPolicy** `string`

required

Restart policy to apply when specified resource is resized. If not specified, it defaults to NotRequired.

▼ **resources** `object`

Compute Resources required by this container. Cannot be updated. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/↗

▼ **claims** `[]object`

ResourceClaim references one entry in PodSpec.ResourceClaims.

▼ **name** `string`

required

Name must match the name of one entry in pod.spec.resourceClaims of the Pod where this field

is used. It makes that resource available inside a container.

▼ limits `object`

Limits describes the maximum amount of compute resources allowed. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/ ↗

▼ requests `object`

Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. Requests cannot exceed Limits. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/ ↗

▼ restartPolicy `string`

RestartPolicy defines the restart behavior of individual containers in a pod. This field may only be set for init containers, and the only allowed value is "Always". For non-init containers or when this field is not

specified, the restart behavior is defined by the Pod's restart policy and the container type. Setting the RestartPolicy as "Always" for the init container will have the following effect: this init container will be continually restarted on exit until all regular containers have terminated. Once all regular containers have completed, all init containers with restartPolicy "Always" will be shut down. This lifecycle differs from normal init containers and is often referred to as a "sidecar" container. Although this init container still starts in the init container sequence, it does not wait for the container to complete before proceeding to the next init container. Instead, the next init container starts immediately after this init container is started, or after any startupProbe has successfully completed.

▼ **securityContext** `object`

SecurityContext defines the security options the container should be run with. If set, the fields of SecurityContext override the equivalent fields of PodSecurityContext. More info: https://kubernetes.io/docs/tasks/configure-pod-container/security-context/ ↗

▼ **allowPrivilegeEscalation** `boolean`

AllowPrivilegeEscalation controls whether a process can gain more privileges than its parent process. This bool directly controls if the

no_new_privs flag will be set on the container process. AllowPrivilegeEscalation is true always when the container is:

1. run as Privileged
2. has CAP_SYS_ADMIN Note that this field cannot be set when spec.os.name is windows.

▼ capabilities `object`

The capabilities to add/drop when running containers. Defaults to the default set of capabilities granted by the container runtime. Note that this field cannot be set when spec.os.name is windows.

▼ add `[]string`

Added capabilities

▼ drop `[]string`

Removed capabilities

▼ privileged `boolean`

Run container in privileged mode. Processes in privileged containers are essentially equivalent to root on the host. Defaults to false. Note

that this field cannot be set when spec.os.name is windows.

▼ procMount `string`

procMount denotes the type of proc mount to use for the containers. The default is DefaultProcMount which uses the container runtime defaults for readonly paths and masked paths. This requires the ProcMountType feature flag to be enabled. Note that this field cannot be set when spec.os.name is windows.

▼ readOnlyRootFilesystem `boolean`

Whether this container has a read-only root filesystem. Default is false. Note that this field cannot be set when spec.os.name is windows.

▼ runAsGroup `integer`

The GID to run the entrypoint of the container process. Uses runtime default if unset. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field

cannot be set when spec.os.name is windows.

▼ runAsNonRoot `boolean`

Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ runAsUser `integer`

The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ seLinuxOptions `object`

The SELinux context to be applied to the container. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is windows.

▼ **level** `string`

Level is SELinux level label that applies to the container.

▼ **role** `string`

Role is a SELinux role label that applies to the container.

▼ **type** `string`

Type is a SELinux type label that applies to the container.

▼ **user** `string`

User is a SELinux user label that applies to the

container.

▼ seccompProfile `object`

The seccomp options to use by this container. If seccomp options are provided at both the pod & container level, the container options override the pod options. Note that this field cannot be set when spec.os.name is windows.

▼ localhostProfile `string`

localhostProfile indicates a profile defined in a file on the node should be used. The profile must be preconfigured on the node to work. Must be a descending path, relative to the kubelet's configured seccomp profile location. Must be set if type is "Localhost". Must NOT be set for any other type.

▼ type `string`

required

type indicates which kind of seccomp profile will be applied. Valid options are:

Localhost - a profile defined in a file on the node should be used. RuntimeDefault - the container runtime default profile should be used. Unconfined - no profile should be applied.

▼ **windowsOptions** `object`

The Windows specific settings applied to all containers. If unspecified, the options from the PodSecurityContext will be used. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is linux.

▼ **gmsaCredentialSpec** `string`

GMSACredentialSpec is where the GMSA admission webhook (https://github.com/kubernetes-sigs/windows-gmsa↗) inlines the contents of the GMSA credential spec named by the

GMSACredentialSpecNam
e field.

▼ **gmsaCredentialSpecName**
`string`

GMSACredentialSpecNam
e is the name of the
GMSA credential spec to
use.

▼ **hostProcess**
`boolean`

HostProcess determines if a container should be run as a 'Host Process' container. All of a Pod's containers must have the same effective HostProcess value (it is not allowed to have a mix of HostProcess containers and non-HostProcess containers). In addition, if HostProcess is true then HostNetwork must also be set to true.

▼ **runAsUserName**
`string`

The UserName in
Windows to run the

entrypoint of the container process. Defaults to the user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ startupProbe `object`

StartupProbe indicates that the Pod has successfully initialized. If specified, no other probes are executed until this completes successfully. If this probe fails, the Pod will be restarted, just as if the livenessProbe failed. This can be used to provide different probe parameters at the beginning of a Pod's lifecycle, when it might take a long time to load data or warm a cache, than during steady-state operation. This cannot be updated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ exec `object`

Exec specifies the action to take.

▼ command `[]string`

Command is the command line to execute inside the container, the working directory for the command is root ('/') in the container's filesystem. The command is simply exec'd, it is not run inside a shell, so traditional shell instructions ('|', etc) won't work. To use a shell, you need to explicitly call out to that shell. Exit status of 0 is treated as live/healthy and non-zero is unhealthy.

▼ failureThreshold `integer`

Minimum consecutive failures for the probe to be considered failed after having succeeded. Defaults to 3. Minimum value is 1.

▼ grpc `object`

GRPC specifies an action involving a GRPC port.

▼ port `integer`

required

Port number of the gRPC service. Number must be in the range 1 to 65535.

▼ **service** `string`

Service is the name of the service to place in the gRPC HealthCheckRequest (see https://github.com/grpc/grpc/blob/master/doc/health-checking.md↗).

If this is not specified, the default behavior is defined by gRPC.

▼ **httpGet** `object`

HTTPGet specifies the http request to perform.

▼ **host** `string`

Host name to connect to, defaults to the pod IP. You probably want to set "Host" in httpHeaders instead.

▼ **httpHeaders** `[]object`

HTTPHeader describes a custom header to be used in HTTP probes

▼ **name**
`string`
required

The header field name. This will be canonicalized upon output, so case-variant names will be understood as the same header.

▼ **value**
`string`
required

The header field value

▼ **path** `string`

Path to access on the HTTP server.

▼ **port** required

Name or number of the port to access on the container. Number must

be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **scheme** `string`

Scheme to use for connecting to the host. Defaults to HTTP.

▼ **initialDelaySeconds** `integer`

Number of seconds after the container has started before liveness probes are initiated. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **periodSeconds** `integer`

How often (in seconds) to perform the probe. Default to 10 seconds. Minimum value is 1.

▼ **successThreshold** `integer`

Minimum consecutive successes for the probe to be considered successful after having failed. Defaults to 1. Must be 1 for

liveness and startup. Minimum value is 1.

▼ **tcpSocket** `object`

TCPSocket specifies an action involving a TCP port.

▼ **host** `string`

Optional: Host name to connect to, defaults to the pod IP.

▼ **port** required

Number or name of the port to access on the container. Number must be in the range 1 to 65535. Name must be an IANA_SVC_NAME.

▼ **terminationGracePeriodSeconds** `integer`

Optional duration in seconds the pod needs to terminate gracefully upon probe failure. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes

are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. If this value is nil, the pod's terminationGracePeriodSeconds will be used. Otherwise, this value overrides the value provided by the pod spec. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). This is a beta field and requires enabling ProbeTerminationGracePeriod feature gate. Minimum value is 1. spec.terminationGracePeriodSeconds is used if unset.

▼ **timeoutSeconds** `integer`

Number of seconds after which the probe times out. Defaults to 1 second. Minimum value is 1. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle#container-probes ↗

▼ **stdin** `boolean`

Whether this container should allocate a buffer for stdin in the container runtime. If this is not set, reads from stdin in the

container will always result in EOF. Default is false.

▼ **stdinOnce** `boolean`

Whether the container runtime should close the stdin channel after it has been opened by a single attach. When stdin is true the stdin stream will remain open across multiple attach sessions. If stdinOnce is set to true, stdin is opened on container start, is empty until the first client attaches to stdin, and then remains open and accepts data until the client disconnects, at which time stdin is closed and remains closed until the container is restarted. If this flag is false, a container processes that reads from stdin will never receive an EOF. Default is false

▼ **terminationMessagePath** `string`

Optional: Path at which the file to which the container's termination message will be written is mounted into the container's filesystem. Message written is intended to be brief final status, such as an assertion failure message. Will be truncated by the node if greater than 4096 bytes. The total message length across all containers will be limited to 12kb. Defaults to /dev/termination-log. Cannot be updated.

▼ terminationMessagePolicy `string`

Indicate how the termination message should be populated. File will use the contents of terminationMessagePath to populate the container status message on both success and failure. FallbackToLogsOnError will use the last chunk of container log output if the termination message file is empty and the container exited with an error. The log output is limited to 2048 bytes or 80 lines, whichever is smaller. Defaults to File. Cannot be updated.

▼ tty `boolean`

Whether this container should allocate a TTY for itself, also requires 'stdin' to be true. Default is false.

▼ volumeDevices `[]object`

volumeDevice describes a mapping of a raw block device within a container.

▼ devicePath `string`

required

devicePath is the path inside of the container that the device will be mapped to.

▼ **name** `string` required

name must match the name of a persistentVolumeClaim in the pod

▼ **volumeMounts** `[]object`

VolumeMount describes a mounting of a Volume within a container.

▼ **mountPath** `string`

required

Path within the container at which the volume should be mounted. Must not contain ':'.

▼ **mountPropagation** `string`

mountPropagation determines how mounts are propagated from the host to container and the other way around. When not set, MountPropagationNone is used. This field is beta in 1.10.

▼ **name** `string` required

This must match the Name of a Volume.

▼ **readOnly** `boolean`

Mounted read-only if true, read-write otherwise (false or unspecified). Defaults to false.

▼ **subPath** `string`

Path within the volume from which the container's volume should be mounted. Defaults to "" (volume's root).

▼ **subPathExpr** `string`

Expanded path within the volume from which the container's volume should be mounted. Behaves similarly to SubPath but environment variable references $(VAR_NAME) are expanded using the container's environment. Defaults to "" (volume's root). SubPathExpr and SubPath are mutually exclusive.

▼ **workingDir** `string`

Container's working directory. If not specified, the container runtime's default will be used, which might be configured in the container image. Cannot be updated.

▼ **nodeName** `string`

NodeName is a request to schedule this pod onto a specific node. If it is non-empty, the scheduler simply schedules this pod onto that node, assuming that it fits resource requirements.

▼ nodeSelector `object`

NodeSelector is a selector which must be true for the pod to fit on a node. Selector which must match a node's labels for the pod to be scheduled on that node. More info: https://kubernetes.io/docs/concepts/configuration/assign-pod-node/ ↗

▼ os `object`

Specifies the OS of the containers in the pod. Some pod and container fields are restricted if this is set.

If the OS field is set to linux, the following fields must be unset: -securityContext.windowsOptions

If the OS field is set to windows, following fields must be unset:

- spec.hostPID
- spec.hostIPC
- spec.hostUsers
- spec.securityContext.seLinuxOptions
- spec.securityContext.seccompProfile
- spec.securityContext.fsGroup
- spec.securityContext.fsGroupChangePolicy
- spec.securityContext.sysctls
- spec.shareProcessNamespace

- spec.securityContext.runAsUser
- spec.securityContext.runAsGroup
- spec.securityContext.supplementalGroups
- spec.containers[*].securityContext.seLinuxOptions
- spec.containers[*].securityContext.seccompProfile
- spec.containers[*].securityContext.capabilities
- spec.containers[*].securityContext.readOnlyRootFilesystem
- spec.containers[*].securityContext.privileged
- spec.containers[*].securityContext.allowPrivilegeEscalation
- spec.containers[*].securityContext.procMount
- spec.containers[*].securityContext.runAsUser
- spec.containers[*].securityContext.runAsGroup

▼ **name** `string` required

Name is the name of the operating system. The currently supported values are linux and windows. Additional value may be defined in future and can be one of: https://github.com/opencontainers/runtime-spec/blob/master/config.md#platform-specific-configuration ↗ Clients should expect to handle additional values and treat unrecognized values in this field as os: null

▼ **overhead** `object`

Overhead represents the resource overhead associated with running a pod for a given RuntimeClass. This field will be autopopulated at admission time by the RuntimeClass admission controller. If the RuntimeClass admission controller is enabled, overhead must not be set in Pod create requests. The RuntimeClass admission controller will reject Pod create requests which have the overhead already set. If RuntimeClass is configured and selected in the PodSpec, Overhead will be set to the value defined in the corresponding RuntimeClass, otherwise it will remain unset and treated as zero. More info: https://git.k8s.io/enhancements/keps/sig-node/688-pod-overhead/README.md↗

▼ **preemptionPolicy** `string`

PreemptionPolicy is the Policy for preempting pods with lower priority. One of Never, PreemptLowerPriority. Defaults to PreemptLowerPriority if unset.

▼ **priority** `integer`

The priority value. Various system components use this field to find the priority of the pod. When Priority Admission Controller is enabled, it prevents users from setting this field. The admission controller populates this field from PriorityClassName. The higher the value, the higher the priority.

▼ **priorityClassName** `string`

If specified, indicates the pod's priority. "system-node-critical" and "system-cluster-critical" are two special keywords which indicate the highest priorities with the former being the highest priority. Any other name must be defined by creating a PriorityClass object with that name. If not specified, the pod priority will be default or zero if there is no default.

▼ readinessGates `[]object`

PodReadinessGate contains the reference to a pod condition

▼ conditionType `string` required

ConditionType refers to a condition in the pod's condition list with matching type.

▼ resourceClaims `[]object`

PodResourceClaim references exactly one ResourceClaim through a ClaimSource. It adds a name to it that uniquely identifies the ResourceClaim inside the Pod. Containers that need access to the ResourceClaim reference it with this name.

▼ name `string` required

Name uniquely identifies this resource claim inside the pod. This must be a DNS_LABEL.

▼ **source** `object`

Source describes where to find the ResourceClaim.

▼ **resourceClaimName** `string`

ResourceClaimName is the name of a ResourceClaim object in the same namespace as this pod.

▼ **resourceClaimTemplateName** `string`

ResourceClaimTemplateName is the name of a ResourceClaimTemplate object in the same namespace as this pod.

The template will be used to create a new ResourceClaim, which will be bound to this pod. When this pod is deleted, the ResourceClaim will also be deleted. The pod name and resource name, along with a generated component, will be used to form a unique name for the ResourceClaim, which will be recorded in pod.status.resourceClaimStatuses .

This field is immutable and no changes will be made to the corresponding ResourceClaim by

the control plane after creating the ResourceClaim.

▼ restartPolicy `string`

Restart policy for all containers within the pod. One of Always, OnFailure, Never. In some contexts, only a subset of those values may be permitted. Default to Always. More info: https://kubernetes.io/docs/concepts/workloads/pods/pod-lifecycle/#restart-policy ↗

▼ runtimeClassName `string`

RuntimeClassName refers to a RuntimeClass object in the node.k8s.io group, which should be used to run this pod. If no RuntimeClass resource matches the named class, the pod will not be run. If unset or empty, the "legacy" RuntimeClass will be used, which is an implicit class with an empty definition that uses the default runtime handler. More info: https://git.k8s.io/enhancements/keps/sig-node/585-runtime-class ↗

▼ schedulerName `string`

If specified, the pod will be dispatched by specified scheduler. If not specified, the pod will be dispatched by default scheduler.

▼ schedulingGates `[]object`

PodSchedulingGate is associated to a Pod to guard its scheduling.

▼ **name** `string` required

Name of the scheduling gate. Each scheduling gate must have a unique name field.

▼ **securityContext** `object`

SecurityContext holds pod-level security attributes and common container settings. Optional: Defaults to empty. See type description for default values of each field.

▼ **fsGroup** `integer`

A special supplemental group that applies to all containers in a pod. Some volume types allow the Kubelet to change the ownership of that volume to be owned by the pod:

1. The owning GID will be the FSGroup
2. The setgid bit is set (new files created in the volume will be owned by FSGroup)
3. The permission bits are OR'd with rw-rw----

If unset, the Kubelet will not modify the ownership and permissions of any volume. Note that this field cannot be set when spec.os.name is windows.

▼ fsGroupChangePolicy `string`

fsGroupChangePolicy defines behavior of changing ownership and permission of the volume before being exposed inside Pod. This field will only apply to volume types which support fsGroup based ownership(and permissions). It will have no effect on ephemeral volume types such as: secret, configmaps and emptydir. Valid values are "OnRootMismatch" and "Always". If not specified, "Always" is used. Note that this field cannot be set when spec.os.name is windows.

▼ runAsGroup `integer`

The GID to run the entrypoint of the container process. Uses runtime default if unset. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container. Note that this field cannot be set when spec.os.name is windows.

▼ runAsNonRoot `boolean`

Indicates that the container must run as a non-root user. If true, the Kubelet will validate the image at runtime to ensure that it does not run as UID 0 (root) and fail to start the container if it does. If unset or false, no such validation will be performed. May also be set in SecurityContext. If set

in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ runAsUser `integer`

The UID to run the entrypoint of the container process. Defaults to user specified in image metadata if unspecified. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container. Note that this field cannot be set when spec.os.name is windows.

▼ seLinuxOptions `object`

The SELinux context to be applied to all containers. If unspecified, the container runtime will allocate a random SELinux context for each container. May also be set in SecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence for that container. Note that this field cannot be set when spec.os.name is windows.

▼ level `string`

Level is SELinux level label that applies to the container.

▼ role `string`

Role is a SELinux role label that applies to the container.

▼ **type** `string`

Type is a SELinux type label that applies to the container.

▼ **user** `string`

User is a SELinux user label that applies to the container.

▼ **seccompProfile** `object`

The seccomp options to use by the containers in this pod. Note that this field cannot be set when spec.os.name is windows.

▼ **localhostProfile** `string`

localhostProfile indicates a profile defined in a file on the node should be used. The profile must be preconfigured on the node to work. Must be a descending path, relative to the kubelet's configured seccomp profile location. Must be set if type is "Localhost". Must NOT be set for any other type.

▼ **type** `string` required

type indicates which kind of seccomp profile will be applied. Valid options are:

Localhost - a profile defined in a file on the node should be used. RuntimeDefault - the container runtime default profile should be used. Unconfined - no profile should be applied.

▼ supplementalGroups `[]integer`

A list of groups applied to the first process run in each container, in addition to the container's primary GID, the fsGroup (if specified), and group memberships defined in the container image for the uid of the container process. If unspecified, no additional groups are added to any container. Note that group memberships defined in the container image for the uid of the container process are still effective, even if they are not included in this list. Note that this field cannot be set when spec.os.name is windows.

▼ sysctls `[]object`

Sysctl defines a kernel parameter to be set

▼ name `string` required

Name of a property to set

▼ **value** `string` required

Value of a property to set

▼ **windowsOptions** `object`

The Windows specific settings applied to all containers. If unspecified, the options within a container's SecurityContext will be used. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence. Note that this field cannot be set when spec.os.name is linux.

▼ **gmsaCredentialSpec** `string`

GMSACredentialSpec is where the GMSA admission webhook (https://github.com/kubernetes-sigs/windows-gmsa↗) inlines the contents of the GMSA credential spec named by the GMSACredentialSpecName field.

▼ **gmsaCredentialSpecName** `string`

GMSACredentialSpecName is the name of the GMSA credential spec to use.

▼ **hostProcess** `boolean`

HostProcess determines if a container should be run as a 'Host Process' container. All of a Pod's containers must have the same effective HostProcess value (it is not allowed to have a mix of HostProcess containers and non-HostProcess containers). In addition, if HostProcess is true then HostNetwork must also be set to true.

▼ **runAsUserName** `string`

The UserName in Windows to run the entrypoint of the container process. Defaults to the user specified in image metadata if unspecified. May also be set in PodSecurityContext. If set in both SecurityContext and PodSecurityContext, the value specified in SecurityContext takes precedence.

▼ **serviceAccount** `string`

DeprecatedServiceAccount is a depreciated alias for ServiceAccountName. Deprecated: Use serviceAccountName instead.

▼ serviceAccountName `string`

ServiceAccountName is the name of the ServiceAccount to use to run this pod. More info: https://kubernetes.io/docs/tasks/configure-pod-container/configure-service-account/ ↗

▼ setHostnameAsFQDN `boolean`

If true the pod's hostname will be configured as the pod's FQDN, rather than the leaf name (the default). In Linux containers, this means setting the FQDN in the hostname field of the kernel (the nodename field of struct utsname). In Windows containers, this means setting the registry value of hostname for the registry key HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\Tcpip\Parameters to FQDN. If a pod does not have FQDN, this has no effect. Default to false.

▼ shareProcessNamespace `boolean`

Share a single process namespace between all of the containers in a pod. When this is set containers will be able to view and signal processes from other containers in the same pod, and the first process in each container will not be assigned PID 1. HostPID and ShareProcessNamespace cannot both be set. Optional: Default to false.

▼ subdomain `string`

If specified, the fully qualified Pod hostname will be "...svc.". If not specified, the pod will not have a

domainname at all.

▼ terminationGracePeriodSeconds `integer`

Optional duration in seconds the pod needs to terminate gracefully. May be decreased in delete request. Value must be non-negative integer. The value zero indicates stop immediately via the kill signal (no opportunity to shut down). If this value is nil, the default grace period will be used instead. The grace period is the duration in seconds after the processes running in the pod are sent a termination signal and the time when the processes are forcibly halted with a kill signal. Set this value longer than the expected cleanup time for your process. Defaults to 30 seconds.

▼ tolerations `[]object`

The pod this Toleration is attached to tolerates any taint that matches the triple <key,value,effect> using the matching operator .

▼ effect `string`

Effect indicates the taint effect to match. Empty means match all taint effects. When specified, allowed values are NoSchedule, PreferNoSchedule and NoExecute.

▼ key `string`

Key is the taint key that the toleration applies to. Empty means match all taint

keys. If the key is empty, operator must be Exists; this combination means to match all values and all keys.

▼ **operator** `string`

Operator represents a key's relationship to the value. Valid operators are Exists and Equal. Defaults to Equal. Exists is equivalent to wildcard for value, so that a pod can tolerate all taints of a particular category.

▼ **tolerationSeconds** `integer`

TolerationSeconds represents the period of time the toleration (which must be of effect NoExecute, otherwise this field is ignored) tolerates the taint. By default, it is not set, which means tolerate the taint forever (do not evict). Zero and negative values will be treated as 0 (evict immediately) by the system.

▼ **value** `string`

Value is the taint value the toleration matches to. If the operator is Exists, the value should be empty, otherwise just a regular string.

▼ **topologySpreadConstraints** `[]object`

TopologySpreadConstraint specifies how to spread matching pods among the given topology.

▼ **labelSelector** `object`

LabelSelector is used to find matching pods. Pods that match this label selector are counted to determine the number of pods in their corresponding topology domain.

▼ **matchExpressions** `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string`

required

key is the label key that the selector applies to.

▼ **operator** `string`

required

operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.

▼ matchLabels `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ matchLabelKeys `[]string`

MatchLabelKeys is a set of pod label keys to select the pods over which spreading will be calculated. The keys are used to lookup values from the incoming pod labels, those key-value labels are ANDed with labelSelector to select the group of existing pods over which spreading will be calculated for the incoming pod. The same key is forbidden to exist in both MatchLabelKeys and LabelSelector. MatchLabelKeys cannot be set when

LabelSelector isn't set. Keys that don't exist in the incoming pod labels will be ignored. A null or empty list means only match against labelSelector.

This is a beta field and requires the MatchLabelKeysInPodTopologySpread feature gate to be enabled (enabled by default).

▼ maxSkew `integer` required

MaxSkew describes the degree to which pods may be unevenly distributed. When `whenUnsatisfiable=DoNotSchedule`, it is the maximum permitted difference between the number of matching pods in the target topology and the global minimum. The global minimum is the minimum number of matching pods in an eligible domain or zero if the number of eligible domains is less than MinDomains. For example, in a 3-zone cluster, MaxSkew is set to 1, and pods with the same labelSelector spread as 2/2/1: In this case, the global minimum is 1. | zone1 | zone2 | zone3 | | P P | P P | P |

- if MaxSkew is 1, incoming pod can only be scheduled to zone3 to become 2/2/2; scheduling it onto zone1(zone2) would make the ActualSkew(3-1) on zone1(zone2) violate MaxSkew(1).
- if MaxSkew is 2, incoming pod can be scheduled onto any zone. When `whenUnsatisfiable=ScheduleAnyway`, it is used to give higher precedence

to topologies that satisfy it. It's a required field. Default value is 1 and 0 is not allowed.

▼ minDomains `integer`

MinDomains indicates a minimum number of eligible domains. When the number of eligible domains with matching topology keys is less than minDomains, Pod Topology Spread treats "global minimum" as 0, and then the calculation of Skew is performed. And when the number of eligible domains with matching topology keys equals or greater than minDomains, this value has no effect on scheduling. As a result, when the number of eligible domains is less than minDomains, scheduler won't schedule more than maxSkew Pods to those domains. If value is nil, the constraint behaves as if MinDomains is equal to 1. Valid values are integers greater than 0. When value is not nil, WhenUnsatisfiable must be DoNotSchedule.

For example, in a 3-zone cluster, MaxSkew is set to 2, MinDomains is set to 5 and pods with the same labelSelector spread as 2/2/2: | zone1 | zone2 | zone3 | | P P | P P | P P | The number of domains is less than 5(MinDomains), so "global minimum" is treated as 0. In this situation, new pod with the same labelSelector cannot be scheduled, because computed skew will be 3(3 - 0) if new Pod is

scheduled to any of the three zones, it will violate MaxSkew.

This is a beta field and requires the MinDomainsInPodTopologySpread feature gate to be enabled (enabled by default).

▼ nodeAffinityPolicy `string`

NodeAffinityPolicy indicates how we will treat Pod's nodeAffinity/nodeSelector when calculating pod topology spread skew. Options are:

- Honor: only nodes matching nodeAffinity/nodeSelector are included in the calculations.
- Ignore: nodeAffinity/nodeSelector are ignored. All nodes are included in the calculations.

If this value is nil, the behavior is equivalent to the Honor policy. This is a beta-level feature default enabled by the NodeInclusionPolicyInPodTopologySpread feature flag.

▼ nodeTaintsPolicy `string`

NodeTaintsPolicy indicates how we will treat node taints when calculating pod topology spread skew. Options are:

- Honor: nodes without taints, along with tainted nodes for which the incoming pod has a toleration, are included.

- Ignore: node taints are ignored. All nodes are included.

If this value is nil, the behavior is equivalent to the Ignore policy. This is a beta-level feature default enabled by the NodeInclusionPolicyInPodTopologySpread feature flag.

▼ topologyKey `string` required

TopologyKey is the key of node labels. Nodes that have a label with this key and identical values are considered to be in the same topology. We consider each <key, value> as a "bucket", and try to put balanced number of pods into each bucket. We define a domain as a particular instance of a topology. Also, we define an eligible domain as a domain whose nodes meet the requirements of nodeAffinityPolicy and nodeTaintsPolicy. e.g. If TopologyKey is "kubernetes.io/hostname", each Node is a domain of that topology. And, if TopologyKey is "topology.kubernetes.io/zone", each zone is a domain of that topology. It's a required field.

▼ whenUnsatisfiable `string`

required

WhenUnsatisfiable indicates how to deal with a pod if it doesn't satisfy the spread constraint.

- DoNotSchedule (default) tells the scheduler not to schedule it.
- ScheduleAnyway tells the scheduler to schedule the pod in any location, but giving higher precedence to topologies that would help reduce the skew. A constraint is considered "Unsatisfiable" for an incoming pod if and only if every possible node assignment for that pod would violate "MaxSkew" on some topology. For example, in a 3-zone cluster, MaxSkew is set to 1, and pods with the same labelSelector spread as 3/1/1: | zone1 | zone2 | zone3 | | P P P | P | P | If WhenUnsatisfiable is set to DoNotSchedule, incoming pod can only be scheduled to zone2(zone3) to become 3/2/1(3/1/2) as ActualSkew(2-1) on zone2(zone3) satisfies MaxSkew(1). In other words, the cluster can still be imbalanced, but scheduler won't make it *more* imbalanced. It's a required field.

▼ volumes `[]object`

Volume represents a named volume in a pod that may be accessed by any container in the pod.

▼ awsElasticBlockStore `object`

awsElasticBlockStore represents an AWS Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info:

https://kubernetes.io/docs/concepts/storage/volumes#awselasticblockstore↗

▼ **fsType** `string`

fsType is the filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: https://kubernetes.io/docs/concepts/storage/volumes#awselasticblockstore↗

▼ **partition** `integer`

partition is the partition in the volume that you want to mount. If omitted, the default is to mount by volume name. Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty).

▼ **readOnly** `boolean`

readOnly value true will force the readOnly setting in VolumeMounts. More info: https://kubernetes.io/docs/concept

s/storage/volumes#awselasticblockstore↗

▼ **volumeID** `string`

required

volumeID is unique ID of the persistent disk resource in AWS (Amazon EBS volume). More info: https://kubernetes.io/docs/concepts/storage/volumes#awselasticblockstore↗

▼ **azureDisk** `object`

azureDisk represents an Azure Data Disk mount on the host and bind mount to the pod.

▼ **cachingMode** `string`

cachingMode is the Host Caching mode: None, Read Only, Read Write.

▼ **diskName** `string`

required

diskName is the Name of the data disk in the blob storage

▼ **diskURI** `string` required

diskURI is the URI of data disk in the blob storage

▼ **fsType** `string`

fsType is Filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.

▼ **kind** `string`

kind expected values are Shared: multiple blob disks per storage account Dedicated: single blob disk per storage account Managed: azure managed data disk (only in managed availability set). defaults to shared

▼ **readOnly** `boolean`

readOnly Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ **azureFile** `object`

azureFile represents an Azure File Service mount on the host and bind mount to the pod.

▼ **readOnly** `boolean`

readOnly defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ **secretName** `string`

required

secretName is the name of secret that contains Azure Storage Account Name and Key

▼ **shareName** `string`

required

shareName is the azure share Name

▼ **cephfs** `object`

cephFS represents a Ceph FS mount on the host that shares a pod's lifetime

▼ **monitors** `[]string`

required

monitors is Required: Monitors is a collection of Ceph monitors More info: https://examples.k8s.io/volumes/cephfs/README.md#how-to-use-it ↗

▼ path `string`

path is Optional: Used as the mounted root, rather than the full Ceph tree, default is /

▼ readOnly `boolean`

readOnly is Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: https://examples.k8s.io/volumes/cephfs/README.md#how-to-use-it ↗

▼ secretFile `string`

secretFile is Optional: SecretFile is the path to key ring for User, default is /etc/ceph/user.secret More info: https://examples.k8s.io/volumes/cephfs/README.md#how-to-use-it ↗

▼ secretRef `object`

secretRef is Optional: SecretRef is reference to the authentication secret for User, default is empty. More info: https://examples.k8s.io/volumes/cephfs/README.md#how-to-use-it ↗

▼ **name** `string`

Name of the referent.
More info:
https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **user** `string`

user is optional: User is the rados user name, default is admin More info:
https://examples.k8s.io/volumes/cephfs/README.md#how-to-use-it ↗

▼ **cinder** `object`

cinder represents a cinder volume attached and mounted on kubelets host machine. More info:
https://examples.k8s.io/mysql-cinder-pd/README.md ↗

▼ **fsType** `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info:

https://examples.k8s.io/mysql-cinder-pd/README.md↗

▼ **readOnly** `boolean`

readOnly defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts. More info: https://examples.k8s.io/mysql-cinder-pd/README.md↗

▼ **secretRef** `object`

secretRef is optional: points to a secret object containing parameters used to connect to OpenStack.

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names↗

▼ **volumeID** `string`

required

volumeID used to identify the volume in cinder. More info:

https://examples.k8s.io/mysql-cinder-pd/README.md ↗

▼ **configMap** `object`

configMap represents a configMap that should populate this volume

▼ **defaultMode** `integer`

defaultMode is optional: mode bits used to set permissions on created files by default. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **items** `[]object`

Maps a string key to a path within a volume.

▼ **key** `string`

required

key is the key to project.

▼ mode `integer`

mode is Optional: mode bits used to set permissions on this file. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ path `string`

required

path is the relative path of the file to map the key to. May not be an absolute path. May not contain the path element '..'. May not start with the string '..'.

▼ name `string`

Name of the referent. More info: https://kubernetes.io/docs/concept

s/overview/working-with-objects/names/#names ↗

▼ **optional** `boolean`

optional specify whether the ConfigMap or its keys must be defined

▼ **csi** `object`

csi (Container Storage Interface) represents ephemeral storage that is handled by certain external CSI drivers (Beta feature).

▼ **driver** `string` required

driver is the name of the CSI driver that handles this volume. Consult with your admin for the correct name as registered in the cluster.

▼ **fsType** `string`

fsType to mount. Ex. "ext4", "xfs", "ntfs". If not provided, the empty value is passed to the associated CSI driver which will determine the default filesystem to apply.

▼ **nodePublishSecretRef** `object`

nodePublishSecretRef is a reference to the secret object containing sensitive information to pass to the CSI driver to complete the CSI NodePublishVolume and NodeUnpublishVolume calls. This field is optional, and may be empty if no secret is required. If the secret object contains more than one secret, all secret references are passed.

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **readOnly** `boolean`

readOnly specifies a read-only configuration for the volume. Defaults to false (read/write).

▼ **volumeAttributes** `object`

volumeAttributes stores driver-specific properties that are passed to the CSI driver. Consult your

driver's documentation for supported values.

▼ **downwardAPI** `object`

downwardAPI represents downward API about the pod that should populate this volume

▼ **defaultMode** `integer`

Optional: mode bits to use on created files by default. Must be a Optional: mode bits used to set permissions on created files by default. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **items** `[]object`

DownwardAPIVolumeFile represents information to create the file containing the pod field

▼ **fieldRef** `object`

Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.

▼ **apiVersion** `string`

Version of the schema the FieldPath is written in terms of, defaults to "v1".

▼ **fieldPath** `string`

required

Path of the field to select in the specified API version.

▼ **mode** `integer`

Optional: mode bits used to set permissions on this file, must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires

decimal values for mode bits. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **path** `string`

required

Required: Path is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the relative path must not start with '..'

▼ **resourceFieldRef** `object`

Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.

▼ **containerName**

`string`

Container name: required for volumes, optional for env vars

▼ **divisor**

Specifies the output format of the exposed resources, defaults to "1"

▼ **resource** `string`

required

Required: resource to select

▼ **emptyDir** `object`

emptyDir represents a temporary directory that shares a pod's lifetime. More info: https://kubernetes.io/docs/concepts/storage/volumes#emptydir↗

▼ **medium** `string`

medium represents what type of storage medium should back this directory. The default is "" which

means to use the node's default medium. Must be an empty string (default) or Memory. More info: https://kubernetes.io/docs/concepts/storage/volumes#emptydir ↗

▼ sizeLimit

sizeLimit is the total amount of local storage required for this EmptyDir volume. The size limit is also applicable for memory medium. The maximum usage on memory medium EmptyDir would be the minimum value between the SizeLimit specified here and the sum of memory limits of all containers in a pod. The default is nil which means that the limit is undefined. More info: https://kubernetes.io/docs/concepts/storage/volumes#emptydir ↗

▼ ephemeral `object`

ephemeral represents a volume that is handled by a cluster storage driver. The volume's lifecycle is tied to the pod that defines it - it will be created before the pod starts, and deleted when the pod is removed.

Use this if: a) the volume is only needed while the pod runs, b) features of normal volumes like restoring from snapshot or capacity tracking are needed, c) the

storage driver is specified through a storage class, and d) the storage driver supports dynamic volume provisioning through a PersistentVolumeClaim (see EphemeralVolumeSource for more information on the connection between this volume type and PersistentVolumeClaim).

Use PersistentVolumeClaim or one of the vendor-specific APIs for volumes that persist for longer than the lifecycle of an individual pod.

Use CSI for light-weight local ephemeral volumes if the CSI driver is meant to be used that way - see the documentation of the driver for more information.

A pod can use both types of ephemeral volumes and persistent volumes at the same time.

▼ **volumeClaimTemplate** `object`

Will be used to create a stand-alone PVC to provision the volume. The pod in which this EphemeralVolumeSource is embedded will be the owner of the PVC, i.e. the PVC will be deleted together with the pod. The name of the PVC will be `<pod name>-<volume name>` where `<volume name>` is the name from the `PodSpec.Volumes` array entry. Pod validation will reject the pod if the concatenated name is not valid for a PVC (for example, too long).

An existing PVC with that name that is not owned by the pod will *not* be used for the pod to avoid using an unrelated volume by mistake. Starting the pod is then blocked until the unrelated PVC is removed. If such a pre-created PVC is meant to be used by the pod, the PVC has to updated with an owner reference to the pod once the pod exists. Normally this should not be necessary, but it may be useful when manually reconstructing a broken cluster.

This field is read-only and no changes will be made by Kubernetes to the PVC after it has been created.

Required, must not be nil.

▼ **metadata** `object`

May contain labels and annotations that will be copied into the PVC when creating it. No other fields are allowed and will be rejected during validation.

▼ **spec** `object`

required

The specification for the PersistentVolumeClaim. The entire content is copied unchanged into the

PVC that gets created from this template. The same fields as in a PersistentVolumeClaim are also valid here.

▼ **accessModes** `[]string`

accessModes contains the desired access modes the volume should have. More info: https://kubernetes.io/docs/concepts/storage/persistent-volumes#access-modes-1↗

▼ **dataSource** `object`

dataSource field can be used to specify either:

- An existing VolumeSnapshot object (snapshot.storage.k8s.io/VolumeSnapshot)

- An existing PVC (PersistentVolumeClaim) If the provisioner or an external controller can support the specified data source, it will create a new volume based on the contents of the specified data source. When the AnyVolumeDataSource feature gate is enabled, dataSource contents will be copied to dataSourceRef, and dataSourceRef contents will be copied to dataSource when dataSourceRef.namespace is not specified. If the namespace is specified, then dataSourceRef

will not be copied to dataSource.

▼ **apiGroup** `string`

APIGroup is the group for the resource being referenced. If APIGroup is not specified, the specified Kind must be in the core API group. For any other third-party types, APIGroup is required.

▼ **kind** `string`

required

Kind is the type of resource being referenced

▼ **name**

`string`

required

Name is the name of resource being referenced

▼ **dataSourceRef**

`object`

dataSourceRef specifies the object from which to populate the volume with data, if a non-empty volume is desired. This may be any object from a non-empty API group (non core object) or a PersistentVolumeClaim object.

When this field is specified, volume binding will only succeed if the type of the specified object matches some installed volume populator or dynamic provisioner. This field will replace the functionality of the dataSource field and as such if both fields are non-empty, they must have the same value. For backwards compatibility, when namespace isn't specified in dataSourceRef, both fields (dataSource and dataSourceRef) will be set to the same value automatically if one of them is empty and the other is non-empty. When namespace is specified in dataSourceRef, dataSource isn't

set to the same value and must be empty. There are three important differences between dataSource and dataSourceRef:

- While dataSource only allows two specific types of objects, dataSourceRef allows any non-core object, as well as PersistentVolumeClaim objects.
- While dataSource ignores disallowed values (dropping them), dataSourceRef preserves all values, and generates an error if a disallowed value is specified.

- While dataSource only allows local objects, dataSourceRef allows objects in any namespaces. (Beta) Using this field requires the AnyVolumeDataSource feature gate to be enabled. (Alpha) Using the namespace field of dataSourceRef requires the CrossNamespaceVolumeDataSource feature gate to be enabled.

▼ **apiGroup** `string`

APIGroup is the group for the resource being referenced

. If APIGroup is not specified, the specified Kind must be in the core API group. For any other third-party types, APIGroup is required.

▼ **kind**

`string`

required

Kind is the type of resource being referenced

▼ **name**

`string`

required

Name is the name of resource

being referenced

▼ **namespace** `string`

Namespace is the namespace of resource being referenced Note that when a namespace is specified, a gateway.networking.k8s.io/ReferenceGrant object is required in the referent namespace to allow that namespace's owner to accept the reference.

See the ReferenceGrant documentation for details. (Alpha) This field requires the CrossNamespaceVolumeDataSource feature gate to be enabled.

▼ resources

`object`

resources represents the minimum resources the volume should have. If RecoverVolumeExpansionFailure feature is enabled users are allowed to specify resource requirements that are lower than previous value but

must still be higher than capacity recorded in the status field of the claim. More info: https://kubernetes.io/docs/concepts/storage/persistent-volumes#resources ↗

▼ **limits**

`object`

Limits describes the maximum amount of compute resources allowed. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/ ↗

▼ **requests**

			`object`	Requests describes the minimum amount of compute resources required. If Requests is omitted for a container, it defaults to Limits if that is explicitly specified, otherwise to an implementation-defined value. Requests cannot exceed Limits. More info: https://kubernetes.io/docs/concepts/configuration/manage-resources-

containers/↗

▼ **selector** `object`

selector is a label query over volumes to consider for binding.

▼ **matchExpressions** `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `s`

key `string` required

key is the label key that the selector applies to.

▼ **operator** `string` required

operator represents a key's relationship to a set of values. Valid operators are In, N

otIn, Exists and DoesNotExist.

▼ **values** `[]string`

values is an array of string va

lu
es
. If
th
e
op
er
at
or
is
In
or
N
otI
n,
th
e
va
lu
es
ar
ra
y
m
us
t
be
no
n-
e
m
pt
y.
If
th
e
op

er
at
or
is
Ex
ist
s
or
D
oe
s
N
ot
Ex
ist
,
th
e
va
lu
es
ar
ra
y
m
us
t
be
e
m
pt
y.
Th
is
ar
ra
y

is replaced during a strategic merge patch.

▼ **matchLabels** `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an

element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **storageClassName** `string`

storageClassName is the name of the StorageClass required by the claim. More info: https://kubernetes.io/docs/concepts/storage/persistent-volumes#class-1 ↗

▼ **volumeAttributesClassName**

`string`

volumeAttributesClassName may be used to set the VolumeAttributesClass used by this claim. If specified, the CSI driver will create or update the volume with the attributes defined in the corresponding VolumeAttributesClass. This has a different purpose than storageClassName, it can be changed after the claim is created. An empty string value means that no VolumeAttributesClass will be applied to the claim but it's not allowed to reset this field to empty string once it is set. If unspecified and the PersistentVolumeClaim is unbound, the default VolumeAttributesC

lass will be set by the persistentvolume controller if it exists. If the resource referred to by volumeAttributesClass does not exist, this PersistentVolumeClaim will be set to a Pending state, as reflected by the modifyVolumeStatus field, until such as a resource exists. More info: https://kubernetes.io/docs/concepts/storage/persistent-volumes#volumeattributesclass↗ (Alpha) Using this field requires the VolumeAttributesClass feature gate to be enabled.

▼ volumeMode

`string`

volumeMode defines what type of volume is required by the

claim. Value of Filesystem is implied when not included in claim spec.

▼ **volumeName** `string`

volumeName is the binding reference to the PersistentVolume backing this claim.

▼ **fc** `object`

fc represents a Fibre Channel resource that is attached to a kubelet's host machine and then exposed to the pod.

▼ **fsType** `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.

▼ **lun** `integer`

lun is Optional: FC target lun number

▼ **readOnly** `boolean`

readOnly is Optional: Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ **targetWWNs** `[]string`

targetWWNs is Optional: FC target worldwide names (WWNs)

▼ **wwids** `[]string`

wwids Optional: FC volume world wide identifiers (wwids) Either wwids or combination of targetWWNs and lun must be set, but not both simultaneously.

▼ **flexVolume** `object`

flexVolume represents a generic volume resource that is provisioned/attached using an exec based plugin.

▼ **driver** `string` required

driver is the name of the driver to use for this volume.

▼ **fsType** `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". The default filesystem depends on FlexVolume script.

▼ **options** `object`

options is Optional: this field holds extra command options if any.

▼ **readOnly** `boolean`

readOnly is Optional: defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ **secretRef** `object`

secretRef is Optional: secretRef is reference to the secret object containing sensitive information to pass to the plugin scripts. This may be empty if no secret object is specified. If the secret object contains more than one secret, all secrets are passed to the plugin scripts.

▼ **name** `string`

Name of the referent.
More info:
https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ flocker `object`

flocker represents a Flocker volume attached to a kubelet's host machine. This depends on the Flocker control service being running

▼ datasetName `string`

datasetName is Name of the dataset stored as metadata -> name on the dataset for Flocker should be considered as deprecated

▼ datasetUUID `string`

datasetUUID is the UUID of the dataset. This is unique identifier of a Flocker dataset

▼ gcePersistentDisk `object`

gcePersistentDisk represents a GCE Disk resource that is attached to a kubelet's host machine and then exposed to the

pod. More info: https://kubernetes.io/docs/concepts/storage/volumes#gcepersistentdisk ↗

▼ **fsType** `string`

fsType is filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: https://kubernetes.io/docs/concepts/storage/volumes#gcepersistentdisk ↗

▼ **partition** `integer`

partition is the partition in the volume that you want to mount. If omitted, the default is to mount by volume name. Examples: For volume /dev/sda1, you specify the partition as "1". Similarly, the volume partition for /dev/sda is "0" (or you can leave the property empty). More info: https://kubernetes.io/docs/concepts/storage/volumes#gcepersistentdisk ↗

▼ **pdName** `string` required

pdName is unique name of the PD resource in GCE. Used to identify the disk in GCE. More info: https://kubernetes.io/docs/concepts/storage/volumes#gcepersistentdisk ↗

▼ **readOnly** `boolean`

readOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: https://kubernetes.io/docs/concepts/storage/volumes#gcepersistentdisk ↗

▼ **gitRepo** `object`

gitRepo represents a git repository at a particular revision. DEPRECATED: GitRepo is deprecated. To provision a container with a git repo, mount an EmptyDir into an InitContainer that clones the repo using git, then mount the EmptyDir into the Pod's container.

▼ **directory** `string`

directory is the target directory name. Must not contain or start with '..'. If '.' is supplied, the volume directory will be the git repository. Otherwise, if specified, the volume

will contain the git repository in the subdirectory with the given name.

▼ **repository** `string`

required

repository is the URL

▼ **revision** `string`

revision is the commit hash for the specified revision.

▼ **glusterfs** `object`

glusterfs represents a Glusterfs mount on the host that shares a pod's lifetime. More info: https://examples.k8s.io/volumes/glusterfs/README.md ↗

▼ **endpoints** `string`

required

endpoints is the endpoint name that details Glusterfs topology. More info: https://examples.k8s.io/volumes/glusterfs/README.md#create-a-pod ↗

▼ **path** `string` required

path is the Glusterfs volume path. More info: https://examples.k8s.io/volumes/glusterfs/README.md#create-a-pod ↗

▼ **readOnly** `boolean`

readOnly here will force the Glusterfs volume to be mounted with read-only permissions. Defaults to false. More info: https://examples.k8s.io/volumes/glusterfs/README.md#create-a-pod ↗

▼ **hostPath** `object`

hostPath represents a pre-existing file or directory on the host machine that is directly exposed to the container. This is generally used for system agents or other privileged things that are allowed to see the host machine. Most containers will NOT need this. More info: https://kubernetes.io/docs/concepts/storage/volumes#hostpath ↗

▼ **path** `string` required

path of the directory on the host. If the path is a symlink, it will follow the link to the real path. More info:

https://kubernetes.io/docs/concepts/storage/volumes#hostpath ↗

▼ **type** `string`

type for HostPath Volume Defaults to "" More info: https://kubernetes.io/docs/concepts/storage/volumes#hostpath ↗

▼ **iscsi** `object`

iscsi represents an ISCSI Disk resource that is attached to a kubelet's host machine and then exposed to the pod. More info: https://examples.k8s.io/volumes/iscsi/README.md ↗

▼ **chapAuthDiscovery** `boolean`

chapAuthDiscovery defines whether support iSCSI Discovery CHAP authentication

▼ **chapAuthSession** `boolean`

chapAuthSession defines whether support iSCSI Session CHAP authentication

▼ fsType `string`

fsType is the filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: https://kubernetes.io/docs/concepts/storage/volumes#iscsi ↗

▼ initiatorName `string`

initiatorName is the custom iSCSI Initiator Name. If initiatorName is specified with iscsiInterface simultaneously, new iSCSI interface : will be created for the connection.

▼ iqn `string` required

iqn is the target iSCSI Qualified Name.

▼ iscsiInterface `string`

iscsiInterface is the interface Name that uses an iSCSI transport. Defaults to 'default' (tcp).

▼ **lun** `integer` required

lun represents iSCSI Target Lun number.

▼ **portals** `[]string`

portals is the iSCSI Target Portal List. The portal is either an IP or ip_addr:port if the port is other than default (typically TCP ports 860 and 3260).

▼ **readOnly** `boolean`

readOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false.

▼ **secretRef** `object`

secretRef is the CHAP Secret for iSCSI target and initiator authentication

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **targetPortal** `string`

required

targetPortal is iSCSI Target Portal. The Portal is either an IP or ip_addr:port if the port is other than default (typically TCP ports 860 and 3260).

▼ **name** `string` required

name of the volume. Must be a DNS_LABEL and unique within the pod. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **nfs** `object`

nfs represents an NFS mount on the host that shares a pod's lifetime More info: https://kubernetes.io/docs/concepts/storage/volumes#nfs ↗

▼ **path** `string` required

path that is exported by the NFS server. More info: https://kubernetes.io/docs/concepts/storage/volumes#nfs ↗

▼ **readOnly** `boolean`

readOnly here will force the NFS export to be mounted with read-only permissions. Defaults to false. More info: https://kubernetes.io/docs/concepts/storage/volumes#nfs ↗

▼ **server** `string` required

server is the hostname or IP address of the NFS server. More info: https://kubernetes.io/docs/concepts/storage/volumes#nfs ↗

▼ **persistentVolumeClaim** `object`

persistentVolumeClaimVolumeSource represents a reference to a PersistentVolumeClaim in the same namespace. More info: https://kubernetes.io/docs/concepts/storage/persistent-volumes#persistentvolumeclaims ↗

▼ **claimName** `string`

required

claimName is the name of a PersistentVolumeClaim in the same namespace as the pod using this volume. More info: https://kubernetes.io/docs/concepts/storage/persistent-

volumes#persistentvolumeclaims ↗

▼ **readOnly** `boolean`

readOnly Will force the ReadOnly setting in VolumeMounts. Default false.

▼ **photonPersistentDisk** `object`

photonPersistentDisk represents a PhotonController persistent disk attached and mounted on kubelets host machine

▼ **fsType** `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.

▼ **pdID** `string` required

pdID is the ID that identifies Photon Controller persistent disk

▼ **portworxVolume** `object`

portworxVolume represents a portworx volume attached and mounted on kubelets

host machine

▼ **fsType** `string`

fSType represents the filesystem type to mount Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs". Implicitly inferred to be "ext4" if unspecified.

▼ **readOnly** `boolean`

readOnly defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ **volumeID** `string`

required

volumeID uniquely identifies a Portworx volume

▼ **projected** `object`

projected items for all in one resources secrets, configmaps, and downward API

▼ **defaultMode** `integer`

defaultMode are the mode bits used to set permissions on created files by default. Must be an octal value between 0000 and

0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ sources `[]object`

Projection that may be projected along with other supported volume types

▼ clusterTrustBundle `object`

ClusterTrustBundle allows a pod to access the `.spec.trustBundle` field of ClusterTrustBundle objects in an auto-updating file.

Alpha, gated by the ClusterTrustBundleProjection feature gate.

ClusterTrustBundle objects can either be selected by name, or by the combination of signer name and a label selector.

Kubelet performs aggressive normalization

of the PEM contents written into the pod filesystem. Esoteric PEM features such as inter-block comments and block headers are stripped. Certificates are deduplicated. The ordering of certificates within the file is arbitrary, and Kubelet may change the order over time.

▼ **labelSelector**
`object`

Select all ClusterTrustBundles that match this label selector. Only has effect if signerName is set. Mutually-exclusive with name. If unset, interpreted as "match nothing". If set but empty, interpreted as "match everything".

▼ **matchExpressions**
`[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ **key** `string` required

key is the label key that th

e se le ct or ap pli es to.

▼ **operator** `string` required

op er at or re pr es en ts a ke y's rel ati on sh ip to a

set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ **values**

`[]string`

values is an array of string values. If the operator is In or NotIn, the valu

es
ar
ra
y
m
us
t
be
no
n-
e
m
pt
y.
If
th
e
op
er
at
or
is
Ex
ist
s
or
D
oe
s
N
ot
Ex
ist
,
th
e
va

lu
es
ar
ra
y
m
us
t
be
e
m
pt
y.
Th
is
ar
ra
y
is
re
pl
ac
ed
du
rin
g
a
str
at
eg
ic
m
er
ge
pa
tc
h.

▼

matchLabels

`object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **name**

`string`

Select a single ClusterTrustBundle by object name. Mutually-exclusive with signerName and labelSelector.

▼ **optional**

`boolean`

If true, don't block pod startup if the referenced ClusterTrustBundle(s) aren't available. If using name, then the named ClusterTrustBundle is allowed not to exist. If using signerName, then the combination of signerName and labelSelector is allowed to match zero ClusterTrustBundles.

▼ **path**

`string`

required

Relative path from the volume root to write the bundle.

▼ **signerName** `string`

Select all ClusterTrustBundles that match this signer name. Mutually-exclusive with name. The contents of all selected ClusterTrustBundles will be unified and deduplicated.

▼ **configMap** `object`

configMap information about the configMap data to project

▼ **items** `[]object`

Maps a string key to a path within a volume.

▼ **key**

`string`

required

key is the key to project.

▼ **mode**

`integer`

mode is Optional: mode bits used to set permissions on this file. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON

requires decimal values for mode bits. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **path**

`string`

required

path is the relative path of the file to map the key to. May not be an

absolute path. May not contain the path element '..'. May not start with the string '..'.

▼ name

`string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ optional

`boolean`

optional specify whether the ConfigMap or its keys must be defined

▼ **downwardAPI**
`object`

downwardAPI information about the downwardAPI data to project

▼ **items**
`[]object`

DownwardAPIVolumeFile represents information to create the file containing the pod field

▼ **fieldRef**
`object`

Required: Selects a field of the pod: only annotations, labels, name and namespace are supported.

▼ **apiVersion**
`str`

`string`	Version of the schema the Field Path is written in terms of, defaults to "v1".

▼ **fieldPath** `string` required

Path of the field to select in the specified API version.

▼ **mode** `integer`

Optional: mode bits used to set permissions on this file, must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. If not specified, the volume defaultMode will be

used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **path**

`string`

required

Required: Path is the relative path name of the file to be created. Must not be absolute or contain the '..' path. Must be utf-8 encoded. The first item of the

relative path must not start with '..'

▼ **resourceFieldRef** `object`

Selects a resource of the container: only resources limits and requests (limits.cpu, limits.memory, requests.cpu and requests.memory) are currently supported.

▼ **containerName** `string`

C on

tainer name: required for volumes, optional for env vars

▼ **divisor**

Specifies the

output format of the exposed resources, defaults to "1"

▼ **resource** `string` required

Requir

ed
:
re
so
ur
ce
to
se
le
ct

▼ **secret** `object`

secret information about the secret data to project

▼ **items** `[]object`

Maps a string key to a path within a volume.

▼ **key** `string` required

key is the key to project.

▼ **mode** `integer`

| | | |

with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **path**

`string`

required

path is the relative path of the file to map the key to. May not be an absolute path. May not contain the path element '..'. May not start with the string '..'.

▼ **name**

`string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **optional**

`boolean`

optional field specify whether the Secret or its key must be defined

▼ **serviceAccountToken**

`object`

serviceAccountToken is information about the serviceAccountToken data to project

▼ **audience**

`string`

audience is the intended audience of the token. A recipient of a token must identify itself with an identifier specified in the audience of the token, and otherwise should reject the token. The audience defaults to the identifier of the apiserver.

▼ **expirationSeconds** `integer`

expirationSeconds is the requested duration of validity of the service account token. As the token approaches expiration, the kubelet volume plugin will proactively rotate the service account token. The kubelet will start trying to rotate the token if

the token is older than 80 percent of its time to live or if the token is older than 24 hours.Defaults to 1 hour and must be at least 10 minutes.

▼ **path** `string`

required

path is the path relative to the mount point of the file to project the token into.

▼ **quobyte** `object`

quobyte represents a Quobyte mount on the host that shares a pod's lifetime

▼ **group** `string`

group to map volume access to Default is no group

▼ **readOnly** `boolean`

readOnly here will force the Quobyte volume to be mounted

with read-only permissions.
Defaults to false.

▼ **registry** `string` required

registry represents a single or multiple Quobyte Registry services specified as a string as host:port pair (multiple entries are separated with commas) which acts as the central registry for volumes

▼ **tenant** `string`

tenant owning the given Quobyte volume in the Backend Used with dynamically provisioned Quobyte volumes, value is set by the plugin

▼ **user** `string`

user to map volume access to
Defaults to serivceaccount user

▼ **volume** `string` required

volume is a string that references an already created Quobyte volume by name.

▼ **rbd** `object`

rbd represents a Rados Block Device mount on the host that shares a pod's lifetime. More info: https://examples.k8s.io/volumes/rbd/README.md ↗

▼ fsType `string`

fsType is the filesystem type of the volume that you want to mount. Tip: Ensure that the filesystem type is supported by the host operating system. Examples: "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified. More info: https://kubernetes.io/docs/concepts/storage/volumes#rbd ↗

▼ image `string` required

image is the rados image name. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ keyring `string`

keyring is the path to key ring for RBDUser. Default is /etc/ceph/keyring. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ monitors `[]string`

required

monitors is a collection of Ceph monitors. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ pool `string`

pool is the rados pool name. Default is rbd. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ readOnly `boolean`

readOnly here will force the ReadOnly setting in VolumeMounts. Defaults to false. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ secretRef `object`

secretRef is name of the authentication secret for RBDUser. If provided overrides keyring. Default is nil. More info: https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ name `string`

Name of the referent.
More info:
https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **user** `string`

user is the rados user name.
Default is admin. More info:
https://examples.k8s.io/volumes/rbd/README.md#how-to-use-it ↗

▼ **scaleIO** `object`

scaleIO represents a ScaleIO persistent volume attached and mounted on Kubernetes nodes.

▼ **fsType** `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Default is "xfs".

▼ **gateway** `string` required

gateway is the host address of the ScaleIO API Gateway.

▼ protectionDomain `string`

protectionDomain is the name of the ScaleIO Protection Domain for the configured storage.

▼ readOnly `boolean`

readOnly Defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ secretRef `object`

required

secretRef references to the secret for ScaleIO user and other sensitive information. If this is not provided, Login operation will fail.

▼ name `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ sslEnabled `boolean`

sslEnabled Flag enable/disable SSL communication with Gateway, default false

▼ **storageMode** `string`

storageMode indicates whether the storage for a volume should be ThickProvisioned or ThinProvisioned. Default is ThinProvisioned.

▼ **storagePool** `string`

storagePool is the ScaleIO Storage Pool associated with the protection domain.

▼ **system** `string` required

system is the name of the storage system as configured in ScaleIO.

▼ **volumeName** `string`

volumeName is the name of a volume already created in the ScaleIO system that is associated with this volume source.

▼ **secret** `object`

secret represents a secret that should populate this volume. More info: https://kubernetes.io/docs/concepts/storage/volumes#secret ↗

▼ **defaultMode** `integer`

defaultMode is Optional: mode bits used to set permissions on created files by default. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. Defaults to 0644. Directories within the path are not affected by this setting. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **items** `[]object`

Maps a string key to a path within a volume.

▼ **key** `string`

required

key is the key to project.

▼ **mode** `integer`

mode is Optional: mode bits used to set permissions on this file. Must be an octal value between 0000 and 0777 or a decimal value between 0 and 511. YAML accepts both octal and decimal values, JSON requires decimal values for mode bits. If not specified, the volume defaultMode will be used. This might be in conflict with other options that affect the file mode, like fsGroup, and the result can be other mode bits set.

▼ **path** `string`

required

path is the relative path of the file to map the key to. May not be an absolute path. May not contain the path element '..'. May not start with the string '..'.

▼ **optional** `boolean`

optional field specify whether the Secret or its keys must be defined

▼ secretName `string`

secretName is the name of the secret in the pod's namespace to use. More info: https://kubernetes.io/docs/concepts/storage/volumes#secret ↗

▼ storageos `object`

storageOS represents a StorageOS volume attached and mounted on Kubernetes nodes.

▼ fsType `string`

fsType is the filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.

▼ readOnly `boolean`

readOnly defaults to false (read/write). ReadOnly here will force the ReadOnly setting in VolumeMounts.

▼ secretRef `object`

secretRef specifies the secret to use for obtaining the StorageOS

API credentials. If not specified, default values will be attempted.

▼ **name** `string`

Name of the referent.
More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **volumeName** `string`

volumeName is the human-readable name of the StorageOS volume. Volume names are only unique within a namespace.

▼ **volumeNamespace** `string`

volumeNamespace specifies the scope of the volume within StorageOS. If no namespace is specified then the Pod's namespace will be used. This allows the Kubernetes name scoping to be mirrored within StorageOS for tighter integration. Set VolumeName to any name to override the default behaviour. Set to "default" if you are not using namespaces within StorageOS.

Namespaces that do not pre-exist within StorageOS will be created.

▼ vsphereVolume `object`

vsphereVolume represents a vSphere volume attached and mounted on kubelets host machine

▼ fsType `string`

fsType is filesystem type to mount. Must be a filesystem type supported by the host operating system. Ex. "ext4", "xfs", "ntfs". Implicitly inferred to be "ext4" if unspecified.

▼ storagePolicyID `string`

storagePolicyID is the storage Policy Based Management (SPBM) profile ID associated with the StoragePolicyName.

▼ storagePolicyName `string`

storagePolicyName is the storage Policy Based Management (SPBM) profile name.

▼ volumePath `string`

required

volumePath is the path that identifies vSphere volume vmdk

▼ **serviceAccountName** `string`

▼ **triggerGroups** `[]object`

EventListenerTriggerGroup defines a group of Triggers that share a common set of interceptors

▼ **interceptors** `[]object` required

TriggerInterceptor provides a hook to intercept and pre-process events

▼ **name** `string`

Optional name to identify the current interceptor configuration

▼ **params** `[]object`

InterceptorParams defines a key-value pair that can be passed on an interceptor

▼ **name** `string` required

▼ **value** required

▼ **ref** `object` required

Ref refers to the Interceptor to use

▼ **apiVersion** `string`

API version of the referent

▼ **kind** `string`

InterceptorKind indicates the kind of the Interceptor, namespaced or cluster scoped.

▼ **name** `string`

Name of the referent; More info: http://kubernetes.io/docs/user-guide/identifiers#names ↗

▼ **webhook** `object`

WebhookInterceptor refers to an old style webhook interceptor service

▼ **header** `[]object`

Param declares an ParamValues to use for the parameter called name.

▼ **name** `string` required

▼ **value** `object` required

ParamValue is a type that can hold a single string or string array. Used in JSON unmarshalling so that a single JSON field can accept either an individual string or an array of strings.

▼ objectRef `object`

ObjectRef is a reference to an object that will resolve to a cluster DNS name to use as the EventInterceptor. Either objectRef or url can be specified

▼ apiVersion `string`

API version of the referent.

▼ fieldPath `string`

If referring to a piece of an object instead of an entire object, this string should contain a valid JSON/Go field access statement, such as desiredState.manifest.containers[2]. For example, if the object reference is to a container within a pod, this would take on a value like: "spec.containers{name}" (where "name" refers to the name of the container that triggered the event) or if no container name is specified "spec.containers[2]" (container with index 2 in this pod). This syntax is chosen only to have some well-defined way of referencing a part of an object.

▼ kind `string`

Kind of the referent. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds ↗

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **namespace** `string`

Namespace of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/namespaces/ ↗

▼ **resourceVersion** `string`

Specific resourceVersion to which this reference is made, if any. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#concurrency-control-and-consistency ↗

▼ **uid** `string`

UID of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#uids ↗

▼ **url** `string`

▼ **name** `string` required

▼ triggerSelector `object` required

EventListenerTriggerSelector defines ways to select a group of triggers using their metadata

▼ labelSelector `object`

A label selector is a label query over a set of resources. The result of matchLabels and matchExpressions are ANDed. An empty label selector matches all objects. A null label selector matches no objects.

▼ matchExpressions `[]object`

A label selector requirement is a selector that contains values, a key, and an operator that relates the key and values.

▼ key `string` required

key is the label key that the selector applies to.

▼ operator `string` required

operator represents a key's relationship to a set of values. Valid operators are In, NotIn, Exists and DoesNotExist.

▼ values `[]string`

values is an array of string values. If the operator is In or NotIn, the values array must be non-empty. If the operator is Exists or DoesNotExist, the values array must be empty. This array is replaced during a strategic merge patch.

▼ matchLabels `object`

matchLabels is a map of {key,value} pairs. A single {key,value} in the matchLabels map is equivalent to an element of matchExpressions, whose key field is "key", the operator is "In", and the values array contains only "value". The requirements are ANDed.

▼ **namespaceSelector** `object`

NamespaceSelector is a selector for selecting either all namespaces or a list of namespaces.

▼ **matchNames** `[]string`

List of namespace names.

▼ **triggers** `[]object`

EventListenerTrigger represents a connection between TriggerBinding, Params, and TriggerTemplate; TriggerBinding provides extracted values for TriggerTemplate to then create resources from. TriggerRef can also be provided instead of TriggerBinding, Interceptors and TriggerTemplate

▼ **bindings** `[]object`

▼ **apiversion** `string`

APIVersion of the binding ref

▼ **kind** `string`

Kind can only be provided if Ref is also provided. Defaults to TriggerBinding

▼ **name** `string`

Name is the name of the binding param Mutually exclusive with Ref

▼ **ref** `string`

Ref is a reference to a TriggerBinding kind. Mutually exclusive with Name

▼ **value** `string`

Value is the value of the binding param. Can contain JSONPath Has to be pointer since "" is a valid value Required if Name is also specified.

▼ **interceptors** `[]object`

TriggerInterceptor provides a hook to intercept and pre-process events

▼ **name** `string`

Optional name to identify the current interceptor configuration

▼ **params** `[]object`

InterceptorParams defines a key-value pair that can be passed on an interceptor

▼ **name** `string` required

▼ **value** required

▼ **ref** `object` required

Ref refers to the Interceptor to use

▼ **apiVersion** `string`

API version of the referent

▼ **kind** `string`

InterceptorKind indicates the kind of the Interceptor, namespaced or cluster scoped.

▼ **name** `string`

Name of the referent; More info: http://kubernetes.io/docs/user-guide/identifiers#names ↗

▼ **webhook** `object`

WebhookInterceptor refers to an old style webhook interceptor service

▼ **header** `[]object`

Param declares an ParamValues to use for the parameter called name.

▼ **name** `string` required

▼ value `object` required

ParamValue is a type that can hold a single string or string array. Used in JSON unmarshalling so that a single JSON field can accept either an individual string or an array of strings.

▼ objectRef `object`

ObjectRef is a reference to an object that will resolve to a cluster DNS name to use as the EventInterceptor. Either objectRef or url can be specified

▼ apiVersion `string`

API version of the referent.

▼ fieldPath `string`

If referring to a piece of an object instead of an entire object, this string should contain a valid JSON/Go field access statement, such as desiredState.manifest.containers[2]. For example, if the object reference is to a container within a pod, this would take on a value like: "spec.containers{name}" (where "name" refers to the name of the container that triggered the event) or if no container name is specified "spec.containers[2]" (container with index 2 in this pod). This syntax is chosen only to have some well-defined way of referencing a part of an object.

▼ kind `string`

Kind of the referent. More info: https://git.k8s.io/community/contributors/devel/sig-

architecture/api-conventions.md#types-kinds ↗

▼ **name** `string`

Name of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#names ↗

▼ **namespace** `string`

Namespace of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/namespaces/ ↗

▼ **resourceVersion** `string`

Specific resourceVersion to which this reference is made, if any. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#concurrency-control-and-consistency ↗

▼ **uid** `string`

UID of the referent. More info: https://kubernetes.io/docs/concepts/overview/working-with-objects/names/#uids ↗

▼ **url** `string`

▼ **name** `string`

▼ **serviceAccountName** `string`

ServiceAccountName optionally associates credentials with each trigger; more granular authorization for who is allowed to utilize the associated pipeline vs. defaulting to whatever permissions are associated with the entire EventListener and associated sink facilitates multi-tenant model based scenarios

▼ **template** `object`

▼ **apiversion** `string`

▼ **ref** `string`

▼ **spec** `object`

TriggerTemplateSpec holds the desired state of TriggerTemplate

▼ **params** `[]object`

ParamSpec defines an arbitrary named input whose value can be supplied by a `Param`.

▼ **default** `string`

Default is the value a parameter takes if no input value via a Param is supplied.

▼ **description** `string`

Description is a user-facing description of the parameter that may be used to populate a UI.

▼ **name** `string` required

Name declares the name by which a parameter is referenced.

▼ **resourcetemplates** `[]object`

TriggerResourceTemplate describes a resource to create

▼ **triggerRef** `string`

▼ **status** `object`

EventListenerStatus holds the status of the EventListener

▼ **address** `object`

Address is a single Addressable address. If Addresses is present, Address will be ignored by clients.

▼ **CACerts** `string`

CACerts is the Certification Authority (CA) certificates in PEM format according to https://www.rfc-editor.org/rfc/rfc7468↗.

▼ **name** `string`

Name is the name of the address.

▼ **url** `string`

▼ **addresses** `[]object`

Addressable provides a generic mechanism for a custom resource definition to indicate a destination for message delivery.

Addressable is the schema for the destination information. This is typically stored in the object's `status`, as this information may be generated by the controller.

▼ **CACerts** `string`

CACerts is the Certification Authority (CA) certificates in PEM format according to https://www.rfc-editor.org/rfc/rfc7468↗.

▼ **name** `string`

Name is the name of the address.

▼ **url** `string`

▼ **annotations** `object`

Annotations is additional Status fields for the Resource to save some additional State as well as convey more information to the user. This is roughly akin to Annotations on any k8s resource, just the reconciler conveying richer information outwards.

▼ **conditions** `[]object`

Condition defines a readiness condition for a Knative resource. See: https://github.com/kubernetes/community/blob/master/contributors/devel/sig-architecture/api-conventions.md#typical-status-properties ↗

▼ lastTransitionTime `string`

LastTransitionTime is the last time the condition transitioned from one status to another. We use VolatileTime in place of metav1.Time to exclude this from creating equality.Semantic differences (all other things held constant).

▼ message `string`

A human readable message indicating details about the transition.

▼ reason `string`

The reason for the condition's last transition.

▼ severity `string`

Severity with which to treat failures of this type of condition. When this is not specified, it defaults to Error.

▼ status `string` required

Status of the condition, one of True, False, Unknown.

▼ type `string` required

Type of condition.

▼ **configuration** `object` required

Configuration stores configuration for the EventListener service

▼ **generatedName** `string` required

GeneratedResourceName is the name given to all resources reconciled by the EventListener

▼ **observedGeneration** `integer`

ObservedGeneration is the 'Generation' of the Service that was last processed by the controller.

触发绑定 [triggers.tekton.dev/v1beta1]

`triggers.tekton.dev` group

TriggerBinding defines a mapping of an input event to parameters. This is used to extract information from events to be passed to TriggerTemplates within a Trigger.

`v1alpha1` version

▼ spec `object`

Spec holds the desired state of the TriggerBinding

▼ params `[]object`

Param defines a string value to be used for a ParamSpec with the same name.

▼ name `string` required

▼ value `string` required

▼ status `object`

TriggerBindingStatus defines the observed state of TriggerBinding.

TriggerBinding defines a mapping of an input event to parameters. This is used to extract information from events to be passed to TriggerTemplates within a Trigger.

`v1beta1` version

▼ spec `object`

Spec holds the desired state of the TriggerBinding

▼ params `[]object`

Param defines a string value to be used for a ParamSpec with the same name.

▼ name `string` required

▼ value `string` required

▼ status `object`

TriggerBindingStatus defines the observed state of TriggerBinding.

拦截器 [triggers.tekton.dev/v1alpha1]

`triggers.tekton.dev` group

Interceptor describes a pluggable interceptor including configuration such as the fields it accepts and its deployment address. The type is based on the Validating/MutatingWebhookConfiguration types for configuring AdmissionWebhooks

`v1alpha1` version

▼ spec `object` required

InterceptorSpec describes the Spec for an Interceptor

▼ clientConfig `object` required

ClientConfig describes how a client can communicate with the Interceptor

▼ caBundle `string`

CaBundle is a PEM encoded CA bundle which will be used to validate the clusterinterceptor server certificate

▼ service `object`

Service is a reference to a Service object where the interceptor is running Mutually exclusive with URL

▼ name `string` required

Name is the name of the service

▼ **namespace** `string` required

Namespace is the namespace of the service

▼ **path** `string`

Path is an optional URL path

▼ **port** `integer`

Port is a valid port number

▼ **url** `string`

URL is a fully formed URL pointing to the interceptor Mutually exclusive with Service

▼ **status** `object`

InterceptorStatus holds the status of the Interceptor

▼ **address** `object`

Address is a single Addressable address. If Addresses is present, Address will be ignored by clients.

▼ **CACerts** `string`

CACerts is the Certification Authority (CA) certificates in PEM format according to https://www.rfc-editor.org/rfc/rfc7468↗.

▼ **audience** `string`

Audience is the OIDC audience for this address.

▼ **name** `string`

Name is the name of the address.

▼ **url** `string`

▼ **addresses** `[]object`

Addressable provides a generic mechanism for a custom resource definition to indicate a destination for message delivery.

Addressable is the schema for the destination information. This is typically stored in the object's `status`, as this information may be generated by the controller.

▼ **CACerts** `string`

CACerts is the Certification Authority (CA) certificates in PEM format according to https://www.rfc-editor.org/rfc/rfc7468↗.

▼ **audience** `string`

Audience is the OIDC audience for this address.

▼ **name** `string`

Name is the name of the address.

▼ **url** `string`

▼ annotations `object`

Annotations is additional Status fields for the Resource to save some additional State as well as convey more information to the user. This is roughly akin to Annotations on any k8s resource, just the reconciler conveying richer information outwards.

▼ conditions `[]object`

Condition defines a readiness condition for a Knative resource. See: https://github.com/kubernetes/community/blob/master/contributors/devel/sig-architecture/api-conventions.md#typical-status-properties ↗

▼ lastTransitionTime `string`

LastTransitionTime is the last time the condition transitioned from one status to another. We use VolatileTime in place of metav1.Time to exclude this from creating equality.Semantic differences (all other things held constant).

▼ message `string`

A human readable message indicating details about the transition.

▼ reason `string`

The reason for the condition's last transition.

▼ severity `string`

Severity with which to treat failures of this type of condition. When this is not specified, it defaults to Error.

▼ status `string` required

Status of the condition, one of True, False, Unknown.

▼ **type** `string` required

Type of condition.

▼ **observedGeneration** `integer`

ObservedGeneration is the 'Generation' of the Service that was last processed by the controller.

集群触发器绑定 [triggers.tekton.dev/v1beta1]

`triggers.tekton.dev` group

ClusterTriggerBinding is a TriggerBinding with a cluster scope. ClusterTriggerBindings are used to represent TriggerBindings that should be publicly addressable from any namespace in the cluster.

`v1alpha1` version

▼ spec `object`

Spec holds the desired state of the ClusterTriggerBinding from the client

▼ params `[]object`

Param defines a string value to be used for a ParamSpec with the same name.

▼ name `string` required

▼ value `string` required

▼ status `object`

TriggerBindingStatus defines the observed state of TriggerBinding.

ClusterTriggerBinding is a TriggerBinding with a cluster scope. ClusterTriggerBindings are used to represent TriggerBindings that should be publicly addressable from any namespace in the cluster.

`v1beta1` version

▼ **spec** `object`

Spec holds the desired state of the ClusterTriggerBinding from the client

▼ **params** `[]object`

Param defines a string value to be used for a ParamSpec with the same name.

▼ **name** `string` required

▼ **value** `string` required

▼ **status** `object`

TriggerBindingStatus defines the observed state of TriggerBinding.

集群拦截器 [triggers.tekton.dev/v1alpha1]

`triggers.tekton.dev` group

ClusterInterceptor describes a pluggable interceptor including configuration such as the fields it accepts and its deployment address. The type is based on the Validating/MutatingWebhookConfiguration types for configuring AdmissionWebhooks

`v1alpha1` version

▼ spec `object` required

ClusterInterceptorSpec describes the Spec for an ClusterInterceptor

▼ clientConfig `object` required

ClientConfig describes how a client can communicate with the Interceptor

▼ caBundle `string`

CaBundle is a PEM encoded CA bundle which will be used to validate the clusterinterceptor server certificate

▼ service `object`

Service is a reference to a Service object where the interceptor is running Mutually exclusive with URL

▼ name `string` required

Name is the name of the service

▼ **namespace** `string` required

Namespace is the namespace of the service

▼ **path** `string`

Path is an optional URL path

▼ **port** `integer`

Port is a valid port number

▼ **url** `string`

URL is a fully formed URL pointing to the interceptor Mutually exclusive with Service

▼ **status** `object`

ClusterInterceptorStatus holds the status of the ClusterInterceptor

▼ **address** `object`

Address is a single Addressable address. If Addresses is present, Address will be ignored by clients.

▼ **CACerts** `string`

CACerts is the Certification Authority (CA) certificates in PEM format according to https://www.rfc-editor.org/rfc/rfc7468↗.

▼ **audience** `string`

Audience is the OIDC audience for this address.

▼ **name** `string`

Name is the name of the address.

▼ **url** `string`

▼ **addresses** `[]object`

Addressable provides a generic mechanism for a custom resource definition to indicate a destination for message delivery.

Addressable is the schema for the destination information. This is typically stored in the object's `status`, as this information may be generated by the controller.

▼ **CACerts** `string`

CACerts is the Certification Authority (CA) certificates in PEM format according to https://www.rfc-editor.org/rfc/rfc7468↗.

▼ **audience** `string`

Audience is the OIDC audience for this address.

▼ **name** `string`

Name is the name of the address.

▼ **url** `string`

▼ annotations `object`

Annotations is additional Status fields for the Resource to save some additional State as well as convey more information to the user. This is roughly akin to Annotations on any k8s resource, just the reconciler conveying richer information outwards.

▼ conditions `[]object`

Condition defines a readiness condition for a Knative resource. See: https://github.com/kubernetes/community/blob/master/contributors/devel/sig-architecture/api-conventions.md#typical-status-properties ↗

▼ lastTransitionTime `string`

LastTransitionTime is the last time the condition transitioned from one status to another. We use VolatileTime in place of metav1.Time to exclude this from creating equality.Semantic differences (all other things held constant).

▼ message `string`

A human readable message indicating details about the transition.

▼ reason `string`

The reason for the condition's last transition.

▼ severity `string`

Severity with which to treat failures of this type of condition. When this is not specified, it defaults to Error.

▼ status `string` required

Status of the condition, one of True, False, Unknown.

▼ **type** `string` required

Type of condition.

▼ **observedGeneration** `integer`

ObservedGeneration is the 'Generation' of the Service that was last processed by the controller.